



Test Report

This test report describes the test results of the below mentioned paragliding harness.

All the tests were carried out by:

Air Turquoise SA, official test laboratory of Switzerland.

para-test.com



paragliding by air turquoise

Standards

Tests were carried out in conformity with the following standards:

- 2. DV LuftGerPV §1, Nr. 7 c (*note: in what follows this will be abbreviated by "LTF")
- European Standard EN1651 September 1999 (*note in what follows this will be abbreviated by "EN")
- European Standard EN12491 September 2001 (*note in what follows this will be abbreviated by "EN12491")

Harness details

Manufacturer:	AIR MKG Kortel Design
Harness model:	Kolibri
Size:	Medium
Harness Weight:	1950 gr.
Maximum certified pilot	100 kg EN / 130 kg LTF
Impact protection type:	Foam
Harness type:	ABS

Test responsible:	Alain Zoller
Test place:	Villeneuve
Test date:	September 30, 2013
Test room temp & humidity:	25,3° C; 54 %rel
Certification number EN:	PH 075.2013
Certification number LTF:	GZ 075.2013

page 1 of 4

Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3



Test summary

A. STRUCTURAL STRENGTH TESTS

A test plan was set up in order to execute the different tests in an efficient order. The table below summarizes this test plan together with the applicable standards and results.

Test ID	TESTED ?	Standard Ref.		TEST setup	Anchoring		Forces		Min. Test duration [sec]	Result
		EN	LTF		Attach - ment points	Dummy	Req. Load in g	Min. force [N]		
1	✓	5.3.2.1		Default flying position	2 main attachment points	Hip fixated	6g	6000	10	OK
2	✓		4.2.1.a				9g	9000		
3	✓	5.3.2.2		Default, landing position	2 main att. points	Hip fixated, landing conf.	6g	6000	10	OK
4	✓		4.2.1.b				15g	15000		
5			4.2.1.a rescue	Rescue	2 rescue att. Pnts.	Hip fixated	9g	9000	10	n/a
6		5.3.2.4					15g	15000		
7			4.2.1.b rescue	Rescue, landing	2 rescue att. Pnts.	Hip fixated, landing conf.	6g	6000	10	n/a
8	✓	5.3.2.3					ONE main att.	1 central hip fixation		
9			4.2.1.d	Towing	2 main att. + 2 tow att.	None	3g	3000	10	n/a
10	✓	5.3.2.5					5g	5000		
11	✓	5.3.2.6		Upside down	2 main att. downw.	Head fix.	4.5g	4500	10	OK
12			4.2.1.c rescue				2 rescue att. downw.	6g		

B. HARNESS PROTECTION SHOCK TEST

Most paraglider harnesses are equipped with a protection device that damps the shock on the pilot’s spine during a hard landing.

Shock impact tests have to be executed on these harnesses in order to prove the damping characteristics of it.





Test ID	TESTED ?	Standar d Ref.:	TEST setup	Anchoring		Impact				Result	
		LTF		Attach- ment points	Dummy	Max. tolerated peak impact in g	Max Peak impact measured	Impact duration of + 38 g (if any) recorded:	Impact duration of + 20 g (if any) recorded:		
PRO TECT 1	✓	5.1.1	Default flying position	Test dummy is attached to the harness like a pilot in flight.			+50g	46.468	0.006	0.017	OK

C. RESCUE DEPLOYMENT RESISTANCE TEST

The deployment of the rescue system has to be ensured in all circumstances of flight. This test is to verify whether the force needed to deploy is in between reasonable limits.

Test ID	TESTED ?	Standar d Ref.	TEST setup	Anchoring		Force for single hand deployment			Result	
		LTF		Attach- ment points	Dummy	Min. force [N]	max. force [N]	Resistance measured [daN]		
Resc depl		6.1.5	Default flying position	Test responsible is attached to the harness like a pilot in flight. (no dummy required)			20 N	70 N	n/t	n/a

D. RESCUE DEPLOYMENT STRAP STRENGTH TEST

The connection between handgrip and inner container has to have sufficient load capacity/structural strength in any situation that may arise during normal use. During this test is verified, whether this connection fulfill the requirements.

Test ID	TESTED ?	Standard Ref.		TEST setup	Minimum force [N]	Min. Test durati on [s]	Breaking resistance measured	Result
		LTF	EN 12491					
Resc strap		6.1.8	5.3.2	Connection strap in tensile testing machine	700N	10	n/t	n/a

After careful examination as explained in above mentioned test reports (from page 2 to page 18), the undersigned persons declare that the harness:

**AIR MKG Kortel Design
Kolibri
Medium**

Complied with:

- **European Standard EN 1651 September 1999**
And / or (if tested)
- **European Standard EN 12491 March 2001**
And / or (if tested)
- **2. DV LuftGerPV §1, Nr. 7 c**

Villeneuve, September 30, 2013

Place, Date



EN & LTP Testing center
www.para-test.com
Alain Zoller

Test responsible

page 4 of 4



Annex: detailed test reports

Harness Test		Test ID 1
Item:	Kolibri	
Manufacturer	AIR MKG Kortel Design	
Test place & date:	Villeneuve	September 30, 2013
Test responsible:	Alain Zoller	
Temp. [°C] & Humidity:	25,3° C; 54 %rel	
Maximum certified pilot weight [kg]:	130	kg
Standard	EN 1651 & 2. DV LuftGerPV §1, Nr. 7 c	
Test standard §:	5.3.2.1 (EN) & 4.2.1 a (LTF DV)	
Test setup:	Default flying position	
Anchoring: Attachment points:	Both main riser attachments (3, 4)	
Dummy:	Default, hip fixed (7, 8)	
Required load in g :	9g	(EN: 6g)
Minimum load [N]:	9000 N	(EN: 6000 N)
Required test load in kg:	1170	kg
Min. duration [s]:	10 s	

Results	
Duration of maintained min. load [s]:	12.1 s
Any signs of structural failure after this test:	No visible failure
Test result:	Passed

Graph:

— TEST ID 1: EN 5.3.2.1 & LTF 4.2.1.a	- - - Norm 600 daN	— norm 900 daN
---------------------------------------	--------------------	----------------

Air Turquoise SA certified by

ISO 9001
BUREAU VERITAS
Certification



Air Turquoise S.A. - Certification of paraglider equipment
Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 1
Prepared by RE
Rev.0, 25.01.2011
No. 71.9.3



Harness Test **Test ID 2**

Item: Kolibri
Manufacturer: AIR MKG Kortel Design
Test place & date: Villeneuve September 30, 2013
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 25,3° C; 54 %rel
Maximum certified pilot weight [kg]: 100 kg

Standard: EN 1651

Test standard §: 5.3.2.2

Test setup: Default flying position

Anchoring: Attachment points: Both main riser attachments (3, 4)


Dummy: Default, hip fixed (7, 8)

Required load in g: 15 g

Min load [N]: 15 000 N

Required test load in kg: **1500** kg

Min. duration [s]: 5s




Results

Duration of maintained min. load [s]: **5.6 s**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 2
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3



Harness Test

Test ID 3

Item:	Kolibri	
Manufacturer	AIR MKG Kortel Design	
Test place & date:	Villeneuve	September 30, 2013
Test responsible:	Alain Zoller	
Temp. [°C] & Humidity:	25,3° C; 54 %rel	
Maximum certified pilot weight [kg]:	130	kg

Standard	2. DV LuftGerPV §1, Nr. 7 c
Test standard §:	4.2.1.b

Test setup: Flying position before landing: seat board (11) in landing position, leg straps (10) closed.

Anchoring: Attachment points: Both of the main riser attachments attached (3 and 4);


Dummy: Default, hip fixed (7, 8)

Required load in g: 6 g

Min load [N]: 6000 N

Required test load in kg: **780** kg

Min. duration [s]: 10 s




Results

Duration of maintained min. load [s]: **11.4 s**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Air Turquoise SA certified by

ISO 9001
BUREAU VERITAS
Certification



Air Turquoise S.A. - Certification of paraglider equipment
Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 3
Prepared by RE
Rev.0, 25.01.2011
No. 71.9.3



Harness Test

Test ID 4

Item: Kolibri
Manufacturer: AIR MKG Kortel Design
Test place & date: Villeneuve September 30, 2013
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 25,3° C; 54 %rel
Maximum certified pilot weight [kg]: 100 kg

Standard: EN 1651

Test standard §: EN 5.3.2.7

Test setup: Flying position before landing: seat board (11) in landing position, leg straps (10) closed.

Anchoring: Attachment points: Both of the main riser attachments attached (3 and 4);


Dummy: Default, hip fixed (7, 8)

Required load in g: 15 g

Min load [N]: 15 000 N

Required test load in kg: **1500 kg**

Min. duration [s]: 5 s




Results

Duration of maintained min. load [s]: **10.4 s**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 4
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3



Harness Test

Test ID 8


Item: Kolibri
 Manufacturer: AIR MKG Kortel Design
 Test place & date: Villeneuve September 30, 2013
 Test responsible: Alain Zoller
 Temp. [°C] & Humidity: 25,3° C; 54 %rel
 Maximum certified pilot weight [kg]: 100 kg

Standard: EN 1651
 Test standard §: 5.3.2.3
 Test setup: Only one riser attached

Anchoring: Attachment points: One main riser attachments (3)

Dummy: Hip fixed (7, 8 -> 12)

Required load in g: 6 g
 Min load [N]: 6 000 N
 Required test load in kg: **600** kg
 Min. duration [s]: 10 s




Results

Duration of maintained min. load [s]: **13.9 s**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 8
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3



Harness Test **Test ID 10**

Item: Kolibri
Manufacturer: AIR MKG Kortel Design
Test place & date: Villeneuve September 30, 2013
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 25,3° C; 54 %rel
Maximum certified pilot weight [kg]: 100 kg

Standard: EN 1651

Test standard §: 5.3.2.6

Test setup: Normal flying position in NEGATIF


Anchoring: Attachment points: ONE of the main riser attachments attached downwards(3 or 4);
Dummy: Dummy anchored at the head position (9)

Required load in g: 4.5 g

Min load [N]: 4500 N

Required test load in kg: **450** kg

Min. duration [s]: 10 s




Results

Duration of maintained min. load [s]: **11.6 s**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 10
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3



Harness Test

Test ID 11

Item:	Kolibri
Manufacturer	AIR MKG Kortel Design
Test place & date:	Villeneuve September 30, 2013
Test responsible:	Alain Zoller
Temp. [°C] & Humidity:	25,3° C; 54 %rel
Maximum certified pilot weight [kg]:	130 kg

Standard 2. DV LuftGerPV §1, Nr. 7 c


Test standard §: 4.2.1.c

Test setup: Pilot upside down flying position

Anchoring: Attachment points: Both of the main riser attachments attached downwards (3 and 4);

Dummy: Dummy anchored at the head position (9)

Required load in g:	6	g
Min load [N]:	6 000 N	
Required test load in kg:	780	kg
Min. duration [s]:	10 s	




Results

Duration of maintained min. load [s]: **11.8 s**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 11
Prepared by RE
Rev.0, 25.01.2011
No. 71.9.3




Protector shock test		Test ID Protect
Item:	Kolibri	
Manufacturer	AIR MKG Kortel Design	
Test place & date:	Villeneuve	September 30, 2013
Test responsible:	Alain Zoller	
Temp. [°C] & Humidity:	25,3° C; 54 %rel	
Maximum certified pilot weight [kg]:	130	kg
Standard	2. DV LuftGerPV §1, Nr. 7 c	
Test standard §:	5.1.1	
Test setup:	<p>Harness attached to protector test dummy, in a similar way like a real pilot in flight.</p> <p>Impact will be simulated by dropping the dummy from a certain height (with and without reserve).</p> <p>To simulate the "in-flight" conditions, the airbag is inflated with pressurized air equalling an airspeed of 7m/s. Inflation has to be stopped at least 5 sec before impact.</p> <p>Impact will be measured by an accelerometer mounted on the dummy. (Impact measured in g's)</p>	
Requirements:	Minimum height:	1.65 m (between lowest point test dummy and impact surface)
	Impact requirements:	+50g as absolute maximum; +38g during less than 7 msec; +20g during less than 25 msec.
	Repetitions:	The test will be performed 2 times, minimum 1 hour and maximum 2 hours after the first impact (with airbag protectors this pause is not necessary). The 2 Max-values should not differ more than 20%
Results		
<u>Shock test 1:</u>		
Impact at a height of 1.65m:	46.468	} $\Delta < 20\% ?$
Impact duration of + 38 g (if any):	0.006	
Impact duration of +20 g (if any):	0.017	
<u>Shock test 2:</u>		
Impact at a height of 1.65m:	49.124	} $\Delta < 20\% ?$
Impact duration of + 38 g (if any):	0.007	
Impact duration of +20 g (if any):	0.018	
Test Result:	Passed	






Graph 1:



Graph 2:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID Protect 1
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3