



Test Report

This test report describes the test results of the below mentioned paragliding harness.

All the tests were carried out by:

Air Turquoise SA, official test laboratory of Switzerland.

para-test.com



paragliding by air turquoise

Standards

Tests were carried out in conformity with the following standards:

- 2. DV LuftGerPV §1, Nr. 7 c (*note: in what follows this will be abbreviated by "LTF")
- European Standard EN1651 September 1999 (*note in what follows this will be abbreviated by "EN")
- European Standard EN12491 September 2001 (*note in what follows this will be abbreviated by "EN12491")

Harness details

Manufacturer:	Gin Gliders
Harness model:	X-Alps
Size:	Medium
Harness Weight:	799 gr
Maximum certified pilot	110 kg
Impact protection type:	NA
Harness type:	ABS
Test responsible:	Alain Zoller
Test place:	Villeneuve
Test date:	May 31, 2013
Test room temp & humidity:	21,4° C; 42 %rel
Certification number EN:	PH 067.2013
Certification number LTF:	GZ 000.0000

page 1 of 4

Air Turquoise SA certified by

ISO 9001
BUREAU VERITAS
Certification



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3



Test summary

A. STRUCTURAL STRENGTH TESTS

A test plan was set up in order to execute the different tests in an efficient order. The table below summarizes this test plan together with the applicable standards and results.

Test ID	TESTED ?	Standard Ref.		TEST setup	Anchoring		Forces		Min. Test duration [sec]	Result
		EN	LTF		Attach - ment points	Dummy	Req. Load in g	Min. force [N]		
1	✓	5.3.2.1		Default flying position	2 main attachment points	Hip fixated	6g	6000	10	OK
2	✓	5.3.2.2	4.2.1.a				9g	9000		
3				Default, landing position	2 main att. points	Hip fixated, landing conf.	6g	6000	10	n/a
4	✓	5.3.2.7	4.2.1.b				15g	15000		
5			4.2.1.a rescue	Rescue	2 rescue att. Pnts.	Hip fixated	9g	9000	10	n/a
6		5.3.2.4					15g	15000		
7			4.2.1.b rescue	Rescue, landing		Hip fixated, landing conf.	6g	6000	10	n/a
8	✓	5.3.2.3		One riser	ONE main att.	1 central hip fixation	6g	6000	10	OK
9			4.2.1.d	Towing	2 main att. + 2 tow att.	None	3g	3000	10	n/a
		5.3.2.5					5g	5000		
10	✓	5.3.2.6		Default, Negatif	One main att.	Head fix.	4.5g	4500	10	OK
11			4.2.1.c	Upside down	2 main att. downw.	Head fix.	6g	6000	10	n/a
12			4.2.1.c rescue	Upside down rescue	2 rescue att. downw.		6g	6000	10	n/a

B. HARNESS PROTECTION SHOCK TEST

Most paraglider harnesses are equipped with a protection device that damps the shock on the pilot's spine during a hard landing.

Shock impact tests have to be executed on these harnesses in order to prove the damping characteristics of it.



Test ID	TESTED ?	Standar d Ref.:	TEST setup	Anchoring		Impact			Result		
		LTF		Attach- ment points	Dummy	Max. tolerated peak impact in g	Max Peak impact measured	Impact duration of + 38 g (if any) recorded:		Impact duration of + 20 g (if any) recorded:	
PRO TECT 1		5.1.1	Default flying position	Test dummy is attached to the harness like a pilot in flight.			+50g	0	0	0	n/a

C. RESCUE DEPLOYMENT RESISTANCE TEST

The deployment of the rescue system has to be ensured in all circumstances of flight. This test is to verify whether the force needed to deploy is in between reasonable limits.

Test ID	TESTED ?	Standar d Ref.	TEST setup	Anchoring		Force for single hand deployment			Result	
		LTF		Attach- ment points	Dummy	Min. force [N]	max. force [N]	Resistance measured [daN]		
Resc depl		6.1.5	Default flying position	Test responsible is attached to the harness like a pilot in flight. (no dummy required)			20 N	70 N	n/t	n/a

D. RESCUE DEPLOYMENT STRAP STRENGTH TEST

The connection between handgrip and inner container has to have sufficient load capacity/structural strength in any situation that may arise during normal use. During this test is verified, whether this connection fulfill the requirements.

Test ID	TESTED ?	Standard Ref.		TEST setup	Minimum force [N]	Min. Test durati on [s]	Breaking resistance measured	Result
		LTF	EN 12491					
Resc strap		6.1.8	5.3.2	Connection strap in tensile testing machine	700N	10	n/t	n/a





After careful examination as explained in above mentioned test reports (from page 2 to page 18), the undersigned persons declare that the harness:

**Gin Gliders
X-Alps
Medium**

Complied with:

- **European Standard EN 1651 September 1999**

And / or (if tested)

- **European Standard EN 12491 March 2001**

And / or (if tested)

- **2. DV LuftGerPV §1, Nr. 7 c**

Villeneuve, May 31, 2013

Place, Date

EN 1651 Testing center
Alain Zoller
www.para-test.com

Test responsible

page 4 of 4



Annex: detailed test reports

Harness Test


Test ID 1

Item: X-Alps
Manufacturer: Gin Gliders
Test place & date: Villeneuve May 31, 2013
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 21,4° C; 42 %rel
Maximum certified pilot weight [kg]: 110 kg

Standard: EN 1651 & 2. DV LuftGerPV §1, Nr. 7 c
Test standard §: 5.3.2.1 (EN) & 4.2.1 a (LTF DV)

Test setup: Default flying position
Anchoring: Attachment points: Both main riser attachments (3, 4)
Dummy: Default, hip fixed (7, 8)

Required load in g : 9g (EN: 6g)
Minimum load [N]: 9000 N (EN: 6000 N)
Required test load in kg: **990 kg**
Min. duration [s]: 10 s




Results

Duration of maintained min. load [s]: **11.9 s**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 1
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3



Harness Test		Test ID 2
Item:	X-Alps	
Manufacturer	Gin Gliders	
Test place & date:	Villeneuve	May 31, 2013
Test responsible:	Alain Zoller	
Temp. [°C] & Humidity:	21,4° C; 42 %rel	
Maximum certified pilot weight [kg]:	110	kg
Standard	EN 1651	
Test standard §:	5.3.2.2	
Test setup:	Default flying position	
Anchoring: Attachment points:	Both main riser attachments (3, 4)	
Dummy:	Default, hip fixed (7, 8)	
Required load in g:	15	g
Min load [N]:	15 000 N	
Required test load in kg:	1650	kg
Min. duration [s]:	5s	

Results	
Duration of maintained min. load [s]:	5.1 s
Any signs of structural failure after this test:	No visible failure
Test result:	Passed

Graph:

— TEST ID 2: EN 5.3.2.2 — Norm 1500 daN

Time (s)	Force (daN) - TEST ID 2	Force (daN) - Norm
5	100	1500
10	300	1500
15	450	1500
20	650	1500
25	900	1500
30	1150	1500
35	1350	1500
40	1600	1500
45	1700	1500
48	1400	1500
50	200	1500

Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 2
Prepared by RE
Rev.0, 25.01.2011
No. 71.9.3

Harness Test

Test ID 4


Item: X-Alps
 Manufacturer: Gin Gliders
 Test place & date: Villeneuve May 31, 2013
 Test responsible: Alain Zoller
 Temp. [°C] & Humidity: 21,4° C; 42 %rel
 Maximum certified pilot weight [kg]: 110 kg

Standard: EN 1651
 Test standard §: EN 5.3.2.7

Test setup: Flying position before landing: seat board (11) in landing position, leg straps (10) closed.

Anchoring: Attachment points: Both of the main riser attachments attached (3 and 4);
 Dummy: Default, hip fixed (7, 8)

Required load in g: 15 g
 Min load [N]: 15 000 N
 Required test load in kg: **1650 kg**
 Min. duration [s]: 5 s




Results

Duration of maintained min. load [s]: **6s**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 4
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3




Harness Test

Test ID 8

Item: X-Alps
 Manufacturer: Gin Gliders
 Test place & date: Villeneuve May 31, 2013
 Test responsible: Alain Zoller
 Temp. [°C] & Humidity: 21,4° C; 42 %rel
 Maximum certified pilot weight [kg]: 110 kg


Standard: EN 1651
 Test standard §: 5.3.2.3
 Test setup: Only one riser attached
 Anchoring: Attachment points: One main riser attachments (3)
 Dummy: Hip fixed (7, 8 -> 12)
 Required load in g: 6 g
 Min load [N]: 6 000 N
 Required test load in kg: **660** kg
 Min. duration [s]: 10 s



Results

Duration of maintained min. load [s]: **10.7s**
 Any signs of structural failure after this test: **No visible failure**
 Test result: **Passed**

Graph:



Air Turquoise SA certified by




Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 8
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3

Harness Test **Test ID 10**

Item: X-Alps
 Manufacturer: Gin Gliders
 Test place & date: Villeneuve May 31, 2013
 Test responsible: Alain Zoller
 Temp. [°C] & Humidity: 21,4° C; 42 %rel
 Maximum certified pilot weight [kg]: 110 kg


Standard: EN 1651
 Test standard §: 5.3.2.6
 Test setup: Normal flying position in NEGATIF
 Anchoring: Attachment points: ONE of the main riser attachments attached downwards(3 or 4);
 Dummy: Dummy anchored at the head position (9)
 Required load in g: 4.5 g
 Min load [N]: 4500 N
 Required test load in kg: **495** kg
 Min. duration [s]: 10 s



Results

Duration of maintained min. load [s]: **12.6s**
 Any signs of structural failure after this test: **No visible failure**
 Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 10
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3