



Test Report

This test report describes the test results of the below mentioned paragliding harness.

All the tests were carried out by:

Air Turquoise SA, official test laboratory of Switzerland.



paragliding by air turquoise

Standards

Tests were carried out in conformity with the following standards:

- NACHRICHTEN FÜR LUFTFAHRER 57 DEZEMBER 2009 **NfL II 91 / 09** (*note: in what follows this will be abbreviated by "LTF")
- European Standard EN1651 September 1999 (*note in what follows this will be abbreviated by "EN")
- European Standard EN12491 September 2001 (*note in what follows this will be abbreviated by "EN12491")

Harness details

Manufacturer:	DUDEK Paragliders S.J.
Harness model / Size:	Powerseat Confort High
SN:	H-02147
Harness Weight:	3.2 kg
Maximum certified pilot weight:	120 kg
Impact protection type:	na
Harness type:	ABS

Test responsible:	Alain Zoller
Test place:	Villeneuve
Test date:	October 16, 2014
Test room temp & humidity:	21,2° C; 55 %rel
Certification number EN:	PH 124.2015
Certification number LTF:	GZ 124.2015

Test summary

A. STRUCTURAL STRENGTH TESTS

A test plan was set up in order to execute the different tests in an efficient order. The table below summarizes this test plan together with the applicable standards and results.

Test ID	TESTED ?	Standard Ref.		TEST setup	Anchoring		Forces		Min. Test duration [sec]	Result
		EN 1651	LTF		Attach - ment points	Dummy	Req. Load in g	Min. force [N]		
1	✓	5.3.2.1	4.2.1.a	Default flying position	2 main attachment points	Hip fixated	6g	6000	10	OK
2	✓	5.3.2.2					9g	9000		
3	✓		4.2.1.b	Default, landing position	2 main att. points	Hip fixated, landing conf.	6g	6000	10	OK
4	✓	5.3.2.7					15g	15000		
5	✓		4.2.1.a rescue	Rescue	2 rescue att. Pnts.	Hip fixated	9g	9000	10	OK
6	✓	5.3.2.4					15g	15000		
7	✓		4.2.1.b rescue	Rescue, landing		Hip fixated, landing conf.	6g	6000	10	OK
8	✓	5.3.2.3		One riser	ONE main att.	1 central hip fixation	6g	6000	10	OK
9		5.3.2.5	4.2.1.d	Towing	2 main att. + 2 tow att.	None	3g 5g	3000 5000	10	n/a
10	✓	5.3.2.6		Default, Negatif	One main att.	Head fix.	4.5g	4500	10	OK
11	✓		4.2.1.c	Upside down	2 main att. downw.	Head fix.	6g	6000	10	OK
12	✓		4.2.1.c rescue	Upside down rescue	2 rescue att. downw.		6g	6000	10	OK

B. HARNESS PROTECTION SHOCK TEST

Most paraglider harnesses are equipped with a protection device that damps the shock on the pilot's spine during a hard landing.

Shock impact tests have to be executed on these harnesses in order to prove the damping characteristics of it.



Test ID	TESTED ?	Standard Ref.:	TEST setup	Anchoring		Impact			Result	
		LTF		Attachment points	Dummy	Max. tolerated peak impact in g	Max Peak impact measured	Impact duration of +38 g (if any) recorded:		Impact duration of +20 g (if any) recorded:
PROTECT 1		5.1.1	Default flying position	Test dummy is attached to the harness like a pilot in flight.		+50g	0	0	0	n/a

C. RESCUE DEPLOYMENT RESISTANCE TEST

The deployment of the rescue system has to be ensured in all circumstances of flight. This test is to verify whether the force needed to deploy is in between reasonable limits.

Test ID	TESTED ?	Standard Ref.	TEST setup	Anchoring		Force for single hand deployment			Result
		LTF		Attachment points	Dummy	Min. force [N]	Max. force [N]	Resistance measured [daN]	
Resc depl	✓	6.1.5	Default flying position	Test responsible is attached to the harness like a pilot in flight. (no dummy required)		20 N	70 N	n/t	OK

D. RESCUE DEPLOYMENT STRAP STRENGTH TEST

The connection between handgrip and inner container has to have sufficient load capacity/structural strength in any situation that may arise during normal use. During this test is verified, whether this connection fulfill the requirements.

Test ID	TESTED ?	Standard Ref.		TEST setup	Minimum force [N]	Min. Test duration [s]	Breaking resistance measured	Result
		LTF	EN 12491					
Resc strap	✓	6.1.8	5.3.2	Connection strap in tensile testing machine	700N	10	n/t	OK



After careful examination as explained in above mentioned test reports (from page 2 to page 18), the undersigned persons declare that the harness:



**DUDEK Paragliders S.J.
Powerseat Confort High
H-02147**

Complied with:

- **European Standard EN 1651 September 1999**
And / or (if tested)
- **European Standard EN 12491 March 2001**
And / or (if tested)
- **NACHRICHTEN FÜR LUFTFAHRER 57 DEZEMBER 2009 nFl II 91 / 09**

Villeneuve, October 16, 2014

Place, Date


EN & LTF Testing center
Alain Zoller 
www.para-test.com

Test responsible



Annex: detailed test reports

Harness Test		Test ID 1
Item:	Powerseat Confort High	
Manufacturer	DUDEK Paragliders S.J.	
Test place & date:	Villeneuve	October 16, 2014
Test responsible:	Alain Zoller	
Temp. [°C] & Humidity:	21,2° C; 55 %rel	
Maximum certified pilot weight [kg]:	120	kg
Standard	EN 1651 & NFL II 91 / 09	
Test standard §:	5.3.2.1 (EN) & 4.2.1 a (LTF DV)	
Test setup:	Default flying position	
Anchoring: Attachment points:	Both main riser attachments (3, 4)	
Dummy:	Default, hip fixed (7, 8)	
Required load in g :	9g	(EN: 6g)
Minimum load [N]:	9000 N	(EN: 6000 N)
Required test load in kg:	1101	kg
Min. duration [s]:	10 s	

Results	
Duration of maintained min. load [s]:	< 10 sec.
Any signs of structural failure after this test:	No visible failure
Test result:	Passed

Graph:

— TEST ID 1: EN 5.3.2.1 & LTF 4.2.1.a
 --- Norm 600 daN
 — norm 900 daN

Time (s)	Force (daN) - TEST ID 1	Norm 600 daN	norm 900 daN
0	0	600	900
10	100	600	900
20	600	600	900
30	900	600	900
40	1050	600	900
50	1100	600	900
55	50	600	900
60	0	600	900



Harness Test

Test ID 2


Item: Powerseat Confort High
Manufacturer: DUDEK Paragliders S.J.
Test place & date: Villeneuve October 16, 2014
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 21,2° C; 55 %rel
Maximum certified pilot weight [kg]: 120 kg

Standard: EN 1651
Test standard §: 5.3.2.2

Test setup: Default flying position
Anchoring: Attachment points: Both main riser attachments (3, 4)

Dummy: Default, hip fixed (7, 8)

Required load in g: 15 g
Min load [N]: 15 000 N
Required test load in kg: **1835 kg**
Min. duration [s]: 5s




Results

Duration of maintained min. load [s]: **< 5 sec.**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:





Harness Test

Test ID 3

Item: Powerseat Confort High
Manufacturer: DUDEK Paragliders S.J.
Test place & date: Villeneuve October 16, 2014
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 21,2° C; 55 %rel
Maximum certified pilot weight [kg]: 120 kg

Standard: NfL II 91 / 09

Test standard §: 4.2.1.b

Test setup: Flying position before landing: seat board (11) in landing position, leg straps (10) closed.

Anchoring: Attachment points: Both of the main riser attachments attached (3 and 4);


Dummy: Default, hip fixed (7, 8)

Required load in g: 6 g

Min load [N]: 6000 N

Required test load in kg: **734 kg**

Min. duration [s]: 10 s




Results

Duration of maintained min. load [s]: **< 10 sec.**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Harness Test

Test ID 4

Item: Powerseat Confort High
Manufacturer: DUDEK Paragliders S.J.
Test place & date: Villeneuve October 16, 2014
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 21,2° C; 55 %rel
Maximum certified pilot weight [kg]: 120 kg

Standard: EN 1651
Test standard §: EN 5.3.2.7

Test setup: Flying position before landing: seat board (11) in landing position, leg straps (10) closed.

Anchoring: Attachment points: Both of the main riser attachments attached (3 and 4);


Dummy: Default, hip fixed (7, 8)

Required load in g: 15 g

Min load [N]: 15 000 N

Required test load in kg: **1835** kg

Min. duration [s]: 5 s




Results

Duration of maintained min. load [s]: **< 5 sec.**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**


Graph:



Harness Test **Test ID 5**

Item: Powerseat Confort High
Manufacturer: DUDEK Paragliders S.J.
Test place & date: Villeneuve October 16, 2014
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 21,2° C; 55 %rel
Maximum certified pilot weight [kg]: 120 kg


Standard: NfL II 91 / 09
Test standard §: 4.2.1.a rescue
Test setup: Rescue attachments
Anchoring: Attachment points: Rescue riser attachments (1,2)
Dummy: Hip fixed (7, 8)
Required load in g: 9 g
Min load [N]: 9 000 N
Required test load in kg: **1101** kg
Min. duration [s]: 10 s



Results

Duration of maintained min. load [s]: **< 10 sec.**
Any signs of structural failure after this test: **No visible failure**
Test result: **Passed**

Graph:





Harness Test


Test ID 6

Item: Powerseat Confort High
Manufacturer: DUDEK Paragliders S.J.
Test place & date: Villeneuve October 16, 2014
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 21,2° C; 55 %rel
Maximum certified pilot weight [kg]: 120 kg

Standard: EN 1651
Test standard §: 5.3.2.4
Test setup: Rescue attachments

Anchoring: Attachment points: Rescue riser attachments (1,2)
Dummy: Hip fixed (7, 8)

Required load in g: 15 g
Min load [N]: 15 000 N
Required test load in kg: **1835 kg**
Min. duration [s]: 5 s




Results

Duration of maintained min. load [s]: **< 5 sec.**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Harness Test

Test ID 7

Item: Powerseat Confort High
Manufacturer: DUDEK Paragliders S.J.
Test place & date: Villeneuve October 16, 2014
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 21,2° C; 55 %rel
Maximum certified pilot weight [kg]: 120 kg

Standard: NfL II 91 / 09

Test standard §: 4.2.1.b rescue

Test setup: Flying position before landing: seat board (11) in landing position, leg straps (10) closed.

Anchoring: Attachment points: Both of the rescue riser attachments attached (1 and 2);


Dummy: Default, hip fixed (7, 8)

Required load in g: 6 g

Min load [N]: 6 000 N

Required test load in kg: **734** kg

Min. duration [s]: 10 s




Results

Duration of maintained min. load [s]: **< 10 sec.**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:





Harness Test

Test ID 8

Item: Powerseat Confort High
Manufacturer: DUDEK Paragliders S.J.
Test place & date: Villeneuve October 16, 2014
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 21,2° C; 55 %rel
Maximum certified pilot weight [kg]: 120 kg

Standard: EN 1651
Test standard §: 5.3.2.3

Test setup: Only one riser attached

Anchoring: Attachment points: One main riser attachments (3)


Dummy: Hip fixed (7, 8 -> 12)

Required load in g: 6 g

Min load [N]: 6 000 N

Required test load in kg: **734 kg**

Min. duration [s]: 10 s




Results

Duration of maintained min. load [s]: **< 10 sec.**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Harness Test

Test ID 10


Item: Powerseat Confort High
Manufacturer: DUDEK Paragliders S.J.
Test place & date: Villeneuve October 16, 2014
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 21,2° C; 55 %rel
Maximum certified pilot weight [kg]: 120 kg

Standard EN 1651

Test standard §: 5.3.2.6

Test setup: Normal flying position in NEGATIF

Anchoring: Attachment points: ONE of the main riser attachments attached downwards(3 or 4);
Dummy: Dummy anchored at the head position (9)



Required load in g: 4.5 g
Min load [N]: 4500 N
Required test load in kg: **550 kg**
Min. duration [s]: 10 s


Results

Duration of maintained min. load [s]: **< 10 sec.**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Harness Test

Test ID 11


Item: Powerseat Confort High
Manufacturer: DUDEK Paragliders S.J.
Test place & date: Villeneuve October 16, 2014
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 21,2° C; 55 %rel
Maximum certified pilot weight [kg]: 120 kg

Standard: NfL II 91 / 09
Test standard §: 4.2.1.c

Test setup: Pilot upside down flying position

Anchoring: Attachment points: Both of the main riser attachments attached downwards (3 and 4);
Dummy: Dummy anchored at the head position (9)

Required load in g: 6 g
Min load [N]: 6 000 N
Required test load in kg: **734** kg
Min. duration [s]: 10 s




Results

Duration of maintained min. load [s]: **< 10 sec.**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Harness Test

Test ID 12

Item: Powerseat Confort High
Manufacturer: DUDEK Paragliders S.J.
Test place & date: Villeneuve October 16, 2014
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 21,2° C; 55 %rel
Maximum certified pilot weight [kg]: 120 kg

Standard: NfL II 91 / 09

Test standard §: 4.2.1.c rescue

Test setup: Pilot upside down flying position

Anchoring: Attachment points: Both of the rescue riser attachments attached downwards (1 and 2);


Dummy: Dummy anchored at the head position (9)

Required load in g: 6 g

Min load [N]: 6 000 N

Required test load in kg: **734** kg

Min. duration [s]: 10 s




Results

Duration of maintained min. load [s]: < 10 sec.

Any signs of structural failure after this test: No visible failure

Test result: Passed

Graph:





Rescue deployment resistance test

Test ID resc

Item: Powerseat Confort High
Manufacturer: DUDEK Paragliders S.J.
Test place & date: Villeneuve October 16, 2014
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 21,2° C; 55 %rel
Maximum certified pilot weight [kg]: 120 kg

Standard: Nfl II 91 / 09

Test standard §: 6.1.5

Test setup:

The deployment of the rescue system has to be ensured in all circumstances, especially with a damaged glider.
 The pilot has to be able to deploy the rescue chute with a single pull out of the outer container, single handed and in an anatomical favorable direction.
 In order to simulate this, the test responsible deploys the rescue seated in the harness. In a similar way as in real flight. The deployment resistance is approximately measured by the load cell, which is placed between the hand of the test responsible and the rescue hand grip.
 On the other hand inadvertent deployment has to be fairly remote. Therefore a shear link has to withstand a minimum load.


Requirements:
Max force for single hand deployment: approx. 70 N
Min force to prevent unwanted opening: approx. 20 N

Results

Measured peak to peak required force for deployment [daN]: 5.1 daN

Comment: Passed

Graph:



Rescue deployment strap strength test

Test ID resc strap

Item: Powerseat Confort High
Manufacturer: DUDEK Paragliders S.J.
Test place & date: Villeneuve October 16, 2014
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 21,2° C; 55 %rel
Maximum certified pilot weight [kg]: 120 kg

Standard EN 12491 & Nfl II 91 / 09

Test standard §: 5.3.2 (EN 12491) & 6.1.8 (LTF)

Test setup: The handgrip of the outer container has to be connected to the inner container with a removable loop in a way that it is possible to use the inner container with different types of outer containers.
 The connection between handgrip and inner container has to have sufficient load capacity/structural strength in any situation that may arise during normal operation.
 In order to verify this, the connection is tested on its tensile strength by a default tensile testing setup.
 In addition to this the breaking resistance will also be measured.

Requirements: **Min. tensile strenght for 10 s:** 700 N (= 70daN)

Results

Duration of maintained load [s]: < 10 sec.

Breaking resistance [daN]: 112.2

Comment: Passed

Graph:

