para-test.com

Ozone Gliders

PG_0612.2012

AIR TURQUOISE SA certified by



Flight test report: EN

Manufacturer

Manulaciulei	Ozone Gilders	Certification number		FG_0012.2012	
Address	2, Queens Drive LA46LN . UK	Date of flight test		07. 08. 2012	
Representative	None	Place of test		Villeneuve	
, Glider model	Ultralite 3 25	Classification		В	
Trimmer	no			_	
mininer	10				
	Test pilot	Fukuoka Seiko		Berruex Gilles	
	Harness	Sup'Air - Altiplume S		Gin Gliders - Gingo 2 L	
	Total weight in flight (kg)	65		110	
1. Inflation/Take-off		Α			
Rising behaviour		Smooth, easy and constant rising	А	Smooth, easy and constant rising	А
Special take off technique	e required	No	А	No	А
2. Landing		Α			
Special landing technique	e required	No	А	No	А
3. Speed in straight flig	ht	В			
Trim speed more than 30) km/h	Yes	А	Yes	А
Speed range using the co	ontrols larger than 10 km/h	Yes	А	Yes	А
Minimum speed		25 km/h to 30 km/h	В	Less than 25 km/h	Α
4. Control movement		Α			
Max. weight in flight up to					
Symmetric control pressu		Increasing / greater than 55 cm	A	not available	0
Max. weight in flight 80 k					
Symmetric control pressure / travel		not available	0	not available	0
Max. weight in flight greater than 100 kg			~	la sus sizes (sus stantle su OF sus	
Symmetric control pressu		not available	0	Increasing / greater than 65 cm	A
5. Pitch stability exiting Dive forward angle on ex	-	A Dive forward less than 30°	۸	Dive forward less than 30°	А
Collapse occurs	it.	No	A	No	A
•	ing controls during accelerated	A	Λ		Λ
Collapse occurs		No	А	No	А
7. Roll stability and dan	nping	Α	7.		~
Oscillations		Reducing	А	Reducing	А
8. Stability in gentle spi	irals	A			
Tendency to return to str		Spontaneous exit	А	Spontaneous exit	А
9. Behaviour in a steep	ly banked turn	В			
Sink rate after two turns		Up to 12 m/s	А	More than 14 m/s	В
10. Symmetric front col	lapse	Α			
Entry		Rocking back less than 45°	А	Rocking back less than 45°	А
Recovery		Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on ex	it / Change of course	Dive forward 0° to 30° / Keeping course	A	Dive forward 0° to 30° / Keeping course	Α
Cascade occurs		No	А	No	А
With accelerator					
Entry		Rocking back less than 45°	А	Rocking back less than 45°	А
Recovery		Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A

Certification number

Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course		Dive forward 0° to 30° / Keeping course	A
Cascade occurs	No	А	No	А
11. Exiting deep stall (parachutal stall)	В			
Deep stall achieved	Yes	А	Yes	А
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit	Dive forward 0° to 30°	А	Dive forward 30° to 60°	В
Change of course	Changing course less than 45°	А	Changing course less than 45°	А
Cascade occurs	No	А	No	А
12. High angle of attack recovery	Α			
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Cascade occurs	No	А	No	А
13. Recovery from a developed full stall	В			
Dive forward angle on exit	Dive forward 0° to 30°	А	Dive forward 30° to 60°	В
Collapse	No collapse	А	No collapse	А
Cascade occurs (other than collapses)	No	А	No	А
Rocking back	Less than 45°	А	Less than 45°	А
Line tension	Most lines tight	А	Most lines tight	А
14. Asymmetric collapse	В			
With 50% collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 0° to 15° $$	A	Less than 90° / Dive or roll angle 0° to 15° $$	A
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No	А	No	А
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
With 75% collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	A	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No	А	No	А
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
With 50% collapse and accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	A	Less than 90° / Dive or roll angle 0° to 15° $$	A
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No	А	No	А
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
With 75% collapse and accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No	А	No	А
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
15. Directional control with a maintained asymmetric collapse	Α			
Able to keep course	Yes	А	Yes	А
180° turn away from the collapsed side possible in 10 s	Yes	A	Yes	Α
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	A	More than 50 % of the symmetric control travel	A

Spin occurs No A No A 17. Low speed spin tendency A A Spin occurs No A No A
Spin occurs No A No A
18. Recovery from a developed spin A
Spin rotation angle after release Stops spinning in less than 90° A Stops spinning in less than 90° A
Cascade occurs No A No A
19. B-line stall A
Change of course before release Changing course less than 45° A Changing course less than 45° A
Behaviour before release Remains stable with straight A Remains stable with straight span A span s
Recovery Spontaneous in less than 3 s A Spontaneous in less than 3 s A
Dive forward angle on exitDive forward 0° to 30°ADive forward 0° to 30°A
Cascade occurs No A No A
20. Big ears A
Entry procedure Standard technique A Standard technique A
Behaviour during big ears Stable flight A Stable flight A
Recovery Spontaneous in less than 3 s A Spontaneous in less than 3 s A
Dive forward angle on exitDive forward 0° to 30°ADive forward 0° to 30°A
21. Big ears in accelerated flight A
Entry procedure Standard technique A Dedicated controls A
Behaviour during big ears Stable flight A Stable flight A
Recovery Spontaneous in less than 3 s A Spontaneous in less than 3 s A
Dive forward angle on exitDive forward 0° to 30°ADive forward 0° to 30°A
Behaviour immediately after releasing the accelerator while Stable flight A Stable flight A maintaining big ears
22. Behaviour exiting a steep spiral A
Tendency to return to straight flight Spontaneous exit A Spontaneous exit A
Turn angle to recover normal flight Less than 720°, spontaneous A Less than 720°, spontaneous A recovery recovery recovery recovery
Sink rate when evaluating spiral stability [m/s] 13 19
23. Alternative means of directional control A
180° turn achievable in 20 sYesAYesA
Stall or spin occurs No A No A
24. Any other flight procedure and/or configuration 0 described in the user's manual
Procedure works as described not available 0 not available 0
Procedure suitable for novice pilots not available 0 not available 0
Cascade occurs not available 0 not available 0
25. Comments of test pilot
Comments