



## Flight test report: EN

|                |  |                       |              |
|----------------|--|-----------------------|--------------|
| Manufacturer   | <b>Sky Country</b>   | Certification number  | PG_0688.2013 |
| Address        | Astronomicheskaya street,<br>27,29<br>61085 Kharkov<br>Ukraine | Date of flight test   | 28. 02. 2013 |
| Representative | None   | Place of test         | Villeneuve   |
| Glider model   | <b>Mystic 3 M</b>  | <b>Classification</b> | <b>C</b>     |
| Trimmer        | no   |                       |              |

|                   |                       |                   |
|-------------------|-----------------------|-------------------|
| <b>Test pilot</b> | Thurnheer Claude      | Zoller Alain      |
| <b>Harness</b>    | Sup'Air - Altiplume M | Sup'Air - Altix M |

**Total weight in flight (kg)** 80 100

|  |   |   |   |   |
|--|---|---|---|---|
| <b>1. Inflation/Take-off</b>   | <b>A</b>                                |   |   |   |
| Rising behaviour   | Smooth, easy and constant rising        | A | Smooth, easy and constant rising        | A |
| Special take off technique required                                    | No                                      | A | No                                      | A |
| <b>2. Landing</b>  | <b>A</b>                                |   |   |   |
| Special landing technique required                                     | No                                      | A | No                                      | A |
| <b>3. Speed in straight flight</b>                                     | <b>B</b>                                |   |   |   |
| Trim speed more than 30 km/h   | Yes                                     | A | Yes                                     | A |
| Speed range using the controls larger than 10 km/h                     | Yes                                     | A | Yes                                     | A |
| Minimum speed  | Less than 25 km/h                       | A | 25 km/h to 30 km/h                      | B |
| <b>4. Control movement</b>   | <b>A</b>                                |   |   |   |
| <i>Max. weight in flight up to 80 kg</i>                               |   |   |   |   |
| Symmetric control pressure / travel                                    | not available                           | 0 | not available                           | 0 |
| <i>Max. weight in flight 80 kg to 100 kg</i>                           |   |   |   |   |
| Symmetric control pressure / travel                                    | Increasing / greater than 60 cm         | A | Increasing / greater than 60 cm         | A |
| <i>Max. weight in flight greater than 100 kg</i>                       |   |   |   |   |
| Symmetric control pressure / travel                                    | not available                           | 0 | not available                           | 0 |
| <b>5. Pitch stability exiting accelerated flight</b>                   | <b>A</b>                                |   |   |   |
| Dive forward angle on exit   | Dive forward less than 30°              | A | Dive forward less than 30°              | A |
| Collapse occurs  | No                                      | A | No                                      | A |
| <b>6. Pitch stability operating controls during accelerated flight</b> | <b>A</b>                                |   |   |   |
| Collapse occurs  | No                                      | A | No                                      | A |
| <b>7. Roll stability and damping</b>                                   | <b>A</b>                                |   |   |   |
| Oscillations   | Reducing                                | A | Reducing                                | A |
| <b>8. Stability in gentle spirals</b>                                  | <b>A</b>                                |   |   |   |
| Tendency to return to straight flight                                  | Spontaneous exit                        | A | Spontaneous exit                        | A |
| <b>9. Behaviour in a steeply banked turn</b>                           | <b>B</b>                                |   |   |   |
| Sink rate after two turns  | More than 14 m/s                        | B | More than 14 m/s                        | B |
| <b>10. Symmetric front collapse</b>                                    | <b>C</b>                                |   |   |   |
| Entry  | Rocking back less than 45°              | A | Rocking back less than 45°              | A |
| Recovery   | Spontaneous in 3 s to 5 s               | B | Spontaneous in 3 s to 5 s               | B |
| Dive forward angle on exit / Change of course                          | Dive forward 0° to 30° / Keeping course | A | Dive forward 0° to 30° / Keeping course | A |
| Cascade occurs   | No                                      | A | No                                      | A |
| <i>With accelerator</i>  |   |   |   |   |
| Entry  | Rocking back greater than 45°           | C | Rocking back greater than 45°           | C |

|  |  |   |  |   |
|--|--|---|--|---|
| Recovery   | Spontaneous in less than 3 s                   | A | Spontaneous in less than 3 s                   | A |
| Dive forward angle on exit / Change of course                            | Dive forward 0° to 30° / Keeping course        | A | Dive forward 30° to 60° / Keeping course       | B |
| Cascade occurs   | No   | A | No   | A |
| <b>11. Exiting deep stall (parachutal stall)</b>                         | <b>A</b>                                       |   |  |   |
| Deep stall achieved  | Yes  | A | Yes  | A |
| Recovery   | Spontaneous in less than 3 s                   | A | Spontaneous in less than 3 s                   | A |
| Dive forward angle on exit   | Dive forward 0° to 30°                         | A | Dive forward 0° to 30°                         | A |
| Change of course   | Changing course less than 45°                  | A | Changing course less than 45°                  | A |
| Cascade occurs   | No   | A | No   | A |
| <b>12. High angle of attack recovery</b>                                 | <b>A</b>                                       |   |  |   |
| Recovery   | Spontaneous in less than 3 s                   | A | Spontaneous in less than 3 s                   | A |
| Cascade occurs   | No   | A | No   | A |
| <b>13. Recovery from a developed full stall</b>                          | <b>A</b>                                       |   |  |   |
| Dive forward angle on exit   | Dive forward 0° to 30°                         | A | Dive forward 0° to 30°                         | A |
| Collapse   | No collapse                                    | A | No collapse                                    | A |
| Cascade occurs (other than collapses)                                    | No   | A | No   | A |
| Rocking back   | Less than 45°                                  | A | Less than 45°                                  | A |
| Line tension   | Most lines tight                               | A | Most lines tight                               | A |
| <b>14. Asymmetric collapse</b>   | <b>C</b>                                       |   |  |   |
| <i>With 50% collapse</i>   |  |   |  |   |
| Change of course until re-inflation / Maximum dive forward or roll angle | Less than 90° / Dive or roll angle 15° to 45°  | A | Less than 90° / Dive or roll angle 0° to 15°   | A |
| Re-inflation behaviour   | Spontaneous re-inflation                       | A | Spontaneous re-inflation                       | A |
| Total change of course   | Less than 360°                                 | A | Less than 360°                                 | A |
| Collapse on the opposite side occurs                                     | No   | A | No   | A |
| Twist occurs   | No   | A | No   | A |
| Cascade occurs   | No   | A | No   | A |
| <i>With 75% collapse</i>   |  |   |  |   |
| Change of course until re-inflation / Maximum dive forward or roll angle | 90° to 180° / Dive or roll angle 45° to 60°    | C | 90° to 180° / Dive or roll angle 45° to 60°    | C |
| Re-inflation behaviour   | Spontaneous re-inflation                       | A | Spontaneous re-inflation                       | A |
| Total change of course   | Less than 360°                                 | A | Less than 360°                                 | A |
| Collapse on the opposite side occurs                                     | No   | A | No   | A |
| Twist occurs   | No   | A | No   | A |
| Cascade occurs   | No   | A | No   | A |
| <i>With 50% collapse and accelerator</i>                                 |  |   |  |   |
| Change of course until re-inflation / Maximum dive forward or roll angle | Less than 90° / Dive or roll angle 15° to 45°  | A | 90° to 180° / Dive or roll angle 15° to 45°    | B |
| Re-inflation behaviour   | Spontaneous re-inflation                       | A | Spontaneous re-inflation                       | A |
| Total change of course   | Less than 360°                                 | A | Less than 360°                                 | A |
| Collapse on the opposite side occurs                                     | No   | A | No   | A |
| Twist occurs   | No   | A | No   | A |
| Cascade occurs   | No   | A | No   | A |
| <i>With 75% collapse and accelerator</i>                                 |  |   |  |   |
| Change of course until re-inflation / Maximum dive forward or roll angle | Less than 90° / Dive or roll angle 45° to 60°  | C | 90° to 180° / Dive or roll angle 60° to 90°    | C |
| Re-inflation behaviour   | Spontaneous re-inflation                       | A | Spontaneous re-inflation                       | A |
| Total change of course   | Less than 360°                                 | A | Less than 360°                                 | A |
| Collapse on the opposite side occurs                                     | Yes, no turn reversal                          | C | No   | A |
| Twist occurs   | No   | A | No   | A |
| Cascade occurs   | No   | A | No   | A |
| <b>15. Directional control with a maintained asymmetric collapse</b>     | <b>A</b>                                       |   |  |   |
| Able to keep course  | Yes  | A | Yes  | A |
| 180° turn away from the collapsed side possible in 10 s                  | Yes  | A | Yes  | A |
| Amount of control range between turn and stall or spin                   | More than 50 % of the symmetric control travel | A | More than 50 % of the symmetric control travel | A |

|   |   |   |  |   |
|---|---|---|--|---|
| <b>16. Trim speed spin tendency</b>   | <b>A</b>  |   |  |   |
| Spin occurs   | No  | A | No   | A |
| <b>17. Low speed spin tendency</b>  | <b>A</b>  |   |  |   |
| Spin occurs   | No  | A | No   | A |
| <b>18. Recovery from a developed spin</b>   | <b>C</b>  |   |  |   |
| Spin rotation angle after release   | Stops spinning in 90° to 180°   | C | Stops spinning in less than 90°                              | A |
| Cascade occurs  | No  | A | No   | A |
| <b>19. B-line stall</b>   | <b>A</b>  |   |  |   |
| Change of course before release   | Changing course less than 45°   | A | Changing course less than 45°                                | A |
| Behaviour before release  | Remains stable with straight span   | A | Remains stable with straight span                            | A |
| Recovery  | Spontaneous in less than 3 s  | A | Spontaneous in less than 3 s                                 | A |
| Dive forward angle on exit  | Dive forward 0° to 30°  | A | Dive forward 0° to 30°                                       | A |
| Cascade occurs  | No  | A | No   | A |
| <b>20. Big ears</b>   | <b>B</b>  |   |  |   |
| Entry procedure   | Standard technique  | A | Dedicated controls   | A |
| Behaviour during big ears   | Stable flight   | A | Stable flight  | A |
| Recovery  | Recovery through pilot action in less than a further 3 s                          | B | Recovery through pilot action in less than a further 3 s     | B |
| Dive forward angle on exit  | Dive forward 0° to 30°  | A | Dive forward 0° to 30°                                       | A |
| <b>21. Big ears in accelerated flight</b>   | <b>B</b>  |   |  |   |
| Entry procedure   | Standard technique  | A | Dedicated controls   | A |
| Behaviour during big ears   | Stable flight   | A | Stable flight  | A |
| Recovery  | Recovery through pilot action in less than a further 3 s                          | B | Recovery through pilot action in less than a further 3 s     | B |
| Dive forward angle on exit  | Dive forward 0° to 30°  | A | Dive forward 0° to 30°                                       | A |
| Behaviour immediately after releasing the accelerator while maintaining big ears          | Stable flight   | A | Stable flight  | A |
| <b>22. Behaviour exiting a steep spiral</b>   | <b>A</b>  |   |  |   |
| Tendency to return to straight flight   | Spontaneous exit  | A | Spontaneous exit   | A |
| Turn angle to recover normal flight   | Less than 720°, spontaneous recovery  | A | Less than 720°, spontaneous recovery                         | A |
| Sink rate when evaluating spiral stability [m/s]  | 19  |   | 19   |   |
| <b>23. Alternative means of directional control</b>                                       | <b>A</b>  |   |  |   |
| 180° turn achievable in 20 s  | Yes   | A | Yes  | A |
| Stall or spin occurs  | No  | A | No   | A |
| <b>24. Any other flight procedure and/or configuration described in the user's manual</b> | <b>0</b>  |   |  |   |
| Procedure works as described  | not available   | 0 | not available  | 0 |
| Procedure suitable for novice pilots  | not available   | 0 | not available  | 0 |
| Cascade occurs  | not available   | 0 | not available  | 0 |
| <b>25. Comments of test pilot</b>   |   |   |  |   |
| Comments  | Symmetrischer Frontklapper und einseitiger Klapper wurden mit Faltleinen getestet |   | Tested with "Folding Lines" for front & asymmetric collapses |   |