Villeneuve



AIR TURQUOISE SA certified by

Flight test report: EN



Manufacturer	Ozone Gliders	Certification number	PG_0779.2013
Address	2, Queens Drive LA46LN . UK	Date of flight test	24. 04. 2014

Place of test

paragliding by air turquoise

Glider model Mantra M6 ML Classification D

David Dagault

Trimmer

Representative

Test pilot	Thurnheer Claude		Berruex Gilles	
Harness	Niviuk Gliders - Hamak 2 M		Sup' Air - Altix M	
Total weight in flight (kg)			105	
1. Inflation/Take-off	C			
Rising behaviour	Overshoots, shall be slowed	С	Overshoots, shall be slowed down	С
	down to avoid a front collapse		to avoid a front collapse	
Special take off technique required	No	Α	No	Α
2. Landing	Α			
Special landing technique required	No	Α	No	Α
3. Speed in straight flight	В			
Trim speed more than 30 km/h	Yes	Α	Yes	Α
Speed range using the controls larger than 10 km/h	Yes	Α	Yes	Α
Minimum speed	25 km/h to 30 km/h	В	Less than 25 km/h	Α
4. Control movement	С			
Max. weight in flight up to 80 kg				
Symmetric control pressure / travel	not available	0	not available	0
Max. weight in flight 80 kg to 100 kg				
Symmetric control pressure / travel	Increasing / 45 cm to 60 cm	С	not available	0
Max. weight in flight greater than 100 kg				
Symmetric control pressure / travel	not available	0	Increasing / 50 cm to 65 cm	С
5. Pitch stability exiting accelerated flight	Α			
Dive forward angle on exit	Dive forward less than 30°	Α	Dive forward less than 30°	Α
Collapse occurs	No	Α	No	Α
6. Pitch stability operating controls during accelerated flight	Α			
Collapse occurs	No	Α	No	Α
7. Roll stability and damping	Α			
Oscillations	Reducing	Α	Reducing	Α
8. Stability in gentle spirals	Α			
Tendency to return to straight flight	Spontaneous exit	Α	Spontaneous exit	Α
9. Behaviour in a steeply banked turn	В			
Sink rate after two turns	More than 14 m/s	В	More than 14 m/s	В
10. Symmetric front collapse	D			
Entry	Rocking back less than 45°	Α	Rocking back less than 45°	Α
Recovery	Recovery through pilot action in less than a further 3 s	D	Recovery through pilot action in less than a further 3 s	D
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 30° to 60° / Keeping course	В
Cascade occurs	No	Α	No	Α
With accelerator				
Entry	Rocking back greater than 45°	С	Rocking back less than 45°	Α

Recovery	Spontaneous in 3 s to 5 s	В	Recovery through pilot action in less than a further 3 s	D
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 30° to 60° / Keeping course	В
Cascade occurs	No	Α	No	Α
11. Exiting deep stall (parachutal stall)	A			
Deep stall achieved	Yes	Α	Yes	Α
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Change of course	Changing course less than 45°	Α	Changing course less than 45°	Α
Cascade occurs	No	Α	No	Α
12. High angle of attack recovery	A			
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Cascade occurs	No	Α	No	Α
13. Recovery from a developed full stall	A			
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Collapse	No collapse	Α	No collapse	Α
Cascade occurs (other than collapses)	No	Α	No	Α
Rocking back	Less than 45°	Α	Less than 45°	Α
Line tension	Most lines tight	Α	Most lines tight	Α
14. Asymmetric collapse	D			
With 50% collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	Less than 90° / Dive or roll angle 0° to 15°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No	Α	No	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
With 75% collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 45° to 60°	С	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No	Α	No	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
With 50% collapse and accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	Less than 90° / Dive or roll angle 15° to 45°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No	Α	No	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
With 75% collapse and accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 45° to 60°	С	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	Α	Inflates in 3 s to 5 s from start of pilot action	D
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No	Α	No	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
15. Directional control with a maintained asymmetric collapse	A			
Able to keep course	Yes	Α	Yes	Α
180° turn away from the collapsed side possible in 10 s	Yes	Α	Yes	Α

Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	Α	More than 50 % of the symmetric control travel	Α
16. Trim speed spin tendency	Α			
Spin occurs	No	Α	No	Α
17. Low speed spin tendency	A			
Spin occurs	No	Α	No	Α
18. Recovery from a developed spin	С			
Spin rotation angle after release	Stops spinning in 90° to 180°	С	Stops spinning in less than 90°	Α
Cascade occurs	No	Α	No	Α
19. B-line stall	0			
Change of course before release	not available	0	not available	0
Behaviour before release	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit	not available	0	not available	0
Cascade occurs	not available	0	not available	0
20. Big ears	В			
Entry procedure	Dedicated controls	Α	Dedicated controls	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Recovery through pilot action in less than a further 3 s	В	Recovery through pilot action in less than a further 3 s	В
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
21. Big ears in accelerated flight	В			
Entry procedure	Dedicated controls	Α	Dedicated controls	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Recovery through pilot action in less than a further 3 s	В	Recovery through pilot action in less than a further 3 s	В
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	Α	Stable flight	Α
22. Behaviour exiting a steep spiral	Α			
Tendency to return to straight flight	Spontaneous exit	Α	Spontaneous exit	Α
Turn angle to recover normal flight	Less than 720°, spontaneous recovery	Α	Less than 720°, spontaneous recovery	Α
Sink rate when evaluating spiral stability [m/s]	19		17	
23. Alternative means of directional control	A			
180° turn achievable in 20 s	Yes	Α	Yes	Α
Stall or spin occurs	No	Α	No	Α
24. Any other flight procedure and/or configuration described in the user's manual	0			
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0
25. Comments of test pilot				
Comments	In Übereinstimmung mit der Betriebsanleitung ist ein B-Stall nicht empfohlen		According to the user manual, a B-Stall is not recommended	