

Flight test report: EN 926-2:2013

Address Francisco Rodríguez, 7 / PO Box 269 33200 Date of flight test 31. 07. 2014 Gilder model Ball 28 Classification B Serial number 90462100 Representative None Trimmer no Place of test Villeneuve Test pilot Thurnheer Claude Berruex Gilles Niviuk - Hamak L Harness Niviuk - Stank M Niviuk - Hamak L Hamak L Harness to risers distance (cm) 44 44 B Distance between risers (cm) 44 B required B Speal Inding technique required No No No B Speal Inding technique required No A No A Spead Inding technique required No A No A Spead Inding technique required No A Yes A Spead Instright	Manufacturer	Windtech Paragliders	Certification number		PG_0873.2014	
Serial number 90462100 Representative None Trimmer no Place of test Villeneuve Test pilot Function of test Berruex Gilles Harness Harness Niviuk - Hamak M Niviuk - Hamak L Harness to risers of com 44 44 Distance between risers (cm) 44 48 Total weight in filight (b) 90 110 1. Inflation/Take-off B Easy rising, some pilot required A Special take off technique required No A No A Special take off technique required No A No A Special lake off technique required No A No A Special lake off technique required No A No A Special lake off technique required No A No A Special instraight filight - No A No A Special take off technique required No A No A Special lake off technique required No A No A Special lake off technique required No A Special law Special law Specin straight filight A S		Francisco Rodríguez, 7 / PO Box 269 33280 33201 GIJON - Asturias			—	
Timmer no Place of test Villeneuve Test pilot Thurnheer Claude Berruex Gilles Harness Niviuk - Hamak M Niviuk - Hamak L Harness to risers distance (cm) 44 44 Distance between risers (cm) 44 48 Total weight in flight (kg) 90 10 1. Inflation/Take-off B Easy rising, some plot correction is required B Special take off technique required No No No A Special take off technique required No No A No A Special take off technique required No No No A A Special take off technique required No A No A Special take off technique required No A No A Special take off technique required No A No A Special take off technique required No A No A Special take off technique required No A No A Special take off technique required No No	Glider model	Bali 28	Classification		В	
Test pilotThurnheer ClaudeBerruex GillesHarnessNiviuk - Hamak MNiviuk - Hamak LHarness to risers distance (cm)4444Distance between risers (cm)4448Total weight in flight (kg)901101. Inflation/Tak-offBEasy rising, some pilot correction isRising behaviourBEasy rising, some pilot correction is required2. LandingANoASpecial take off technique requiredNoANo3. Special is weight flightAYesASpecial landing technique requiredNoANoASpecial landing technique requiredNoANoASpecial landing technique requiredNoANoASpecial landing technique requiredNoANoASpecial is weight flightAYesASpecial stace off technique requiredASpecial is weight flightYesAYesASpecial is weight flight bp 08 08Symmetric control pressure / travelIncreasing / greater than 60 cmAMax. weight in flight greater than 100 km/hLess than 25 km/hASymmetric control pressure / travelnot availableIncreasing / greater than 60 cmAMax. weight in flight greater than 100 kgNoNoASymmetric control pressure / travelNoANoACollapse occursNoANoAACollapse occursNo <td>Serial number</td> <td>90462100</td> <td>Representative</td> <td></td> <td>None</td> <td></td>	Serial number	90462100	Representative		None	
HarnessNiviuk - Hamak MNiviuk - Hamak LHarness to risers distance (cm)4444Distance between risers (cm)4448Distance between risers (cm)90101.Inflation/Tak-offBEasy rising, some pilot correction is requiredBSpecial take off technique requiredNoANoASpecial instraight flightAYesAYesASpecial instraight flightYesAYesAASpecial regues take off technique requiredNoAYesAASpecial regues take off technique requiredNoNoAAAAControl regues take off technique requiredNoNo <td>Trimmer</td> <td>no</td> <td>Place of test</td> <td></td> <td>Villeneuve</td> <td></td>	Trimmer	no	Place of test		Villeneuve	
Harness to risers distance (cm)4444Distance between risers (cm)4448Total weight in flight (kg)90101. Inflation/Take-offBEasy rising, some pilot correction is requiredBSpecial take off technique requiredNoNoNoASpecial take off technique requiredNoNoNoA2. LandingASpecial landing technique requiredNoNoNoA3. Special instraight flightATrim speed more than 30 km/hYesAYesASpecial range using the controls larger than 10 km/hYesAYesA4. Control movementAYesAYesAMax. weight in flight up 08 0KgSymmetric control pressure / travelnot available0Increasing / greater than 60 cmADive forward less than 10 km/hYesAnot available0A. Sees than 25 km/hALess than 25 km/hALess than 25 km/hASymmetric control pressure / travelnot available0Increasing / greater than 60 cmADive forward less than 10 km/hYesAnot available0A. Sees than 25 km/hALess than 25 km/hALess than 25 km/hASymmetric control pressure / travelnot available0Increasing / greater than 65 cmADive forward less than 30° (reasing / greater	Test pilot		Thurnheer Claude		Berruex Gilles	
Distance between risers (cm)4448Total weight in flight (kg)901101. Inflation/Take-offBEasy rising, some pilot correction is requiredBRising behaviourEasy rising, some pilot correction is requiredNoANoASpecial take off technique requiredNoANoAA2. LandingATTTTTSpecial inding technique requiredNoANoAA3. Special instraight flightATTTTTTA. Special instraight flightATTT	Harness		Niviuk - Hamak M		Niviuk - Hamak L	
Total weight in flight (kg)901101. Inflation/Take-offBEasy rising, some pilot correction is requiredBRising behaviourEasy rising, some pilot correction is requiredNoANoASpecial take off technique requiredNoANoAA2. LandingANoANoASpecial take off technique requiredNoANoAA2. Special take off technique requiredANoAASpecial take off technique requiredASpecial take off technique requiredASpecial take off technique requiredASpecial take off technique requiredASpecial take off technique requiredAYesAYesASpecial take off technique requiredEasy than 25 km/hAYesASpecial take off technique requiredAYesAYesAA control pressure / travelnot availableOnot availableOIot availableAMax. weight in flight 80 kg to 100 kgNoANoAAColapse take off the ANoAS	Harness to risers	distance (cm)	44		44	
1. Inflation/Take-off B Rising behaviour Easy rising, some pilot correction is required B Easy rising, some pilot correction is required B Special take off technique required No A No A Special landing technique required A A No A Special landing technique required A A No A Special landing technique required A A A A Special landing technique required A A A A Special landing technique required A A A A A Special landing technique required A A Yes A A Special landing technique required Less than 25 km/h A Less than 25 km/h A Less than 25 km/h A Less than 25 km/h A <td< td=""><td>Distance between</td><td>risers (cm)</td><td>44</td><td></td><td>48</td><td></td></td<>	Distance between	risers (cm)	44		48	
Rising behaviourEasy rising, some pilot correction is requiredBEasy rising, some pilot correction is requiredBSpecial take off technique requiredNoANoA2. LandingASpecial landing technique requiredNoANoA3. Speed in straight flightATrim speed more than 30 km/hYesAYesASpeed range using the controls larger than 10 km/hYesAYesA4. Control movementAMar. weight in flight up to 80 kgSymedric control pressure / travelnot available0not available0not available0Max. weight in flight gb to 100 kgSymmetric control pressure / travelnot available0Increasing / greater than 60 cmASymmetric control pressure / travelnot available0Increasing / greater than 65 cmASymmetric control pressure / travelnot available0Increasing / greater than 30°ANoACollapse occursNoANoANoACollapse occursNoANoANoA <td< td=""><td>Total weight in flig</td><td>Jht (kg)</td><td>90</td><td></td><td>110</td><td></td></td<>	Total weight in flig	Jht (kg)	90		110	
Correction is requiredrequiredSpecial take off bednique requiredNoANoASpecial landing bednique requiredNoANoA3. Speed in straight flightATTTrim speed more than 30 km/hYesAYesASpeed range using the controls larger than 10 km/hYesAYesASpeed range using the controls larger than 10 km/hYesAYesA4. Control movementAYesAYesAMax. weight in flight up to 80 kgTTTTSymmetric control pressure / travelnot available0not available0Max. weight in flight greater than 100 kgTTTTSymmetric control pressure / travelnot available0Increasing / greater than 60 cmAMax. weight in flight greater than 100 kgTTTTSymmetric control pressure / travelnot available0Increasing / greater than 65 cmAOkie forward less than 30°ANoNoANoDive forward less than 30°ANoACollapse occursNoACollapse occursNoAReducingATTCollapse occursNoAReducingAACollapse occursAA. Toti stability operating controls during accelerated flightATTTCollapse occursNoAReducingA <td>1. Inflation/Take-off</td> <td></td> <td>В</td> <td></td> <td></td> <td></td>	1. Inflation/Take-off		В			
2. LandingASpecial landing technique requiredNoANoA3. Speed in straight flightAASpeed range using the controls larger than 10 km/hYesAYesASpeed range using the controls larger than 10 km/hYesAYes stan 25 km/hALess than 25 km/hA4. Control movementACess than 25 km/hALess than 25 km/hAA4. Control movementAAVesASpeed range using the controls barger than 60 kgTTMax. weight in flight up to 80 kgTTTTTSymmetric control pressure / travelnot available0not availableDMax. weight in flight greater than 100 kgTTTTSymmetric control pressure / travelnot available0Increasing / greater than 60 cmANoADive forward lage on exitDive forward less than 30°ANoNoANoACollapse occursNoANoANoARA. Tot stability operating controls during accelerated flightANoAAACollapse occursNoANoANoAAA. Stability in greater straight flightAASpontaneous exitAAA. Stability in greater straight flightAASpontaneous exit (g force decreasing, rate of turnASpontaneous exit (g force decreasing, rate of turn <t< td=""><td>-</td><td></td><td>correction is required</td><td>В</td><td>required</td><td>В</td></t<>	-		correction is required	В	required	В
Special anding technique requiredNoANoA3. Speed in straight flightAFTrim speed more than 30 km/hYesAYesASpeed range using the controls larger than 10 km/hYesAYesAA. Control movementALess than 25 km/hALess than 25 km/hAA. Control movementAFFFFMax. weight in flight up to 80 kgnot available0not available0Max. weight in flight op to 80 kgIncreasing / greater than 60 cmAnot available0Max. weight in flight geater than 100 kgIncreasing / greater than 60 cmAnot available0Max. weight in flight geater than 100 kgIncreasing / greater than 60 cmAnot available0Symmetric control pressure / travelnot available0Increasing / greater than 60 cmASymmetric control pressure / travelnot available0Increasing / greater than 60 cmASymmetric control pressure / travelNoANoAACollapse occursNoANoAACollapse occursNoANoAACollapse occursReducingAReducingANoAStability and dampingReducingASpontaneous exitAAStability in gente spiralsAImmediate reduction of rate of turmAStability in gente spiralsASpontaneous exit <td></td> <td>ie required</td> <td></td> <td>А</td> <td>No</td> <td>А</td>		ie required		А	No	А
3. Speed in straight flightATrim speed more than 30 km/hYesAYesASpeed range using the controls larger than 10 km/hYesAYesAMinimum speedLess than 25 km/hALess than 25 km/hA4. Control movementALess than 25 km/hALess than 25 km/hAMax. weight in flight up to 80 kgnot available0not availableDMax. weight in flight 20 to 80 kgnot available0not availableDMax. weight in flight 80 kg to 100 kgstart and the start and the s	-			_		
Trim speed more than 30 km/hYesAYesASpeed range using the controls larger than 10 km/hYesAYesAMinimum speedLess than 25 km/hALess than 25 km/hA4. Control movementAAMax. weight in flight up to 80 kgsymmetric control pressure / travelnot available0not available0Max. weight in flight 80 kg to 100 kgsymmetric control pressure / travelIncreasing / greater than 60 cmAnot available0Max. weight in flight greater than 100 kgsymmetric control pressure / travelnot available0Increasing / greater than 60 cmASymmetric control pressure / travelnot available0Increasing / greater than 65 cmASymmetric control pressure / travelnot available0Increasing / greater than 65 cmASymmetric control pressure / travelNot available0Increasing / greater than 65 cmASymmetric control pressure / travelNoANoAASymmetric control pressure / travelNoANoAASym				A	No	A
Speed range using the controls larger than 10 km/hYesAYesAMinimum speedLess than 25 km/hALess than 25 km/hA4. Control movementAMax. weight in flight up to 80 kgnot available0not available0Max. weight in flight 00 kg to 100 kgnot available0not available0Symmetric control pressure / travelIncreasing / greater than 60 cmAnot available0Max. weight in flight greater than 100 kgIncreasing / greater than 60 cmAnot available0Symmetric control pressure / travelnot available0Increasing / greater than 65 cmASymmetric control pressure / travelnot available0Increasing / greater than 65 cmASymmetric control pressure / travelNot available0Increasing / greater than 65 cmASymmetric control pressure / travelNot available0Increasing / greater than 65 cmACollapse occursNoANoAACollapse occursNoANoAACollapse occursNoANoAACollapse occursNoANoAACollapse occursNoANoAACollapse occursNoANoAASublity in gentle spiralsASpontaneous exitAASublity in gentle spiralsAInmediate reduction of rate of turnASub				۸	Vee	۸
Minimum speedLess than 25 km/hALess than 25 km/hA4. Control movementAMax. weight in flight up to 80 kgSymmetric control pressure / travelnot available0Max. weight in flight 80 kg to 100 kgSymmetric control pressure / travelIncreasing / greater than 60 cmAnot available0Max. weight in flight greater than 100 kgSymmetric control pressure / travelnot available0not available0Max. weight in flight greater than 100 kgSymmetric control pressure / travelnot available0not available10Symmetric control pressure / travelnot available0not available10Symmetric control pressure / travelNot available0101010Symmetric control pressure / travelNot available01010101010Symmetric control pressure / travelNot available01						
4. Control movementAMax. weight in flight up to 80 kgNot available0not available0Symmetric control pressure / travelnot available0not available0Max. weight in flight 80 kg to 100 kgIncreasing / greater than 60 cmAnot available0Max. weight in flight greater than 100 kgIncreasing / greater than 60 cmAnot available0Max. weight in flight greater than 100 kgIncreasing / greater than 60 cmANot available0Max. weight in flight greater than 100 kgIncreasing / greater than 60 cmADive forward less than 30°ASymmetric control pressure / travelnot available0Increasing / greater than 65 cmASymmetric control pressure / travelNoADive forward less than 30°ASymteritic control pressure / travelNoANoACollapse occursNoANoACollapse occursNoANoACollapse occursNoANoACollapse occursNoANoACollapse occursReducingASpontaneous exitAStability in gentle spiralsASpontaneous exitASpontaneous exitStability in gentle spiralsASpontaneous exit (g force decreasing, rate of turn decreasing, rate						
Symmetric control pressure / travelnot available0not available0Max. weight in flight 80 kg to 100 kgIncreasing / greater than 60 cmAnot available0Symmetric control pressure / travelIncreasing / greater than 60 cmAnot available0Max. weight in flight greater than 100 kgnot available0Increasing / greater than 65 cmASymmetric control pressure / travelnot available0Increasing / greater than 65 cmA5. Pitch stability exiting accelerated flightAVVDive forward angle on exitDive forward less than 30°ADive forward less than 30°ACollapse occursNoANoA6. Pitch stability operating controls during accelerated flightANoACollapse occursNoANoA6. Stability and damping OscillationsAReducingAReducingA8. Stability in gentle spiralsANoANoA9. Behaviour exiting a fully developed spiral dive Initial response of glider (first 180°)Immediate reduction of rate of turn decreasing, rate of furm decreasing, rate of furm decreasing, rate of furm decreasing, rate of furm decreasing, rate of furm decreasing	•					
Max. weight in flight 80 kg to 100 kg Increasing / greater than 60 cm A not available 0 Symmetric control pressure / travel Increasing / greater than 60 cm A not available 0 Max. weight in flight greater than 100 kg Symmetric control pressure / travel not available 0 Increasing / greater than 65 cm A Symmetric control pressure / travel not available 0 Increasing / greater than 65 cm A Si Pitch stability exiting accelerated flight A Vertex of the stability accelerated flight A Dive forward less than 30° A Collapse occurs No A No A No A Symmetric controls during accelerated flight A No A No A Collapse occurs No A No A A Collapse occurs A Collapse occurs No A No A A A A Collapse occurs A Reducing A No A A Socillations Reducing A Reducing A A Stability in gentle sp	Max. weight in flight up	o to 80 kg				
Symmetric control pressure / travelIncreasing / greater than 60 cmAnot available0Max. weight in flight greater than 100 kgnot available0Increasing / greater than 65 cmASymmetric control pressure / travelnot available0Increasing / greater than 65 cmA5. Pitch stability exiting accelerated flightADive forward angle on exitDive forward less than 30°ADive forward less than 30°ACollapse occursNoANoA6. Pitch stability operating controls during accelerated flightACollapse occursNoANoA6. Pitch stability and damping OscillationsANoANo7. Roll stability in gentle spiralsAAMeducingA8. Stability in gentle spiralsAAMeducing a fully developed spiral dive furmAMeducing a fully developed spiral dive furmA9. Behaviour exiting a fully developed spiral dive Initial response of glider (first 180°)Immediate reduction of rate of furm decreasing, rate of furmASpontaneous exit (g force decreasing, rate of furmA	Symmetric control press	ure / travel	not available	0	not available	0
Max. weight in flight greater than 100 kgSymmetric control pressure / travelnot available0Increasing / greater than 65 cmA5. Pitch stability exiting accelerated flightAADive forward angle on exitDive forward less than 30°ADive forward less than 30°ACollapse occursNoANoA6. Pitch stability operating controls during accelerated flightANoACollapse occursNoANoA6. Pitch stability and dampingANoAAOscillationsReducingAReducingA8. Stability in gentle spiralsASpontaneous exitASpontaneous exit9. Behaviour exiting a fully developed spiral dive Initial response of glider (first 180°)Immediate reduction of rate of turnASpontaneous exit (g force decreasing, rate of turnASpontaneous exit (g force decreasing, rate of turnASpontaneous exit (g force decreasing, rate of turnA	Max. weight in flight 80) kg to 100 kg				
Symmetric control pressure / travelnot available0Increasing / greater than 65 cmA5. Pitch stability exiting accelerated flightADive forward angle on exitDive forward less than 30°ADive forward less than 30°ACollapse occursNoANoA6. Pitch stability operating controls during accelerated flightANoACollapse occursNoANoACollapse occursNoANoAStability and dampingAReducingAStability in gentle spiralsAReducingATendency to return to straight flightAAStability in gentle spiral diveAImmediate reduction of rate of turnStability in gentle spiral flightAAStability in gentle spiral flight </td <td>Symmetric control press</td> <td>ure / travel</td> <td>Increasing / greater than 60 cm</td> <td>A</td> <td>not available</td> <td>0</td>	Symmetric control press	ure / travel	Increasing / greater than 60 cm	A	not available	0
5. Pitch stability exiting accelerated flightADive forward angle on exitDive forward less than 30°ADive forward less than 30°ACollapse occursNoANoA6. Pitch stability operating controls during accelerated flightAANoACollapse occursNoANoA6. Pitch stability and dampingAANoA7. Roll stability and dampingAReducingAReducingA0scillationsReducingAReducingAA8. Stability in gentle spiralsASpontaneous exitASpontaneous exitA9. Behaviour exiting a fully developed spiral dive Initial response of glider (first 180°)Immediate reduction of rate of turnASpontaneous exit (g force decreasing, rate of turn decreasing)ASpontaneous exit (g force decreasing, rate of turn decreasing)A		-				
Dive forward angle on exitDive forward less than 30°ADive forward less than 30°ACollapse occursNoANoA6. Pitch stability operating controls during accelerated flightASubsectionACollapse occursNoANoA7. Roll stability and dampingAKeducingAReducingAOscillationsReducingAReducingAStability in gentle spiralsA8. Stability in gentle spiralsASpontaneous exitASpontaneous exitA9. Behaviour exiting a fully developed spiral dive Initial response of glider (first 180°)Immediate reduction of rate of turnAImmediate reduction of rate of turnATendency to return to straight flightSpontaneous exit (g force decreasing, rate of turn decreasing)ASpontaneous exit (g force decreasing, rate of turn decreasing)A				0	Increasing / greater than 65 cm	A
Collapse occursNoANoA6. Pitch stability operating controls during accelerated flightA <td< td=""><td>-</td><td></td><td></td><td>^</td><td>Dive ferward less then 20°</td><td>^</td></td<>	-			^	Dive ferward less then 20°	^
6. Pitch stability operating controls during accelerated flightACollapse occursNoANoA7. Roll stability and dampingAOscillationsReducingAReducingA8. Stability in gentle spiralsATendency to return to straight flightSpontaneous exitASpontaneous exit9. Behaviour exiting a fully developed spiral dive Initial response of glider (first 180°)Immediate reduction of rate of turnAImmediate reduction of rate of turnATendency to return to straight flightSpontaneous exit (g force decreasing, rate of turn decreasing)ASpontaneous exit (g force decreasing, rate of turn decreasing)A	-	xit				
Collapse occursNoANoA7. Roll stability and dampingAAFeducingAOscillationsReducingAReducingA8. Stability in gentle spiralsAFeducingATendency to return to straight flightSpontaneous exitASpontaneous exit9. Behaviour exiting a fully developed spiral diveAImmediate reduction of rate of furnAInitial response of glider (first 180°)Immediate reduction of rate of furnASpontaneous exit (g force decreasing, rate of furn decreasing)A	6. Pitch stability opera	ting controls during accelerated		A	NU	A
7. Roll stability and dampingAOscillationsReducingAReducingA8. Stability in gentle spiralsAASpontaneous exitA7. Endency to return to straight flightSpontaneous exitASpontaneous exitA9. Behaviour exiting a fully developed spiral diveAImmediate reduction of rate of turnAInitial response of glider (first 180°)Immediate reduction of rate of turnAImmediate reduction of rate of turnATendency to return to straight flightSpontaneous exit (g force decreasing, rate of turn decreasing)ASpontaneous exit (g force decreasing, rate of turn decreasing)A	-		No	А	No	А
OscillationsReducingAReducingA8. Stability in gentle spiralsATendency to return to straight flightSpontaneous exitASpontaneous exitA9. Behaviour exiting a fully developed spiral diveAImmediate reduction of rate of turnAImmediate reduction of rate of turnA1nitial response of glider (first 180°)Immediate reduction of rate of turnASpontaneous exit (g force decreasing, rate of turnATendency to return to straight flightSpontaneous exit (g force decreasing, rate of turnASpontaneous exit (g force decreasing, rate of turn decreasing)A		mping				
Tendency to return to straight flightSpontaneous exitASpontaneous exitA9. Behaviour exiting a fully developed spiral diveAImmediate reduction of rate of turnAImmediate reduction of rate of turnAInitial response of glider (first 180°)Immediate reduction of rate of turnAImmediate reduction of rate of turnATendency to return to straight flightSpontaneous exit (g force decreasing, rate of turnASpontaneous exit (g force decreasing, rate of turnA	-		Reducing	А	Reducing	А
9. Behaviour exiting a fully developed spiral dive A Initial response of glider (first 180°) Immediate reduction of rate of turn A Tendency to return to straight flight Spontaneous exit (g force decreasing, rate of turn A Spontaneous exit (g force decreasing, rate of turn A	8. Stability in gentle sp	irals	Α			
Initial response of glider (first 180°)Immediate reduction of rate of turnAImmediate reduction of rate of turnATendency to return to straight flightSpontaneous exit (g force decreasing, rate of turnASpontaneous exit (g force decreasing, rate of turnA	Tendency to return to str	raight flight	Spontaneous exit	А	Spontaneous exit	А
turn Tendency to return to straight flight Spontaneous exit (g force decreasing, rate of turn A Spontaneous exit (g force decreasing, rate of turn decreasing) A						
decreasing, rate of turn decreasing, rate of turn decreasing)			turn	A		A
	Tendency to return to st	raight flight	decreasing, rate of turn	A		A

Turn angle to recover normal flight	Less than 720°, spontaneous recovery	A	Less than 720°, spontaneous recovery	A
10. Symmetric front collapse	В			
Approximately 30 % chord				
Entry	Rocking back less than 45°	А	Rocking back less than 45°	А
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit Change of course	Dive forward 0° to 30° Keeping course	A	Dive forward 0° to 30° Keeping course	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
At least 50% chord				
Entry	Rocking back less than 45°	А	Rocking back less than 45°	А
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit / Change of course	Dive forward 30° to 60° / Entering a turn of less than 90°	В	Dive forward 30° to 60° / Keeping course	В
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
With accelerator Entry	Rocking back less than 45°	А	Rocking back less than 45°	А
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit / Change of course	Dive forward 30° to 60° /	В	Dive forward 30° to 60° / Keeping	В
	Keeping course		course	
Cascade occurs	No	A	No	A
Folding lines used	No A	A	No	A
11. Exiting deep stall (parachutal stall) Deep stall achieved	Yes	А	Yes	А
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Change of course	Changing course less than 45°	A	Changing course less than 45°	A
Cascade occurs	No	A	No	A
12. High angle of attack recovery	A	~		~
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Cascade occurs	No	A	No	A
13. Recovery from a developed full stall	В			
Dive forward angle on exit	Dive forward 0° to 30°	А	Dive forward 30° to 60°	в
Collapse	No collapse	А	No collapse	А
Cascade occurs (other than collapses)	No	А	No	А
Rocking back	Less than 45°	А	Less than 45°	А
Line tension	Most lines tight	А	Most lines tight	А
14. Asymmetric collapse	В			
Small asymmetric collapse	Loss than 00° / Divo or roll or ri-	^	$1 \cos t \cos 0.0^{\circ} / Divo \cos \cos 0.0^{\circ}$	۸
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	A	Less than 90° / Dive or roll angle 0° to 15°	A
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of	А	No (or only a small number of	А
	collapsed cells with a spontaneous reinflation)		collapsed cells with a spontaneous reinflation)	
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	A	No	A
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А

Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	A	No	A
		~		Λ
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	Less than 90° / Dive or roll angle 15° to 45°	A
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	A
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
Large asymmetric collapse with fully activated accelerator		-		-
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	A
Total change of course	Less than 360°	Α	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
15. Directional control with a maintained asymmetric	Α			
	Vaa	^	Vaa	•
Able to keep course	Yes	A	Yes	A
180° turn away from the collapsed side possible in 10 s	Yes	A	Yes	A
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	A	More than 50 % of the symmetric control travel	A
16. Trim speed spin tendency	Α			
Spin occurs	No	Α	No	А
17. Low speed spin tendency	Α			
Spin occurs	No	А	No	А
18. Recovery from a developed spin	Α			
Spin rotation angle after release	Stops spinning in less than 90°	Α	Stops spinning in less than 90°	А
Cascade occurs	No	А	No	А
19. B-line stall	Α			
Change of course before release	Changing course less than 45°	А	Changing course less than 45°	А
Behaviour before release	Remains stable with straight span	А	Remains stable with straight span	A
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit	Dive forward 0° to 30°	А	Dive forward 0° to 30°	А
Cascade occurs	No	A	No	A
20. Big ears	A			
Entry procedure	Dedicated controls	А	Dedicated controls	А
Behaviour during big ears	Stable flight	A	Stable flight	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
21. Big ears in accelerated flight	A	7		~
Entry procedure	A Dedicated controls	А	Dedicated controls	А
			Stable flight	
Behaviour during big ears	Stable flight	A		A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A

А
Α
0
0
0

24. Comments of test pilot

Comments