

Flight test report: EN 926-2:2013

i light test i ej	5011. EN 520-2.2010				
Manufacturer	Niviuk Gliders / Air Games S.L.	Certification number		PG_0929.2015	
Address	C. Del Ter, 6 – Nave D 17165 La Cellera de Ter Girona Spain	Date of flight test		30. 10. 2014	
Glider model	Artik P 25	Classification		С	
Serial number	Artik 4 9-25 Light	Representative		None	
Trimmer	no	Place of test		Villeneuve	
Test pilot		Thurnheer Claude		Zoller Alain	
Harness		Supair - Altiplume S		Flugsau - XX-Lite	
Harness to risers distance (cm)		44		41	
Distance between risers (cm)		40		44	
Total weight in flight (kg)		75		95	
1. Inflation/Take-off		Α			
Rising behaviour		Smooth, easy and constant rising	А	Smooth, easy and constant rising	А
Special take off technique required		No	А	No	А
2. Landing		Α			
Special landing technique required		No	А	No	А
3. Speed in straight flight		В			
Trim speed more than 30 km/h		Yes	A	Yes	A
Speed range using the controls larger than 10 km/h		Yes	A	Yes	A
Minimum speed 4. Control movement		Less than 25 km/h A	A	25 km/h to 30 km/h	В
	<				
Max. weight in flight up to 80 kg		Increasing / greater than 55 cm	٨	not available	0
Symmetric control pressure / travel		increasing / greater than 55 cm	A		0
Max. weight in flight 80 kg to 100 kg					
Symmetric control pressure / travel		not available	0	Increasing / greater than 60 cm	A
Max. weight in flight gr	eater than 100 kg				
Symmetric control press		not available	0	not available	0
5. Pitch stability exiting	-	Α			
Dive forward angle on ex	<i>k</i> it	Dive forward less than 30°	A	Dive forward less than 30°	A
	ing controls during accelerated	No A	A	No	A
flight Collapse occurs		No	А	No	А
7. Roll stability and dar	nping	A	11		73
Oscillations		Reducing	А	Reducing	А
8. Stability in gentle sp	irals	A		5	
Tendency to return to straight flight		Spontaneous exit	А	Spontaneous exit	А
9. Behaviour exiting a fully developed spiral dive		Α			
Initial response of glider	(first 180°)	Immediate reduction of rate of turn	A	Immediate reduction of rate of turn	A
Tendency to return to str	aight flight	Spontaneous exit (g force decreasing, rate of turn decreasing)	A	Spontaneous exit (g force decreasing, rate of turn decreasing)	A

Turn angle to recover normal flight	Less than 720°, spontaneous recovery	A	Less than 720°, spontaneous recovery	A
10. Symmetric front collapse	В			
Approximately 30 % chord				
Entry	Rocking back less than 45°	А	Rocking back less than 45°	А
Recovery	Spontaneous in 3 s to 5 s	В	Spontaneous in less than 3 s	А
Dive forward angle on exit Change of course	Dive forward 0° to 30° Keeping course	A	Dive forward 0° to 30° Keeping course	Α
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
At least 50% chord				
Entry	Rocking back less than 45°	А	Rocking back less than 45°	А
Recovery	Spontaneous in 3 s to 5 s	В	Spontaneous in less than 3 s	A
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	A	Dive forward 0° to 30° / Keeping course	A
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
-				
With accelerator				
Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Spontaneous in 3 s to 5 s	В	Spontaneous in less than 3 s	A
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	A	Dive forward 0° to 30° / Keeping course	A
Cascade occurs	No	A	No	A
Folding lines used	No	A	No	A
11. Exiting deep stall (parachutal stall) Deep stall achieved	A Yes	А	Yes	А
· ·				A
Recovery Dive forward angle on exit	Spontaneous in less than 3 s Dive forward 0° to 30°	A A	Spontaneous in less than 3 s Dive forward 0° to 30°	A
Change of course	Changing course less than 45°	A	Changing course less than 45°	A
Cascade occurs	No	A	No	A
12. High angle of attack recovery	A	~	NO	~
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Cascade occurs	No	A	No	A
13. Recovery from a developed full stall	A			
Dive forward angle on exit	Dive forward 0° to 30°	А	Dive forward 0° to 30°	А
Collapse	No collapse	А	No collapse	А
Cascade occurs (other than collapses)	No	А	No	А
Rocking back	Less than 45°	А	Less than 45°	А
Line tension	Most lines tight	А	Most lines tight	А
14. Asymmetric collapse	С		-	
Small asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 0° to 15°	A	Less than 90° / Dive or roll angle 0° to 15°	A
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	A	No	A
Folding lines used	No	A	No	A
Large asymmetric collapse	00° to 100° / Divo or roll arals	P	00° to 190° / Divo or roll anala 45°	~
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	90° to 180° / Dive or roll angle 45° to 60°	C
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	A
Total change of course	Less than 360°	A	Less than 360°	A

Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
Ĵ				
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	A	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	A
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
Large asymmetric collapse with fully activated accelerator		_		-
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 45° to 60°	С	90° to 180° / Dive or roll angle 45° to 60°	С
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	A
Total change of course	Less than 360°	А	Less than 360°	A
Collapse on the opposite side occurs	Yes, no turn reversal	С	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
15. Directional control with a maintained asymmetric collapse	Α			
Able to keep course	Yes	А	Yes	А
180° turn away from the collapsed side possible in 10 s	Yes	А	Yes	А
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	A	More than 50 % of the symmetric control travel	A
16. Trim speed spin tendency	Α			
Spin occurs	No	Α	No	A
17. Low speed spin tendency	Α			
Spin occurs	No	А	No	А
18. Recovery from a developed spin	Α			
Spin rotation angle after release	Stops spinning in less than 90°	А	Stops spinning in less than 90°	A
Cascade occurs	No	Α	No	A
19. B-line stall	A	_		
Change of course before release	Changing course less than 45°	A	Changing course less than 45°	A
Behaviour before release	Remains stable with straight span	A	Remains stable with straight span	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Cascade occurs	No	A	No	A
20. Big ears	B		-	
Entry procedure	Dedicated controls	A	Dedicated controls	A
Behaviour during big ears	Stable flight	A	Stable flight	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in 3 s to 5 s	B
Dive forward angle on exit	Dive forward 0° to 30°	А	Dive forward 0° to 30°	А
04 Discours in accelerated flight				
21. Big ears in accelerated flight	В	۸	Dedicated control-	^
Entry procedure	B Dedicated controls	A	Dedicated controls	A
Entry procedure Behaviour during big ears	B Dedicated controls Stable flight	А	Stable flight	А
Entry procedure	B Dedicated controls			
Entry procedure Behaviour during big ears	B Dedicated controls Stable flight	А	Stable flight Recovery through pilot action in	А

А
Α
0
0
0

24. Comments of test pilot

Comments