

## Flight test report: EN 926-2:2013

	Manufacturer Address	ADVANCE Thun AG Uttigenstrasse 87	Certification number Date of flight test		PG_0980.2015 21. 09. 2015	
		3600 Thun Switzerland				
	Glider model	Pi 2 27	Classification		В	
	Serial number	64246	Representative		Kari Eisenhut	
	Trimmer	no	Place of test		Villeneuve	
	Test pilot		Thurnheer Claude		Zoller Alain	
	Harness		Sup' Air - Altiplume M		Gin Gliders - Gingo 2 L	
	Harness to risers dis	stance (cm)	43		43	
	Distance between risers (cm)		40		46	
	Total weight in flight (kg)		75		120	
	1. Inflation/Take-off		Α			
	Rising behaviour		Smooth, easy and constant rising	А	Smooth, easy and constant rising	А
	Special take off technique required		No		No	А
	2. Landing		Α			
	Special landing technique required		No	А	No	А
	3. Speed in straight flight		Α			
	Trim speed more than 30 km/h		Yes	А	Yes	А
	Speed range using the controls larger than 10 km/h		Yes	A	Yes	А
	Minimum speed		Less than 25 km/h	А	Less than 25 km/h	A
	4. Control movement		Α			
	Max. weight in flight up to	o 80 kg				
	Symmetric control pressure / travel		Increasing / greater than 55 cm	Α	not available	0
	Max. weight in flight 80 kg	g to 100 kg				
	Symmetric control pressure	-	not available	0	not available	0
	Max. weight in flight grea	ter than 100 kg				
	Symmetric control pressure		not available	0	Increasing / greater than 65 cm	А
	5. Pitch stability exiting accelerated flight		Α			
	Dive forward angle on exit		Dive forward less than $30^\circ$	А	Dive forward less than 30°	А
	Collapse occurs		No	А	No	А
	6. Pitch stability operating flight	g controls during accelerated	Α			
	Collapse occurs		No	А	No	А
	7. Roll stability and damp	ing	Α			
	Oscillations		Reducing	А	Reducing	А
	8. Stability in gentle spira	ls	Α			
	Tendency to return to straig	· •	Spontaneous exit	A	Spontaneous exit	A
	9. Behaviour exiting a fully developed spiral dive		<b>A</b>			
	Initial response of glider (fir	st 180°)	Immediate reduction of rate of turn	A	Immediate reduction of rate of turn	A
	Tendency to return to straig	jht flight	Spontaneous exit (g force decreasing, rate of turn decreasing)	A	Spontaneous exit (g force decreasing, rate of turn decreasing)	A
	Turn angle to recover norm	al flight	Less than 720°, spontaneous recovery	A	Less than 720°, spontaneous recovery	А

## 10. Symmetric front collapse

## Α

Approximately 30 % chord		•		•
Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit Change of course	Dive forward 0° to 30° Keeping course	A	Dive forward 0° to 30° Keeping course	A
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
At least 50% chord				
Entry	Rocking back less than 45°	А	Rocking back less than 45°	А
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	A	Dive forward 0° to 30° / Keeping course	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
C C				
With accelerator				
Entry	Rocking back less than 45°	А	Rocking back less than 45°	А
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	A	Dive forward 0° to 30° / Keeping course	A
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
11. Exiting deep stall (parachutal stall)	А			
Deep stall achieved	Yes	А	Yes	А
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit	Dive forward 0° to 30°	А	Dive forward 0° to 30°	А
Change of course	Changing course less than $45^\circ$	А	Changing course less than 45°	А
Cascade occurs	No	А	No	А
12. High angle of attack recovery	Α			
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	А
Cascade occurs	No	А	No	A
13. Recovery from a developed full stall	В			_
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 30° to 60°	В
Collapse	No collapse	A	No collapse	A
Cascade occurs (other than collapses)	No	Α	No	A
Rocking back	Less than 45°	A	Less than 45°	A
Line tension	Most lines tight	Α	Most lines tight	A
14. Asymmetric collapse	В			
Small asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	Less than 90° / Dive or roll angle 0° to 15° $$	А
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of	А	No (or only a small number of	А
	collapsed cells with a spontaneous reinflation)		collapsed cells with a spontaneous reinflation)	
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or				
roll angle	Less than 90° / Dive or roll angle 15° to 45°	A	90° to 180° / Dive or roll angle 15° to 45°	В
roll angle Re-inflation behaviour		A A		B
-	15° to 45°		to 45°	

Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	Α	No	A
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	A	Less than 90° / Dive or roll angle 15° to 45°	A
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle $15^\circ$ to $45^\circ$	A	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
15. Directional control with a maintained asymmetric collapse	Α			
Able to keep course	Yes	А	Yes	А
180° turn away from the collapsed side possible in 10 s	Yes	А	Yes	А
Amount of control range between turn and stall or spin	More than 50 % of the	А	More than 50 % of the symmetric	А
	symmetric control travel		control travel	
16. Trim speed spin tendency	A			
Spin occurs	No	A	No	A
17. Low speed spin tendency	A	•	Ne	
Spin occurs	No	A	No	A
18. Recovery from a developed spin	A			
Spin rotation angle after release	Stops spinning in less than 90°	A	Stops spinning in less than 90°	A
Cascade occurs	No	A	No	A
19. B-line stall	A Changing course loss than 45°	٨	Changing pourse loss there 45°	٨
Change of course before release	Changing course less than 45°	A	Changing course less than 45°	A
Behaviour before release	Remains stable with straight span	A	Remains stable with straight span	A
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit	Dive forward 0° to 30°	А	Dive forward 30° to 60°	А
Cascade occurs	No	А	No	А
20. Big ears	Α			
Entry procedure	Dedicated controls	А	Dedicated controls	А
Behaviour during big ears	Stable flight	А	Stable flight	А
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit	Dive forward 0° to 30°	А	Dive forward 0° to 30°	А
21. Big ears in accelerated flight	Α			
Entry procedure	Dedicated controls	А	Dedicated controls	А
Behaviour during big ears	Stable flight	А	Stable flight	А
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit	Dive forward 0° to 30°	А	Dive forward 0° to 30°	А

А
Α
0
0
0

24. Comments of test pilot

Comments