## AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Comte 8 🔺 CH-1844 Villeneuve 🔺 +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes

no

yes

Trimmer

Folding lines used



С

Α

Α

Villeneuve

Spontaneous exit

Immediate reduction of rate of turn

## Flight test report: EN 926-2:2013 & LTF 91/09

Manufacturer Address	Ozone Gliders 2, Queens Drive LA46LN . UK	Certification number Date of flight test	PG_1048.2016 23. 05. 2016
Glider model	LM6 S	Classification	D
Serial number	PR13-R-04A-004	Representative	None

Test pilot	Dupont Philippe	Thurnheer Claude
Harness	Sky Paragliders - Reverse 2 S	Niviuk - Hamak M
Harness to risers distance (cm)	43	43
Distance between viscos (aux)	40	4.4

Distance between risers (cm)	40		44
Total weight in flight (kg)	70		85
1. Inflation/Take-off	С		
Rising behaviour	Overshoots, shall be slowed down to avoid a front collapse	С	Overshoots, shall be slowed down to avoid a front collapse
Special take off technique required	No	Α	No
2. Landing	Α		

Place of test

Special landing technique required	No	Α	NO	Α
3. Speed in straight flight	В			
Trim speed more than 30 km/h	Yes	Α	Yes	Α
Speed range using the controls larger than 10 km/h	Yes	Α	Yes	Α
Minimum speed	Less than 25 km/h	Α	25 km/h to 30 km/h	В

;
;

Tendency to return to straight flight

Initial response of glider (first 180°)

9. Behaviour exiting a fully developed spiral dive

Max. weight in flight up to 80 kg Symmetric control pressure / travel	Increasing / 40 cm to 55 cm	С	not available	0
Max. weight in flight 80 kg to 100 kg				
Symmetric control pressure / travel	not available	0	Increasing / 45 cm to 60 cm	С
Max. weight in flight greater than 100 kg				
Symmetric control pressure / travel	not available	0	not available	0
5. Pitch stability exiting accelerated flight	A			
Dive forward angle on exit	Dive forward less than 30°	Α	Dive forward less than 30°	Α
Collapse occurs	No	Α	No	Α
6. Pitch stability operating controls during accelerated flight	Α			
Collapse occurs	No	Α	No	Α
7. Roll stability and damping	A			
Oscillations	Reducing	Α	Reducing	Α
8. Stability in gentle spirals	A			

Spontaneous exit

D

turn

Tendency to return to straight flight	Turn remains constant (g force constant, rate of turn constant)	D	Turn remains constant (g force constant, rate of turn constant)	D	

Immediate reduction of rate of

Turn angle to recover normal flight	With pilot action	D	With pilot action	D
10. Symmetric front collapse	D	D	With phot action	D
To. Symmouro from Conapso				
Approximately 30 % chord				
Entry	Rocking back less than 45°	Α	Rocking back less than 45°	Α
Recovery	Spontaneous in less than 3 s	Α	Recovery through pilot action in less than a further 3 s	D
Dive forward angle on exit Change of course	Dive forward 0° to 30° Keeping course	Α	Dive forward 0° to 30° Keeping course	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes		Yes	
A4 In a 4 500/ a harri				
At least 50% chord	Dealing healthee than 45°	^	Danking hank lang than 45°	^
Entry	Rocking back less than 45°	Α	Rocking back less than 45°	A
Recovery	Recovery through pilot action in less than a further 3 s	D	Recovery through pilot action in less than a further 3 s	D
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes		Yes	
Ç				
With accelerator				
Entry	Rocking back less than 45°	Α	Rocking back less than 45°	Α
Recovery	Recovery through pilot action in less than a further 3 s	D	Spontaneous in 3 s to 5 s	В
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes		Yes	
11. Exiting deep stall (parachutal stall)	A			
Deep stall achieved	Yes	Α	Yes	Α
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Change of course	Changing course less than 45°	Α	Changing course less than 45°	Α
Cascade occurs	No	Α	No	Α
12. High angle of attack recovery	A			
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Cascade occurs	No	Α	No	Α
13. Recovery from a developed full stall	A			
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Collapse	No collapse	Α	No collapse	Α
Cascade occurs (other than collapses)	No	Α	No	Α
Rocking back	Less than 45°	Α	Less than 45°	Α
Line tension	Most lines tight	Α	Most lines tight	Α
14. Asymmetric collapse	С			
Small asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or	Less than 90° / Dive or roll angle	Α	Less than 90° / Dive or roll angle 0°	Α
roll angle	0° to 15°		to 15°	
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	A
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes		Yes	
Large asymmetric collapse	0001 1000151	_	0001 100015: " "	_
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 45° to 60°	С	90° to 180° / Dive or roll angle 15° to 45°	В
<b>5</b> -			-	

Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of	Α	No (or only a small number of	A
Collapse of the opposite side occurs	collapsed cells with a spontaneous reinflation)	^	collapsed cells with a spontaneous reinflation)	^
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes		Yes	
Small asymmetric collapse with fully activated accelerator Change of course until re-inflation / Maximum dive forward or	Loop than 00° / Divo or roll angle	۸	Loop than 00° / Divo or roll angle	٨
roll angle	Less than 90° / Dive or roll angle 15° to 45°		Less than 90° / Dive or roll angle 15° to 45°	Α .
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes		Yes	
Large seymmetric colleges with fully activated appelarator				
Large asymmetric collapse with fully activated accelerator Change of course until re-inflation / Maximum dive forward or		_	Long than 00° / Divo or roll angle	C
roll angle	90° to 180° / Dive or roll angle 45° to 60°	С	Less than 90° / Dive or roll angle 45° to 60°	С
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes		Yes	
15. Directional control with a maintained asymmetric collapse	Α			
Able to keep course	Yes	Α	Yes	Α
180° turn away from the collapsed side possible in 10 s	Yes	Α	Yes	Α
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	Α	More than 50 % of the symmetric control travel	Α
16. Trim speed spin tendency	A			
Spin occurs	No	Α	No	Α
17. Low speed spin tendency	A			
Spin occurs	No	Α	No	Α
18. Recovery from a developed spin	D			
Spin rotation angle after release	Stops spinning in less than 90°	Α	Stops spinning in 180° to 360°	D
Cascade occurs	No	Α	No	Α
19. B-line stall	0			
Change of course before release	not available	0	not available	0
Behaviour before release	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit	not available	0	not available	0
Cascade occurs	not available	0	not available	0
20. Big ears	B			
Entry procedure	Dedicated controls	A	Dedicated controls	A
Behaviour during big ears	Stable flight	Α	Stable flight	A
Recovery	Spontaneous in 3 s to 5 s	В	Spontaneous in 3 s to 5 s	В
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
21. Big ears in accelerated flight	B Dedicated controls	Λ	Dedicated controls	^
Entry procedure	Dedicated controls Stable flight	A	Dedicated controls Stable flight	A A
Behaviour during big ears		Α	STADIE MODE	
Pagayany			· · · · · · · · · · · · · · · · · · ·	
Recovery	Recovery through pilot action in less than a further 3 s	В	Recovery through pilot action in less than a further 3 s	В

Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	Α	Stable flight	Α
22. Alternative means of directional control	Α			
180° turn achievable in 20 s	Yes	Α	Yes	Α
Stall or spin occurs	No	Α	No	Α
23. Any other flight procedure and/or configuration described in the user's manual	0			
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0

## 24. Comments of test pilot

Comments