

Flight and Load test report

Manufacturer GIN GLIDERS Inc.
Address 285-1 Galdam-Ri, Mohyun-Myun,
 onglIn-City, yunggi-Do
 449-855 Korea

Type/model: Yeti Cross M
Total weight in flight: 104 kg


Description of tests	place:	date:	result:
1. Deployment system strength test A load of 700 N between each components	Villeneuve	15.09.2013	OK
2. Speed of opening test - ref. A (2 times) Time from the instant of free drop until a load of 200 N is sustained Opening time Opening time	Villeneuve	18.02.2013 24.02.2013	2.92 sec 3.28 sec
3. Descent rate and stability test - ref. A and B (2 times) The paraglider is released as the parachute begins to open, minimum 100 m descent. Stability 1 Sink rate 1 Stability 2 Sink rate 2	Villeneuve	18.02.2013 24.02.2013 18.02.2013 24.02.2013	Stable 5.03 m/sec Stable 4.87 m/sec
4. Strength test 40 m/s opening shock (2 times) The drop test device is accelerated to a straight line velocity of 40 m/s. Speed of opening is less than 5 seconds and shock not exceeded 15g Test 1 Test 2	Illarsaz	06.08.2013 14.08.2013	OK OK
5. Interaction and stability test (piloted) - ref. C a the emergency parachute is deployed from a paraglider in normal straight flight. b the pilot shall take no action while the behaviour of the parachute and paraglider are observed 200 metres. c the pilot take action while the behaviour of the parachute and paraglider are observed 200 metres.			not available not available not available

The model described is in conformity with some points of the standard EN 12491:2001



Air Turquoise SA
 Route du Pré-au-Comte 8
 Case postale 10
 CH- 1844 Villeneuve
 email: info@para-test.com

For Air Turquoise SA

testing center
 Alain Zoller

 www.para-test.com

ISO 9001
 BUREAU VERITAS
 Certification



homepage: www.para-test.com

Weather data, ref. 3 and B

Date / place	hPa	wind	temp	humidity
Villeneuve, February 18, 2013	964	1	4.5°	72.0%
	Corrected mass:	102.69 kg		
Villeneuve, February 24, 2013	966	2	4.5°	73.0%
	Corrected mass:	102.90 kg		

Reference

A. At horizontal airspeed 8 m/s and vertical speed 1.5 m/s

B. Formula to be used for correcting the test mass ofr differences from ICAO standard atmosphere

$$m_{corr} := m_{dec} \cdot \frac{p \cdot T_0}{p_0 \cdot T}$$

Ground level atmospheric pressure at the test location: (p)

ICAO standard atmospheric pressure at MSL: (p₀)

Ground level température at the test location: (T)

ICAO standard temperature at MSL: (T₀)

Total weight in flight: (m_{dec})

Corrected mass: (m_{corr})

C. Only parachute with controls for steering and landing flare



Air Turquoise SA

Route du Pré-au-Comte 8
Case postale 10
CH - 1844 Villeneuve
Switzerland
mobile: +41 79 202 52 30
Tel. no : +41 21 965 65 65
fax : +41 219 65 65 68
email: info@para-test.com
homepage: www.para-test.com

For Air Turquoise SA



EN 9125 Testing center
Alain Zoller
www.para-test.com

