

INSPECTION REPORT

PARAGLIDERS RESCUE SYSTEMS | EMERGENCY PARACHUTE

Inspection report number: **EP_098.2015**

SAMPLE DATA

Manufacturer name: **Supair Sàrl**
 Representative: **Laurent Chiabaut**
 Street: **34, rue Adrastée**
 Post code / place: **74650 Chavanod**
 Country: **France**
 Model name: **Fluid**
 Model size: **M**
 Manufacturer max load [kg]: **100**
 Manufacturers serial number flight (EP1, EP2, EP4, EP6): **PDAP-FL-M-09M**
 Manufacturers serial number load (EP3, EP5): **PDAP-FL-M-10M**
 Volum [cm3]: **3782**
 Date of reception: **07.01.2014**
 Date of reception: **07.01.2014**
 Date of issue: **27.10.2015**
 Place of declaration: **Villeneuve**
 Director management: **Alain Zoller**

Signature:

Air Turquoise SA, having thoroughly assessed the sample mentioned hereunder, declare it was found conform with all requirements defined by the following directives:

EN 12491 | 2001 and LTF NFL II 91/09 chapter 6 Paraglider rescue systems
 LTF Ref chapter: 6.1.1 to 6.1.19, exclusion 6.1.10

Present declaration's scope only extends to the conformity of a given sample, on a given date and in a given place – as mentioned here above.

This inspection report contain the following test and is complet with the test report number EP1 to EP6

TESTS	RESULTS	INSPECTORS	PLACES	DATES
1. Deployment system strength test (inner container)				
Minimum 700 N strength required during min 10 [s]:	POSITIVE	AZ	Villeneuve	23.02.2015
2. Descent rate and stability test - ref. A and B				
Sink rate EN standard	POSITIVE	AZ	Villeneuve	07.01.2014
Sink rate LTF standard	POSITIVE	AZ	Villeneuve	07.01.2014
Speed opening	POSITIVE	AZ	Villeneuve	07.01.2014
Stability	POSITIVE	AZ	Villeneuve	07.01.2014
3. Strength test opening shock				
Test 1 40 [m/s]	POSITIVE	AZ	Illarsaz	06.08.2014
Test 2 40 [m/s]	POSITIVE	AZ	Illarsaz	24.10.2014
Test 3 40 [m/s]	POSITIVE	AZ	Illarsaz	20.11.2014
4. Interaction and stability test (piloted) - ref. C				
the emergency parachute is deployed from a paraglider in normal straight flight.	N/A	n/a	n/a	x
the pilot shall take no action while the behaviour of the parachute and paraglider are observed 200 metres.	N/A	n/a	n/a	x
the pilot take action while the behaviour of the parachute and paraglider are observed 200 metres.	N/A	n/a	n/a	x
5. Connecting strap				
Minimum load capacity of 2400 [daN]	POSITIVE	AZ	Villeneuve	18.02.2015
6. Measurement				
According to manufacturer user manual	POSITIVE	AZ	Villeneuve	13.10.2015

This declaration must not be reproduced in part without the written permission of AIR TURQUOISE SA.



Deployment system strength

EP PARAGLIDERS RESCUE SYSTEMS

TEST REPORT EP 1

Test report number: EP_098.2015

SAMPLE DATA

Manufacturer name: Supair Sàrl
Representative: Laurent Chiabaut
Street: 34, rue Adrastée
Post code / place: 74650 Chavanod
Country: France
Rescue systems manufacturers name: Fluid
Rescue systems manufacturers Size: M
Rescue systems manufacturers max load (kg): 100
Manufacturers serial number flight : PDAP-FL-M-09M
Date of sample received: 07.01.2014
Place of test: Villeneuve
Date of test: 23.02.2015
Directive: EN 12491 | 2001 chapter 5.3.2 and LTF 91/09 chapter 6
Inspector: Alain Zoller
Results: POSITIVE

Signature:

ATMOSPHERE AGL

[C°] 21.8
RH [%] 32
[hPa] 1016.7

The deployment system is loaded at min 700 [N] during 10 secondes min. The deployment system is loaded until breaking. Each component is tested.

RESULTS

Minimum strength required during min 10s [kN]: 700.00
Strength of 700 N duration each components no1 [s]: 1 15.44
Strength of 700 N duration each components no2 [s]: 2 17.2
Strength of 700 N duration each components no3 [s]: 3 N/A
Uncertainty 95% [kN]: 0.017

INSPECTION RESULTS MINIMUM Time [s]: 15.4

Max strength components [kN]:

Max strength components no1 [kN]: 1 1.920
Max strength components no2 [kN]: 2 1.157
Max strength components no3 [kN]: 3 N/A
Uncertainty 95% [kN]: 0.017
Max strength [kN]: 1.157



Deployment system strength


PARAGLIDERS RESCUE SYSTEMS

TEST REPORT EP 1


Test report number: EP_098.2015

Involved test	Item	Validity	Manufacturer	Type nr.	S/N
Deployment system strength test	Load Cell (axial)	11.06.2016	Burster / MTS	8431-10000	1185483
Deployment system strength test	USB interface	11.06.2016	Burster / MTS	9205-V001	10000469
Deployment system strength test	Winch	06.01.2017	Arwin	300/600	n/a
Weather	Geos n° 11 Skywat	08.05.2017	JDC elec.	Geos n° 11	22


Min strength 10 sec. each components 1



Min strength 10 sec. each components 2



Min strength 10 sec. each components 3






Descent rate and stability test - ref. A and B

EP PARAGLIDERS RESCUE SYSTEMS

TEST REPORT EP 2

Test report number: EP_098.2015

SAMPLE DATA

Manufacturer name: **Supair Sàrl**
 Representative: **Laurent Chiabaut**
 Street: **34, rue Adrastée**
 Post code / place: **74650 Chavanod**
 Country: **France**
 Rescue systems manufacturers name: **Fluid**
 Rescue systems manufacturers Size: **M**
 Rescue systems manufacturers max load [kg]: **100**
 Manufacturers serial number flight : **PDAP-FL-M-09M**
 Date of sample received: **07.01.2014**
 Place of test: **Villeneuve**
 Date of test: **07.01.2014**
 Directive: **EN 12491 | 2001 chapter 5.3.4 and 5.3.3 and LTF 91/09 chapter 6**
 Inspector: **Alain Zoller**
 Signature: 

ATMOSPHERE AGL	Test no1	ATMOSPHERE AGL	Test no2
[C°]	5	[C°]	10
RH [%]	79	RH [%]	67
[hPa]	968	[hPa]	970
Wind [m/s]	0.1	Wind [m/s]	0.1

The rescue system is dropped from a paraglider in straight flight at 8 [m/s] +-1 [m/s]. The paraglider is released as the rescue system begins to open, minimum 100 [m] descent. Wink link 200 [N] is used to measure the speed opening.

RESULTS	EN	LTF
Sink rate results:	POSITIVE	POSITIVE
Stability results:	POSITIVE	POSITIVE
Speed opening results:	POSITIVE	POSITIVE
Max sink rate test requirements [m/s]	5.50	6.80
Sink rate test 1 [m/s]	4.80	4.80
Sink rate test 2 [m/s]	4.63	4.63
Behavior during descent		
Stability test 1	Stable	Stable
Stability test 2	Stable	Stable
Requirement time from the instant of free drop until a load of 200 [N] is sustained [s]	5.00	5.00
Speed opening test 1 [s]	2.31	2.31
Speed opening test 2 [s]	2.67	2.67

Involved test	Item	Validity	Manufacturer	Type nr.	S/N
Deployment system strength test	Weak links	2030	Tost	n/a	n/a
Descent rate and stability test	Line 30 meters	2020	Air Turquoise	n/a	n/a
Descent rate and stability test	Camcorder	2020	CANON	Legria HF G10	463440300907
Weather	Geos n° 11 Skywatch	08.05.2017	JDC elec.	Geos n° 11	22



Descent rate and stability test - ref. A and B

PARAGLIDERS RESCUE SYSTEMS

TEST REPORT EP 2

Test report number: EP_098.2015

A. At horizontal airspeed 8 m/s and vertical speed 1.5 m/s

B. Formula to be used for correcting the test mass of differences from ICAO standard atmosphere

$$m_{corr} := m_{dec} \cdot \frac{p \cdot T_0}{p_0 \cdot T}$$

Sink rate test 1

Ground level atmospheric pressure at test location: (p)	968 [hPa]	RH [%]	79
ICAO standard atmospheric pressure at MSL: (p ₀)	1013.25 [hPa]	Wind [m/s]	0.1
Ground level temperature at the test location: (T)	5 [C°]		
	278.15 [°K]		
ICAO standard temperature at MSL: (T ₀)	15 [C°]		
	288.15 [°K]		
Total weight in flight: (m _{dec})	100 [kg]		
Corrected mass: (m _{corr})	98.97 [kg]		
Corrected mass with uncertainty: (m _{corr})	99.87 [kg]		
Time when pilot release rescue	12.64		
Time when weak link broke	14.8		
Speed opening (sec.):	2.31 [s]		
Time boil touch	35.88		
Time pilot touch	42.28		
Time between boil touch and pilot touch (30m)	6.25 [s]		
Sink rate:	4.8048 [m/s]		
Behaviour:	Stable		
Inspector:	AZ		
Date of test :	07.01.2014		

Sink rate test 2

Ground level atmospheric pressure at the test location: (p)	970 [hPa]	RH [%]	67
ICAO standard atmospheric pressure at MSL: (p ₀)	1013.25 [hPa]	Wind [m/s]	0.1
Ground level temperature at the test location: (T)	10 [C°]		
	283.15 [°K]		
ICAO standard temperature at MSL: (T ₀)	15 [C°]		
	288.15 [°K]		
Total weight in flight: (m _{dec})	100 [kg]		
Corrected mass: (m _{corr})	97.42 [kg]		
Corrected mass with uncertainty: (m _{corr})	98.32 [kg]		
Time when pilot release rescue	18.36		
Time when weak link broke	20.88		
Speed opening (sec.):	2.67 [s]		
Time boil touch	34.6		
Time pilot touch	41.24		
Time between boil touch and pilot touch (30m)	6.49 [s]		
Sink rate:	4.6271 [m/s]		
Behaviour:	Stable		
Inspector:	AZ		
Date of test :	07.01.2014		



Descent rate and stability test - ref. A and B

PARAGLIDERS RESCUE SYSTEMS

TEST REPORT EP 2

Test report number: EP_098.2015

WINK LINKS 1

Picture



WINK LINKS 2

Picture





Strength test opening shock

PARAGLIDERS RESCUE SYSTEMS

TEST REPORT EP 3

Inspection report number: EP_098.2015

TEST SAMPLE DATA

Manufacturer name: **Supair Sàrl**
Representative **Laurent Chiabaut**
Street: **34, rue Adrastée**
Post code / place: **74650 Chavanod**
Country: **France**
Rescue systems manufacturers name: **Fluid**
Rescue systems manufacturers Size: **M**
Rescue systems manufacturers max load [kg]: **100**
Manufacturers serial number load : **PDAP-FL-M-10M**
Date of sample received: **07.01.2014**
Place of test: **Illarsaz**
Date of test: 1 | 2 | 3: **06.08.2014** **24.10.2014** **20.11.2014**
Directive: **EN 12491 | 2001 chapter 5.3.5 and LTF 91/09 chapter 6**
Inspector: **Alain Zoller**

Results: **POSITIVE**

Signature: 

ATMOSPHERE AGL	Test no1	Test no2	Test no3
[C°]	19.6	10	6
RH [%]	76	65	80
[hPa]	969	973.6	971
Wind [m/s]	0.1	0.2	0.1

The drop test device is accelerated to a straight line velocity of 40 m/s. Speed of opening must be less than 5 seconds and shock not exceeded 15g.

RESULTS

Speed of opening in max 5 secondes

Speed of opening test 1 [s] **POSITIVE**
Speed of opening test 2 [s] **POSITIVE**
Speed of opening test 3 [s] **POSITIVE**
Uncertainty 95% [s] **0.15**

Sample statut after shock

Strength test 40 m/s opening shock 1 **POSITIVE**
Strength test 40 m/s opening shock 2 **POSITIVE**
Strength test 40 m/s opening shock 3 **POSITIVE**
Uncertainty 95% [m/s] **1.73**

Wink link statut after shock

Wink link test 1 **POSITIVE**
Wink link test 2 **POSITIVE**
Wink link test 3 **POSITIVE**
Uncertainty 95% [%] **10**

Strength test opening shock

PARAGLIDERS RESCUE SYSTEMS TEST REPORT EP 3

Test report number: EP_098.2015

Involved test	Item	Validity	Manufacturer	Type nr.	S/N
Strength test 41 m/s opening shock	Helicopter	Air-Glacier	Air-Glacier	Air-Glacier	Air-Glacier
Strength test 41 m/s opening shock	Weight	2017	Air Turquoise	n/a	n/a
Strength test 41 m/s opening shock	Wink links	2020	Tost	n/a	n/a
Strength test 41 m/s opening shock	Camecorder	2017	CANON	Legria HF G10	463440300907
Weather	Geos n° 11 Skywatch	08.05.2017	JDC elec.	Geos n° 11	22

WINK LINKS 15g 1





Interaction and stability test (piloted) - ref. C

EP PARAGLIDERS RESCUE SYSTEMS

TEST REPORT EP 4

Test report number: EP_098.2015

TEST SAMPLE DATA

Manufacturer name: **Supair Sàrl**
Representative: **Laurent Chiabaut**
Street: **34, rue Adrastée**
Post code / place: **74650 Chavanod**
Country: **France**
Rescue systems manufacturers name: **Fluid**
Rescue systems manufacturers Size: **M**
Rescue systems manufacturers max load (kg): **100**
Manufacturers serial number flight : **PDAP-FL-M-09M**
Date of sample received: **07.01.2014**
Place of test: **x**
Date of test: **x**
Directive: **EN 12491 | 2001 chapter 5.3.6 and LTF 91/09 chapter 6**
Inspector: **x**

Results: **N/A**

Signature:

ATMOSPHERE AGL	Test no1	ATMOSPHERE AGL	Test no2
[C°]	x	[C°]	x
RH [%]	x	RH [%]	x
[hPa]	x	[hPa]	x
Wind [m/s]	x	Wind [m/s]	x

TEST RESULTS

- a the emergency parachute is deployed from a paraglider in normal straight flight. N/A
- b the pilot shall take no action while the behaviour of the parachute and paraglider are observed 200 metres. N/A
- c the pilot take action while the behaviour of the parachute and paraglider are observed 200 metres. N/A



Connecting strap

EP PARAGLIDERS RESCUE SYSTEMS

TEST REPORT EP 5

Test report number: EP_098.2015

TEST SAMPLE DATA

Manufacturer name: **Supair Sàrl**
 Representative: **Laurent Chiabaut**
 Street: **34, rue Adrastée**
 Post code / place: **74650 Chavanod**
 Country: **France**
 Rescue systems manufacturers name: **Fluid**
 Rescue systems manufacturers Size: **M**
 Rescue systems manufacturers max load (kg): **100**
 Manufacturers serial number load : **PDAP-FL-M-10M**
 Date of sample received: **07.01.2014**
 Place of test: **Villeneuve**
 Date of test: **18.02.2015**
 Directive: **LTF 91/09 chapter 6**
 Inspector: **Alain Zoller**

Results: **POSITIVE**

Signature:

ATMOSPHERE AGL


[C°] **21.1**
 RH [%] **31**
 [hPa] **1011.9**

The connecting strap is loaded at min 2400 [daN] and must not break.

RESULTS [daN]

Minimum required load **2400**
 Load capacity **2511**
 Uncertainty 95% **42**
 Max STRENGTH **2468.5**

GRAPHIQUE Connecting strap



Involved test	Item	Validity	Manufacturer	Type nr. S/N
Strap	Load Cell (axial)	11.06.20	Althen	SHK-D-3 20562
Atmosphere	Geos n° 11 Skywatch	08.05.20	JDC elec.	Geos n° 22



Measurement 50 N

EP PARAGLIDERS RESCUE SYSTEMS

MEASUREMENT REPORT EP 6

Teste report number: EP_098.2015

TEST SAMPLE DATA

Manufacturer name: **Supair Sàrl**
Representative: **Laurent Chiabaut**
Street: **34, rue Adrastée**
Post code / place: **74650 Chavanod**
Country: **France**
Rescue systems manufacturers name: **Fluid**
Rescue systems manufacturers Size: **M**
Rescue systems manufacturers max load (kg): **100**
Manufacturers serial number flight : **PDAP-FL-M-09M**
Place of test: **Villeneuve**
Date of measurement: **13.10.2015**
Directive: **EN 12491 | 2001 chapter and LTF 91/09 chapter 6**
Inspector: **Alain Zoller**

According to manufacturer user manual **POSITIVE**

Signature:

ATMOSPHERE AGL

[C°] **21.1**
RH [%] **47.7**
[hPa] **1009.3**

The rescue system lines are measured with 50[N] of tension. Center line and all types of mains lines are measured from attach point base until end of riser. Canopy dimensions are not measured. The rescue system is weighed with pod. Dimentions are compare with users manual.

RESULTS

Center Line (average) [mm] **4655**
Main Line (average of 5 pcs) 1 [mm] **4480**
Main Line (average of 5 pcs) 2 [mm] **4870**
Tolerance [mm] **25**
Number of center lines: **1**
Number of main lines 1: **16**
Weight [grame] **1660**

Involved test	Item	Validity	Manufacturer	Type nr.	S/N
Line length measurements	laser distance meter	07.04.2017	Leica	DISTO D3a BT	911110352
Atmosphere	Geos n° 11 Skywatch	08.05.2017	JDC elec.	Geos n° 11	22