## AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Comte 8 \* CH-1844 Villeneuve \* +41 (0)21 965 65 65

Test laboratoru for paragliders, paraglider harnesses and paraglider reserve parachutes



## Harness inspection certificate - NfL

Inspection certificate number:

PH\_353.2022

Impact pad number:

PH\_353.2022

Manufacturer data

Manufacturer name:

Representative:

Woody Valley srl Simone Caldana

Street:

Post code / place:

Via Linz 23 **38121 Trento** 

Country:

Italy

Sample data:

Harness

Impact pad

n/a

No

Name: Type: Size:

ABS

Exense

4.18

Weight of Sample [kg]: Serial number:

Clip-in weight [kg]: 120

Integrated container for rescue system:

Volume container [cm<sup>3</sup>]:

Yes

9000 max

044 0115 2015 S

4100 min

Date of reception:

02.02.2022

Name Impact pad: (1) Impact pad integrated: (1)

Foam Impact pad type: Weight of Sample [kg]: (1) 1.06

Serial number: (1) 038 0115 2156

Date of reception:

02.02.2022

**Test report summary** 

Structual test

Impact pad test

Result Place Date

**POSITIVE** Villeneuve 03.02.2022 **POSITIVE** Villeneuve 03.02.2022

## Issue data

Place of declaration:

Date of issue: Managing Director: Villeneuve

10.02.2022

Signature:

Andrea Wigger

This signature approves the validity of the test reports if available; no. 94.21 (test id 02, 03, 13, 09, 04, 14, 07) and no. 94.22 (test id: P, PR) Air Turquoise SA, having thoroughly assessed the sample mentioned above, declares it was found conform with all requirements defined by the following norms:

Airworthiness Requirements NfL 2-565-20 - EN12491:2015 5.3.2

Present declaration's scope only extends to the conformity of a given sample, on a given date and in a given place – as mentioned here above This inspection certificate contains the following test and is complet with the test, if available, report: 94.21 and 94.22

<sup>(</sup>f) If Impact pad is NOT integrated in the harness, it will have independently Inspection number, and serial number. Definition of integrated impact pad is impact pad which can not be dismounted from the harness, e.g. airbag. (2) If harness has an integrated inner container for emergency parachute, extra deployment tests are done for different type of emergency parachute.