AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Comte 8 A CH-1844 Villeneuve A +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Harness inspection certificate - NfL

Inspection certificate number:

PH 367.2022

Impact pad number:

MISC 226.2022

Manufacturer data

Manufacturer name:

Supair SAS

Representative:

Laurent Chiabaut

Street

Parc Altais / 34, rue Adrastée

Post code / place:

74650 Chavanod

Country:

France

Sample data:

Harness

Impact pad

Name:

Delight 4 Sport

Name Impact pad: (1)

Bumpair Delight 4

Type:

ABS

Impact pad integrated: (1) Impact pad type:

Foam

Size:

M

Weight of Sample [kg]: Serial number:

3.7 2172MM0602RO#14

Weight of Sample [kg]: (1)

Date of reception:

Clip-in weight [kg]:

130

Serial number:(1)

Bump.D4F A1

Integrated container for

Yes

5000 max

2400 min

Date of reception:

rescue system: Volume container [cm3]:

22.12.2021

09.02.2022

Test report summary

Structual test

Impact pad test

Result Place Date

POSITIVE Villeneuve 22.08.2022

POSITIVE Villeneuve 09.02.2022

Issue data

Place of declaration:

Date of issue:

Managing Director:

Villeneuve 07.09.2022

Andrea Wigger

Signature:

This signature approves the validity of the test reports if available; no. 94.21 (test id 02, 03, 13, 09, 04, 14, 07) and no. 94.22 (test id: P, PR) Air Turquoise SA, having thoroughly assessed the sample mentioned above, declares it was found conform with all requirements defined by the following norms:

Airworthiness Requirements NfL 2-565-20 - EN12491:2015 5.3.2

Present declaration's scope only extends to the conformity of a given sample, on a given date and in a given place – as mentioned here above. This inspection certificate contains the following test and is complet with the test, if available, report: 94.21 and 94.22

⁽¹⁾ If Impact pad is NOT integrated in the harness, it will have independently Inspection number, and serial number. Definition of integrated impact pad is impact pad which can not be dismounted from the harness, e.g. airbag. (2) If harness has an integrated inner container for emergency parachute, extra deployment tests are done for different type of emergency parachute.