



Classification: **A**



In accordance with standards EN 926-1:2015, EN 926-2:2013+A1:2021 and NfL 2-565-20

PG_2043.2022

Date of issue (DMY):

27.09.2022

Manufacturer:

Niviuk Gliders / Air Games S.L.

Model:

Hook 6 P 24

Serial number:

HOOK6P241

Configuration during flight tests

Paraglider

| | |
|-------------------------------|--------------|
| Maximum weight in flight (kg) | 92 |
| Minimum weight in flight (kg) | 70 |
| Glider's weight (kg) | 3.7 |
| Number of risers | 3+1 |
| Projected area (m2) | 20.59 |

Accessories

| | |
|---|-------------|
| Range of speed system (cm) | 16.7 |
| Speed range using brakes (km/h) | 14 |
| Total speed range with accessories (km/h) | 25 |
| Range of trimmers (cm) | 0 |

Harness used for testing (max weight)

| | |
|---------------------------------|--------------------|
| Harness type | ABS |
| Harness brand | Advance |
| Harness model | Success 4 M |
| Harness to risers distance (cm) | 43 |
| Distance between risers (cm) | 44 |

Inspections (whichever happens first)

| |
|--|
| every 100 hours of use or every 24 months (whichever happens first) |
| Warning! Before use refer to user's manual |
| Person or company having presented the glider for testing: None |

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23
A 0