AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Compte 8 • CH-1844 Villeneuve • +41 (0)21 965 65 65

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Flight test report: EN 926-2:2013+A1:2021* and NfL 2-565-20

Manufacturer Address	Ozone Gliders LTD 16 Barnes Green EH54 8PP Livingston United Kingdom		Certification number	er	PG_2244.2023 10.08.2023	
Glider model	Zeolite 2 GT MS		Classification		D	
Serial number	PR3-Y14A-017		Representative		Honorin	
Trimmer	no		Place of test		Villeneuve	
Folding lines used			Tidoo of tool		Villottedve	
Test pilot		Victor Chinen Cirilli		Claude Thurnheer		
Harness		Advance Thun AG Success 4 M		Advance Thun AG Success 4 M		
Harness to risers	s distance (cm)	43	43		43	
Distance betwee	n risers (cm)	44			44	
Total weight in flight (kg)		80		95		
1. Inflation/Take-off		C				
Rising behaviour		Overshoots, shall be slowed down to avoid a front collapse		С	Overshoots, shall be slowed down to avoid a front collapse	С
Special take off technic	que required	No	No A		No	Α
2. Landing		A				
Special landing technique required		No A		Α	No	Α
3. Speed in straight flight		В				
Trim speed more than 30 km/h		Yes		Α	Yes	Α
Speed range using the controls larger than 10 km/h		Yes		Α	Yes	Α
Minimum speed		25 km/h to 30 km/h		В	25 km/h to 30 km/h	В
4. Control movement	: :	С				
Max. weight in flight	up to 80 kg					
Symmetric control pressure / travel		not available		0	not available	0
Max. weight in flight 80 kg to 100 kg		Lauranian (AS and to CO and			_	
Symmetric control pres	ssure / travel	Increasing / 45 cm to 60 cm C		Increasing / 45 cm to 60 cm	С	
Max. weight in flight	= =			•	and accordable	0
Symmetric control pres	ssure / travel	not available		0	not available	0
5. Pitch stability exiti	ng accelerated flight	A Dive forward le	th 200	٨	Divertenment lead their 200	۸
Dive forward angle on	exit	Dive forward le	iss than 30°	Α	Dive forward less than 30°	Α
Collapse occurs		No		Α	No	Α
6. Pitch stability oper accelerated flight	rating controls during	Α				
Collapse occurs		No A		Α	No	Α
7. Roll stability and d	amping	A				
Oscillations		Reducing A		Α	A Reducing	
8. Stability in gentle s	spirals	A			_	
Tendency to return to straight flight		Spontaneous exit A		Spontaneous exit	Α	

9. Behaviour exiting a fully developed spiral dive	D			
Initial response of glider (first 180°)	Immediate increase in rate of turn	С	No immediate reaction	В
Tendency to return to straight flight	Turn remains constant (g force constant, rate of turn constant)		Turn remains constant (g force constant rate of turn constant)	, D
Turn angle to recover normal flight	With pilot action	D	1080° to 1440°, spontaneous recovery	С
10. Symmetric front collapse Approximately 30 % chord	D			
Entry	Rocking back less than 45°	Α	Rocking back less than 45°	Α
Recovery	Spontaneous in less than 3 s	Α	Recovery through pilot action in less than a further 3 s	D
Dive forward angle on exit Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
At least 50% chord Entry	Rocking back less than 45°	Α	Rocking back less than 45°	Α
Recovery	Spontaneous in 3 s to 5 s	В	Spontaneous in 3 s to 5 s	В
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
With accelerator				
Entry	Rocking back greater than 45°	С	Rocking back greater than 45°	С
Recovery	Spontaneous in 3 s to 5 s	В	Spontaneous in 3 s to 5 s	В
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
11. Exiting deep stall (parachutal stall) Deep stall achieved	A Yes	Α	Yes	Α
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Change of course	Changing course less than 45°	Α	Changing course less than 45°	Α
Cascade occurs	No	Α	No	Α
12. High angle of attack recovery Recovery	A Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Cascade occurs	No	Α	No	Α
13. Recovery from a developed full stall Dive forward angle on exit	C Dive forward 30° to 60°	В	Dive forward 30° to 60°	В
Collapse	No collapse	Α	No collapse	Α
Cascade occurs (other than collapses)	No	Α	No	Α

Rocking back	Greater than 45°	С	Less than 45°	Α
Line tension	Most lines tight		Most lines tight	Α
14. Asymmetric collapse	D			
Small asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	Less than 90° / Dive or roll angle 15° to 45°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	90° to 180° / Dive or roll angle 45° to 60°	С
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	Less than 90° / Dive or roll angle 15° to 45°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 60° to 90°	D	180° to 360° / Dive or roll angle 45° to 60°	С
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α

Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
15. Directional control with a maintained asymmetric collapse	A			
Able to keep course	Yes	Α	Yes	Α
180° turn away from the collapsed side possible in 10 s	Yes	Α	Yes	Α
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	Α	More than 50 % of the symmetric control travel	Α
16. Trim speed spin tendency	A			_
Spin occurs	No	Α	No	A
17. Low speed spin tendency Spin occurs	A No	Α	No	Α
18. Recovery from a developed spin	D Stone enimping in less than 00°	۸	Stone enioning in 1909 to 2609	
Spin rotation angle after release	Stops spinning in less than 90°	Α	Stops spinning in 180° to 360°	D
Cascade occurs	No	Α	No	Α
19. B-line stall	not available	0	not available	0
Change of course before release	not available	U	not available	U
Behaviour before release	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit	not available	0	not available	0
Cascade occurs	not available	0	not available	0
20. Big ears	B Dedicated controls	Α	Dedicated controls	Α
Entry procedure	Dedicated controls	^	Dedicated controls	^
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Spontaneous in 3 s to 5 s	В	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
21. Big ears in accelerated flight	В			
Entry procedure	Dedicated controls	Α	Dedicated controls	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Recovery through pilot action in less than a further 3 s	В	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	Α	Stable flight	Α
22. Alternative means of directional control	A Yes	Α	Yes	Α
180° turn achievable in 20 s	165	^	165	Α
Stall or spin occurs	No	Α	No	Α
23. Any other flight procedure and/or configuration described in the user's manual	0			
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0

24. Comments of test pilot	

*This standard is NOT covered by accreditation D-IS-19457-01