AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Compte 8 • CH-1844 Villeneuve • +41 (0)21 965 65 65

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Flight test report: EN 926-2:2013+A1:2021* and NfL 2-565-20

•						
Manufacturer Ozone Gliders LTD			Certification number	er	PG_2267.2023	
Address	16 Barnes Green		Flight test		15.09.2023	
	EH54 8PP Livingston					
Clidar madal	•		Classification		D	
_			Representative		Russel Ogden	
			Place of test		Villeneuve	
			1 1000 01 1001		· moriouvo	
· ·	yes	Alain Zoller			Alexandra lefraca	
rest pilot		Alam Zoller			Alexandre Jofresa	
Harness		Advance Th	un AG Success 4 L		Advance Thun AG Success 4	
	distance	43	ull AG Success 4 L		46	
		46			48	
(cm) Total weight in flight (kg)		100		115		
(om) Fotal Worghi	g (ng)	100			110	
1. Inflation/Take-off		С				
Rising behaviour		Overshoots, sh avoid a front co	all be slowed down to	С	Easy rising, some pilot correction is required	В
Address 16 Barnes Green EH54 8PP Livingston United Kingdom Glider model Zeolite 2 GT L Serial number PR3-Y-28C-001 Trimmer no Folding lines used yes Test pilot Harness Harness to risers distance (cm) Distance between risers (cm) Total weight in flight (kg) 1. Inflation/Take-off Rising behaviour Special take off technique required 2. Landing Special landing technique required 3. Speed in straight flight Trim speed more than 30 km/h Speed range using the controls larger than 10 km/h Minimum speed 4. Control movement Max. weight in flight up to 80 kg Symmetric control pressure / travel Max. weight in flight 80 kg to 100 kg Symmetric control pressure / travel Max. weight in flight greater than 100 kg Symmetric control pressure / travel 5. Pitch stability exiting accelerated flight Dive forward angle on exit Collapse occurs 6. Pitch stability operating controls during accelerated flight Collapse occurs 7. Roll stability and damping		No	•	Α	No	Α
2 Landing		Α				
•	ue required	No		Α	No	Α
		_				
		B Yes		Α	Yes	Α
Trim speed more than 30 km/n		res			165	A
Speed range using the controls larger than 10 km/h		Yes		Α	Yes	Α
Minimum speed		Less than 25 k	m/h	Α	25 km/h to 30 km/h	В
4. Control movement		С				
	ıp to 80 ka	Ü				
4. Control movement Max. weight in flight up to 80 kg Symmetric control pressure / travel		not available		0	not available	0
May waight in flight 0	0 km to 400 km					
		not available		0	not available	0
		not available		Ŭ	not d'anable	Ū
		In anna anima / 50	t- OF	_	la anga sia ny / 50 ang ta 65 ang	0
Symmetric control pres	sure / travei	Increasing / 50	cm to 65 cm	С	Increasing / 50 cm to 65 cm	С
		Α				
Dive forward angle on e	exit	Dive forward le	ess than 30°	Α	Dive forward less than 30°	Α
Collapse occurs		No		Α	No	Α
	ating controls during	Α				
•		No		Α	No	Α
·				,,		,,
	amping	A Doducing		٨	Dadusing	Λ
Oscillations		Reducing		Α	Reducing	Α
8. Stability in gentle s		Α				
Tendency to return to s	traight flight	Spontaneous e	exit	Α	Spontaneous exit	Α

9. Behaviour exiting a fully developed spiral dive	D		
Initial response of glider (first 180°)	No immediate reaction	B Immediate reduction of rate of turn	Α
Tendency to return to straight flight	Turn remains constant (g force constant, rate of turn constant)	D Spontaneous exit (g force decreasing, rate of turn decreasing)	Α
Turn angle to recover normal flight	With pilot action	D 720° to 1 080°, spontaneous recovery	В
10. Symmetric front collapse Approximately 30 % chord	D		
Entry	Rocking back less than 45°	A Rocking back less than 45°	Α
Recovery	Spontaneous in less than 3 s	A Spontaneous in less than 3 s	Α
Dive forward angle on exit Change of course	Dive forward 0° to 30° / Keeping course	A Dive forward 0° to 30° / Keeping course	Α
Cascade occurs	No	A No	Α
Folding lines used	Yes (Only if asked)	D Yes (Only if asked)	D
At least 50% chord	Decking heat loss than 45°	A. Daaking heak lose than 45°	٨
Entry	Rocking back less than 45°	A Spentaneous in less than 45°	A
Recovery	Spontaneous in less than 3 s	A Spontaneous in less than 3 s	A
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	A No.	A
Cascade occurs	No	A No	A
Folding lines used	Yes (Only if asked)	D Yes (Only if asked)	D
With accelerator	D 1: 1 1 450	0. D. II. II. II. 150	
Entry	Rocking back greater than 45°	C Rocking back less than 45°	Α
Recovery	Spontaneous in 3 s to 5 s	B Spontaneous in less than 3 s	Α
Dive forward angle on exit / Change of course	Dive forward 30° to 60° / Entering a turn of less than 90°	B Dive forward 0° to 30° / Keeping course	Α
Cascade occurs	No	A No	Α
Folding lines used	Yes (Only if asked)	D Yes (Only if asked)	D
11. Exiting deep stall (parachutal stall)	A	A	٨
Deep stall achieved	No	A Secretarious in less than 2 a	A
Recovery	Spontaneous in less than 3 s	A Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	A Dive forward 0° to 30°	Α
Change of course	Changing course less than 45°	A Changing course less than 45°	Α
Cascade occurs	No	A No	Α
12. High angle of attack recovery	A Spontaneous in less than 3 s	A Spontaneous in less than 3 s	Α
Recovery Cascade occurs	No	A No	A
	NO C	A 110	A
13. Recovery from a developed full stall Dive forward angle on exit	Dive forward 0° to 30°	A Dive forward 0° to 30°	Α
Collapse	No collapse	A No collapse	Α
Cascade occurs (other than collapses)	No	A No	Α

Rocking back	Greater than 45°	С	Less than 45°	Α
Line tension	Most lines tight	Α	Most lines tight	Α
14. Asymmetric collapse	D			
Small asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 0° to 15°	Α	Less than 90° / Dive or roll angle 0° to 15°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	Less than 90° / Dive or roll angle 15° to 45°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	Less than 90° / Dive or roll angle 0° to 15°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	Less than 90° / Dive or roll angle 15° to 45°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α

Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
15. Directional control with a maintained asymmetric collapse	A			
Able to keep course	Yes	Α	Yes	Α
180° turn away from the collapsed side possible in 10 s	Yes	Α	Yes	Α
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	Α	More than 50 % of the symmetric control travel	Α
16. Trim speed spin tendency	Α			
Spin occurs	No	Α	No	Α
17. Low speed spin tendency	D		V	
Spin occurs	No	Α	Yes	D
18. Recovery from a developed spin	В			
Spin rotation angle after release	Stops spinning in 90° to 180°	В	Stops spinning in 90° to 180°	В
Cascade occurs	No	Α	No	Α
19. B-line stall	0			
Change of course before release	not available	0	not available	0
Behaviour before release	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit	not available	0	not available	0
Cascade occurs	not available	0	not available	0
20. Big ears	В			
Entry procedure	Dedicated controls	Α	Dedicated controls	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Spontaneous in 3 s to 5 s	В	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
21. Big ears in accelerated flight	Α			
Entry procedure	Dedicated controls	Α	Dedicated controls	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Spontaneous in 3 s to 5 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	Α	Stable flight	Α
22. Alternative means of directional control	A			
180° turn achievable in 20 s	Yes	Α	Yes	Α
Stall or spin occurs	No	Α	No	Α
23. Any other flight procedure and/or configuration described in the user's manual	A			
Procedure works as described	not available	0	Yes	Α
Procedure suitable for novice pilots	not available	0	Yes	Α
Cascade occurs	not available	0	No	Α