AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Compte 8 • CH-1844 Villeneuve • +41 (0)21 965 65 65

Ozone Gliders LTD

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes

Manufacturer



Certification number PG 2296.2023

Flight test report: EN 926-2:2013+A1:2021* and NfL 2-565-20

Manadataro	Ozone Gliders LTD		Octunication name	DCI	F G_2290.2023	
Address	16 Barnes Green		Flight test		10.08.2023	
	EH54 8PP Livingston					
	United Kingdom					
Glider model	Zeolite 2 ML		Classification		D	
Serial number	Serial number PR3-Y-20E-011		Representative		Honorin	
Trimmer	no		Place of test		Villeneuve	
Folding lines used	yes					
3	,					
Test pilot		Claude Thurnh	ieer		Anselm Rauh	
Harness		Advance Thun	AG Success 4 M		Woody Valley srl Wani Light 2 L	
Harness to risers di	stance	43			43	
(cm) Distance between		44			48	
• •						
(cm) Total weight in	flight (kg)	90			105	
1. Inflation/Take-off		С				
Rising behaviour			lowed down to avoid a front	С	Overshoots, shall be slowed down to avoid a front	С
		collapse			collapse	
Special take off technique	required	No		Α	No	Α
2. Landing		Α				
Special landing technique	required	No		Α	No	Α
oposiai iariamg toomiquo	10quii 0u					
3. Speed in straight fligh	t	В				
Trim speed more than 30 k	km/h	Yes		Α	Yes	Α
		V				
Speed range using the controls larger than 10 km/h		Yes		Α	Yes	Α
Minimum speed		25 km/h to 30 km/h		В	25 km/h to 30 km/h	В
		_				
4. Control movement		С				
Max. weight in flight up to 80 kg Symmetric control pressure / travel		not available		0	not available	0
Max. weight in flight 80 k	ra to 100 ka					
Max. weight in flight 80 kg to 100 kg Symmetric control pressure / travel		Increasing / greater than 60 cm A		not available	0	
Cymmetric control precodi	0 / 114 / 01	J. J				
Max. weight in flight grea	ater than 100 kg					
Symmetric control pressur	re / travel	not available		0	Increasing / 50 cm to 65 cm	С
		•				
5. Pitch stability exiting a		A			Di di di da	
Dive forward angle on exit		Dive forward less than	30°	Α	Dive forward less than 30°	Α
Collapse occurs		No		Α	No	Α
6. Pitch stability operatin accelerated flight	ng controls during	Α				
Collapse occurs		No		Α	No	Α
7. Roll stability and damping		Α				
Oscillations		Reducing		Α	Reducing	Α
8. Stability in gentle spira	ale	A				
Tendency to return to strai		Spontaneous exit		Α	Spontaneous exit	Α
rendency to return to strai	igni iligni	Sp. T. T. T. O. C. O. M.		•	-,	

Behaviour exiting a fully developed spiral dive	D.	_	No. 2000 Processing	
nitial response of glider (first 180°)	No immediate reaction	В	No immediate reaction	
endency to return to straight flight	Spontaneous exit (g force decreasing, rate of turn decreasing)	Α	Turn remains constant (g force constant, rate of turn constant)	
urn angle to recover normal flight	1080° to 1440°, spontaneous recovery	С	1080° to 1440°, spontaneous recovery	
Symmetric front collapse Approximately 30 % chord	D			
Entry	Rocking back less than 45°	Α	Rocking back less than 45°	
Recovery	Spontaneous in less than 3 s	Α	Recovery through pilot action in less than a furthe 3 s	r
Dive forward angle on exit Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	
Cascade occurs	No		No	
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	
At least 50% chord Entry	Rocking back less than 45°	Α	Rocking back less than 45°	
Recovery	Spontaneous in 3 s to 5 s	В	Recovery through pilot action in less than a furthe 3 s	r
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 30° to 60° / Keeping course	
Cascade occurs	No	Α	No	
olding lines used	Yes (Only if asked)	D	Yes (Only if asked)	
Vith accelerator				
Entry	Rocking back greater than 45°	С	Rocking back greater than 45°	
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in 3 s to 5 s	
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 30° to 60° / Entering a turn of less than 90°	
Cascade occurs	No	Α	No	
olding lines used	Yes (Only if asked)	D	Yes (Only if asked)	
1. Exiting deep stall (parachutal stall)	C		W	
Deep stall achieved	Yes		Yes	
Recovery	Spontaneous in 3 s to 5 s		Spontaneous in less than 3 s	
Dive forward angle on exit	Dive forward 0° to 30°		Dive forward 0° to 30°	
Change of course	Changing course less than 45°		Changing course less than 45°	
Cascade occurs	No	А	No	
2. High angle of attack recovery Recovery	D Spontaneous in less than 3 s	Α	Recovery through pilot action in less than a furthe	٠r
Cascade occurs	No	Α	3 s No	
3. Recovery from a developed full stall Dive forward angle on exit	B Dive forward 0° to 30°	Α	Dive forward 30° to 60°	
Collapse	No collapse	Α	No collapse	
Cascade occurs (other than collapses)	No	Α	No	

Rocking back	Less than 45°	Α	Less than 45°	Α
Line tension	Most lines tight	Α	Most lines tight	Α
14. Asymmetric collapse Small asymmetric collapse	D			
Change of course until re-inflation / Maximum	Less than 90° / Dive or roll angle 15° to 45°	Α	Less than 90° / Dive or roll angle 15° to 45°	Α
dive forward or roll angle	-		•	Α
Re-inflation behaviour Total change of course	Spontaneous re-inflation Less than 360°	A A	•	A
rotal change of course	2000 (1.0.1) 000		2000 111411 000	
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	Less than 90° / Dive or roll angle 15° to 45°	Α
Re-inflation behaviour	Inflates in less than 3 s from start of pilot action	С	Inflates in less than 3 s from start of pilot action	С
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	90° to 180° / Dive or roll angle 45° to 60°	С
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	Yes, no turn reversal	С	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α

Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
15. Directional control with a maintained asymmetric collapse	A			
Able to keep course	Yes	Α	Yes	Α
180° turn away from the collapsed side possible in 10 s	Yes	Α	Yes	Α
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	Α	More than 50 % of the symmetric control travel	Α
16. Trim speed spin tendency	A			
Spin occurs	No	A	No	Α
17. Low speed spin tendency Spin occurs	A No	Α	No	Α
18. Recovery from a developed spin Spin rotation angle after release	D Stops spinning in 180° to 360°	D	Stops spinning in 180° to 360°	D
Spiri rotation angle after release		J	Ctope opining in 100 to 000	5
Cascade occurs	No	Α	No	Α
19. B-line stall	0			
Change of course before release	not available	0	not available	0
Behaviour before release	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit	not available	0	not available	0
Cascade occurs	not available	0	not available	0
20. Big ears	A			
Entry procedure	Dedicated controls	Α	Dedicated controls	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
21. Big ears in accelerated flight	Α			
Entry procedure	Dedicated controls	Α	Dedicated controls	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	Α	Stable flight	Α
22. Alternative means of directional control	A			_
180° turn achievable in 20 s	Yes	Α	Yes	Α
Stall or spin occurs	No	Α	No	Α
23. Any other flight procedure and/or configuration described in the user's manual	0			
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0