



Flight test report: EN 926-2:2013

| | | | |
|--|---|-----------------------|-------------------------|
| Manufacturer | ADVANCE Thun AG | Certification number | PG_0943.2015 |
| Address | Uttigenstrasse 87 3600 Thun Switzerland | Date of flight test | 05. 08. 2015 |
| Glider model | Omega XAlps 24.5 | Classification | D |
| Serial number | 63798 | Representative | None |
| Trimmer | no | Place of test | Villeneuve |
| Test pilot | | Thurnheer Claude | Zoller Alain |
| Harness | | Sup' Air - Access M | Gin Gliders - Gingo 2 L |
| Harness to risers distance (cm) | | 43 | 42 |
| Distance between risers (cm) | | 44 | 46 |
| Total weight in flight (kg) | | 90 | 110 |

| | | | | |
|--|---|---|---|---|
| 1. Inflation/Take-off | C | | | |
| Rising behaviour | Overshoots, shall be slowed down to avoid a front collapse | C | Overshoots, shall be slowed down to avoid a front collapse | C |
| Special take off technique required | No | A | No | A |
| 2. Landing | A | | | |
| Special landing technique required | No | A | No | A |
| 3. Speed in straight flight | A | | | |
| Trim speed more than 30 km/h | Yes | A | Yes | A |
| Speed range using the controls larger than 10 km/h | Yes | A | Yes | A |
| Minimum speed | Less than 25 km/h | A | Less than 25 km/h | A |
| 4. Control movement | C | | | |
| Max. weight in flight up to 80 kg | | | | |
| Symmetric control pressure / travel | not available | 0 | not available | 0 |
| Max. weight in flight 80 kg to 100 kg | | | | |
| Symmetric control pressure / travel | Increasing / greater than 60 cm | A | not available | 0 |
| Max. weight in flight greater than 100 kg | | | | |
| Symmetric control pressure / travel | not available | 0 | Increasing / 50 cm to 65 cm | C |
| 5. Pitch stability exiting accelerated flight | A | | | |
| Dive forward angle on exit | Dive forward less than 30° | A | Dive forward less than 30° | A |
| Collapse occurs | No | A | No | A |
| 6. Pitch stability operating controls during accelerated flight | A | | | |
| Collapse occurs | No | A | No | A |
| 7. Roll stability and damping | A | | | |
| Oscillations | Reducing | A | Reducing | A |
| 8. Stability in gentle spirals | A | | | |
| Tendency to return to straight flight | Spontaneous exit | A | Spontaneous exit | A |
| 9. Behaviour exiting a fully developed spiral dive | D | | | |
| Initial response of glider (first 180°) | No immediate reaction | B | Immediate reduction of rate of turn | A |
| Tendency to return to straight flight | Turn remains constant (g force constant, rate of turn constant) | D | Turn remains constant (g force constant, rate of turn constant) | D |
| Turn angle to recover normal flight | With pilot action | D | With pilot action | D |

10. Symmetric front collapse**D****Approximately 30 % chord**

| | | | | |
|---|--|---|--|---|
| Entry | Rocking back less than 45° | A | Rocking back less than 45° | A |
| Recovery | Recovery through pilot action in less than a further 3 s | D | Recovery through pilot action in less than a further 3 s | D |
| Dive forward angle on exit / Change of course | Dive forward 0° to 30° / Keeping course | A | Dive forward 30° to 60° / Keeping course | B |
| Cascade occurs | No | A | No | A |
| Folding lines used | Yes | D | Yes | D |

At least 50% chord

| | | | | |
|---|--|---|--|---|
| Entry | Rocking back less than 45° | A | Rocking back less than 45° | A |
| Recovery | Recovery through pilot action in less than a further 3 s | D | Recovery through pilot action in less than a further 3 s | D |
| Dive forward angle on exit / Change of course | Dive forward 0° to 30° / Keeping course | A | Dive forward 30° to 60° / Keeping course | B |
| Cascade occurs | No | A | No | A |
| Folding lines used | Yes | D | Yes | D |

With accelerator

| | | | | |
|---|---|---|--|---|
| Entry | Rocking back less than 45° | A | Rocking back greater than 45° | C |
| Recovery | Spontaneous in 3 s to 5 s | B | Spontaneous in 3 s to 5 s | B |
| Dive forward angle on exit / Change of course | Dive forward 0° to 30° / Keeping course | A | Dive forward 30° to 60° / Keeping course | B |
| Cascade occurs | No | A | No | A |
| Folding lines used | Yes | D | Yes | D |

11. Exiting deep stall (parachutal stall)**A**

| | | | | |
|----------------------------|-------------------------------|---|-------------------------------|---|
| Deep stall achieved | Yes | A | Yes | A |
| Recovery | Spontaneous in less than 3 s | A | Spontaneous in less than 3 s | A |
| Dive forward angle on exit | Dive forward 0° to 30° | A | Dive forward 0° to 30° | A |
| Change of course | Changing course less than 45° | A | Changing course less than 45° | A |
| Cascade occurs | No | A | No | A |

12. High angle of attack recovery**A**

| | | | | |
|----------------|------------------------------|---|------------------------------|---|
| Recovery | Spontaneous in less than 3 s | A | Spontaneous in less than 3 s | A |
| Cascade occurs | No | A | No | A |

13. Recovery from a developed full stall**B**

| | | | | |
|---------------------------------------|-------------------------|---|-------------------------|---|
| Dive forward angle on exit | Dive forward 30° to 60° | B | Dive forward 30° to 60° | B |
| Collapse | No collapse | A | No collapse | A |
| Cascade occurs (other than collapses) | No | A | No | A |
| Rocking back | Less than 45° | A | Less than 45° | A |
| Line tension | Most lines tight | A | Most lines tight | A |

14. Asymmetric collapse**C****Small asymmetric collapse**

| | | | | |
|--|--|---|--|---|
| Change of course until re-inflation / Maximum dive forward or roll angle | Less than 90° / Dive or roll angle 15° to 45° | A | Less than 90° / Dive or roll angle 0° to 15° | A |
| Re-inflation behaviour | Spontaneous re-inflation | A | Spontaneous re-inflation | A |
| Total change of course | Less than 360° | A | Less than 360° | A |
| Collapse on the opposite side occurs | No (or only a small number of collapsed cells with a spontaneous re-inflation) | A | No (or only a small number of collapsed cells with a spontaneous re-inflation) | A |
| Twist occurs | No | A | No | A |
| Cascade occurs | No | A | No | A |
| Folding lines used | Yes | D | Yes | D |

Large asymmetric collapse

| | | | | |
|--|---|---|---|---|
| Change of course until re-inflation / Maximum dive forward or roll angle | 90° to 180° / Dive or roll angle 15° to 45° | B | 90° to 180° / Dive or roll angle 45° to 60° | C |
| Re-inflation behaviour | Spontaneous re-inflation | A | Spontaneous re-inflation | A |
| Total change of course | Less than 360° | A | Less than 360° | A |

| | | | | |
|--|--|---|--|---|
| Collapse on the opposite side occurs | No (or only a small number of collapsed cells with a spontaneous re-inflation) | A | No (or only a small number of collapsed cells with a spontaneous re-inflation) | A |
| Twist occurs | No | A | No | A |
| Cascade occurs | No | A | No | A |
| Folding lines used | Yes | D | Yes | D |
| Small asymmetric collapse with fully activated accelerator | | | | |
| Change of course until re-inflation / Maximum dive forward or roll angle | Less than 90° / Dive or roll angle 15° to 45° | A | Less than 90° / Dive or roll angle 15° to 45° | A |
| Re-inflation behaviour | Spontaneous re-inflation | A | Spontaneous re-inflation | A |
| Total change of course | Less than 360° | A | Less than 360° | A |
| Collapse on the opposite side occurs | No (or only a small number of collapsed cells with a spontaneous re-inflation) | A | No (or only a small number of collapsed cells with a spontaneous re-inflation) | A |
| Twist occurs | No | A | No | A |
| Cascade occurs | No | A | No | A |
| Folding lines used | Yes | D | Yes | D |
| Large asymmetric collapse with fully activated accelerator | | | | |
| Change of course until re-inflation / Maximum dive forward or roll angle | 90° to 180° / Dive or roll angle 15° to 45° | B | 90° to 180° / Dive or roll angle 45° to 60° | C |
| Re-inflation behaviour | Inflates in less than 3 s from start of pilot action | C | Spontaneous re-inflation | A |
| Total change of course | Less than 360° | A | Less than 360° | A |
| Collapse on the opposite side occurs | No (or only a small number of collapsed cells with a spontaneous re-inflation) | A | No (or only a small number of collapsed cells with a spontaneous re-inflation) | A |
| Twist occurs | No | A | No | A |
| Cascade occurs | No | A | No | A |
| Folding lines used | Yes | D | Yes | D |
| 15. Directional control with a maintained asymmetric collapse | | | | |
| Able to keep course | Yes | A | Yes | A |
| 180° turn away from the collapsed side possible in 10 s | Yes | A | Yes | A |
| Amount of control range between turn and stall or spin | More than 50 % of the symmetric control travel | A | More than 50 % of the symmetric control travel | A |
| 16. Trim speed spin tendency | | | | |
| Spin occurs | No | A | No | A |
| 17. Low speed spin tendency | | | | |
| Spin occurs | No | A | No | A |
| 18. Recovery from a developed spin | | | | |
| Spin rotation angle after release | Stops spinning in less than 90° | A | Stops spinning in 90° to 180° | B |
| Cascade occurs | No | A | No | A |
| 19. B-line stall | | | | |
| Change of course before release | Changing course less than 45° | A | Changing course less than 45° | A |
| Behaviour before release | Remains stable with straight span | A | Remains stable with straight span | A |
| Recovery | Spontaneous in less than 3 s | A | Spontaneous in less than 3 s | A |
| Dive forward angle on exit | Dive forward 0° to 30° | A | Dive forward 0° to 30° | A |
| Cascade occurs | No | A | No | A |
| 20. Big ears | | | | |
| Entry procedure | Dedicated controls | A | Standard technique | A |
| Behaviour during big ears | Stable flight | A | Stable flight | A |
| Recovery | Spontaneous in less than 3 s | A | Spontaneous in less than 3 s | A |
| Dive forward angle on exit | Dive forward 0° to 30° | A | Dive forward 0° to 30° | A |
| 21. Big ears in accelerated flight | | | | |
| Entry procedure | Dedicated controls | A | Standard technique | A |
| Behaviour during big ears | Stable flight | A | Stable flight | A |
| Recovery | Recovery through pilot action in less than a further 3 s | B | Spontaneous in less than 3 s | A |

| | | | | |
|---|--------------------------|---|------------------------|---|
| Dive forward angle on exit | Dive forward 0° to 30° | A | Dive forward 0° to 30° | A |
| Behaviour immediately after releasing the accelerator while maintaining big ears | Stable flight | A | Stable flight | A |
| 22. Alternative means of directional control | A | | | |
| 180° turn achievable in 20 s | Yes | A | Yes | A |
| Stall or spin occurs | No | A | No | A |
| 23. Any other flight procedure and/or configuration described in the user's manual | 0 | | | |
| Procedure works as described | not available | 0 | not available | 0 |
| Procedure suitable for novice pilots | not available | 0 | not available | 0 |
| Cascade occurs | not available | 0 | not available | 0 |
| 24. Comments of test pilot | <input type="checkbox"/> | | | |
| Comments | | | | |