AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Compte 8 • CH-1844 Villeneuve • +41 (0)21 965 65 65

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Flight test report: EN 926-2:2013+A1:2021 and NfL 2024-2-785

•						
Manufacturer Advance Thun AG			Certification numb	ber	PG_2625.2025	
Address Uttigenstrasse 87			Flight test		25.08.2025	
	3600 Thun					
Glider model	Switzerland Pi 4 22		Classification		В	
Serial number	111074		Representative		None	
Trimmer	no		Place of test		Villeneuve	
Folding lines used	no				· · · · · · · · · · · · · · · · · · ·	
. o.agoo acca						
Test pilot		Victor Chinen Cirilli		Alexandre Jofresa		
Натроса		Woody Valley srl Wani Light 2 M		Supair s.a.s. ALTIRANDO Lite 2)	
Harness Harness to risers distance [cm]		43		40		
Distance between r		40			48	
Total weight in fligh	nt [kg]	67		103		
1. Inflation/Take-off		Α				
Rising behaviour		Smooth, easy and cor	nstant rising	Α	Smooth, easy and constant rising	Α
Special take off technique	required	No		Α	No	Α
2. Landing		A				
Special landing technique	required	No		Α	No	Α
2 Chood in attaight fligh		В				
Speed in straight flight Trim speed more than 30		Yes		Α	Yes	Α
Thin speed more than 30 km/h						
Speed range using the co	ntrols larger than 10 km/h	Yes		Α	Yes	Α
Minimum speed		Less than 25 km/h		Α	25 km/h to 30 km/h	В
4. Control movement		Α				
Max. weight in flight up to 80 kg						
Symmetric control pressure / travel		Increasing / greater th	an 55 cm	Α	not available	0
Max. weight in flight 80	kg to 100 kg					
Symmetric control pressure / travel		not available		0	not available	0
May weight in flight gre	ater than 100 kg					
Max. weight in flight greater than 100 kg Symmetric control pressure / travel		not available		0	Increasing / greater than 65 cm	Α
,						
5. Pitch stability exiting accelerated flight		A Dive forward less than	n 30°	Α	Dive forward less than 30°	Α
Dive forward angle on exi	l	Dive loi ward less trial	130	^	Dive loward less than 50	^
Collapse occurs		No		Α	No	Α
6. Pitch stability operating controls during accelerated flight		Α				
6. Pitch stability operating controls during		No		Α	No	Α
7. Roll stability and damping		A				
Oscillations		Reducing		Α	Reducing	Α
8. Stability in gentle spirals		A				
Tendency to return to straight flight		Spontaneous exit		Α	Spontaneous exit	Α
						_

9. Behaviour exiting a fully developed spiral dive	A			
Initial response of glider (first 180°)	Immediate reduction of rate of turn	Α	Immediate reduction of rate of turn	Α
Tendency to return to straight flight	Spontaneous exit (g force decreasing, rate of turn decreasing)	Α	Spontaneous exit (g force decreasing, rate of turn decreasing)	ı A
Turn angle to recover normal flight	Less than 720°, spontaneous recovery	Α	Less than 720°, spontaneous recovery	Α
10. Symmetric front collapse Approximately 30 % chord	Α			
Entry	Rocking back less than 45°	Α	Rocking back less than 45°	Α
Recovery	Spontaneous in less than 3 s		Spontaneous in less than 3 s	Α
Dive forward angle on exit Change of course	Dive forward 0° to 30° / Keeping course		Dive forward 0° to 30° / Keeping course	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	Α	No	Α
At least 50% chord Entry	Rocking back less than 45°	Α	Rocking back less than 45°	Α
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	Α	No	Α
With accelerator				
Entry	Rocking back less than 45°	Α	Rocking back less than 45°	Α
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	Α	No	Α
11. Exiting deep stall (parachutal stall)	A Yes	٨	Yes	٨
Deep stall achieved	Spontaneous in less than 3 s		Spontaneous in less than 3 s	A A
Recovery	Dive forward 0° to 30°	A		A
Dive forward angle on exit	Changing course less than 45°	A		A
Change of course Cascade occurs	No		No No	A
	A	,,		^`
12. High angle of attack recovery Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Cascade occurs	No	Α	No	Α
13. Recovery from a developed full stall Dive forward angle on exit	A Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Collapse	No collapse	Α	No collapse	Α
Cascade occurs (other than collapses)	No	Α	No	Α

Rocking back	Less than 45°	Α	Less than 45°	Α
Line tension	Most lines tight		Most lines tight	Α
14. Asymmetric collapse	В			
Small asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 0° to 15°	Α	Less than 90° / Dive or roll angle 0° to 15°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°		Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	Α	No	Α
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	Α	No	Α
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	Less than 90° / Dive or roll angle 15° to 45°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	Α	No	Α
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	Less than 90° / Dive or roll angle 15° to 45°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α

Folding lines used	No	Α	No	Α
15. Directional control with a maintained asymmetric collapse	A			
Able to keep course	Yes	Α	Yes	Α
180° turn away from the collapsed side possible in 10 s	Yes	Α	Yes	Α
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	Α	More than 50 % of the symmetric control travel	Α
16. Trim speed spin tendency	A			
Spin occurs	No	Α	No	Α
17. Low speed spin tendency Spin occurs	A No	Α	No	Α
18. Recovery from a developed spin	A			
Spin rotation angle after release	Stops spinning in less than 90°	Α	Stops spinning in less than 90°	Α
Cascade occurs	No	Α	No	Α
19. B-line stall	A			
Change of course before release	Changing course less than 45°	Α	Changing course less than 45°	Α
Behaviour before release	Remains stable with straight span	Α	Remains stable with straight span	Α
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Cascade occurs	No	Α	No	Α
20. Big ears	A			
Entry procedure	Dedicated controls	Α	Dedicated controls	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
21. Big ears in accelerated flight	A			
Entry procedure	Dedicated controls	Α	Dedicated controls	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	Α	Stable flight	Α
22. Alternative means of directional control	A Voc	^	Voc	٨
180° turn achievable in 20 s	Yes	Α	Yes	Α
Stall or spin occurs	No	Α	No	Α
23. Any other flight procedure and/or configuration described in the user's manual	0			
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0