

## Flight test report

**Manufacturer** Dudek Paragliders  
**Address** ul. Centralna 2U  
 86-031 Osielsko  
 Poland  
**Representative** none  
**Type of glider** Synthesis Cabrio 46  
**Trimmer** Closed trimmer

**Certification number** PG 119.2008  
**Date of flight test** 24/01/2008  
**Place of test** Villeneuve



**Classification C**

**Test Pilot** Claude Thurnheer not available  
**Harness** Advance Bi-pro 50 cm not available  
**Total weight in flight** 180 kg not available

	Min weight		Max weight	
<b>1. Inflation/Take-off</b>				
Rising behaviour	Smooth, easy and constant rising	A	not available	0
Special take off technique required	No	A	not available	0
<b>2. Landing</b>				
Special landing technique required	No	A	not available	0
<b>3. Speed in straight flight</b>				
Trim speed more than 30 km/h	Yes	A	not available	0
Speed range using the controls larger than 10 km/h	Yes	A	not available	0
Minimum speed	25 km/h to 30 km/h	B	not available	0
<b>4. Control movement</b>				
<i>Max. weight in flight up to 80 kg</i> Symmetric control pressure/travel	not available	0	not available	0
<i>Max. weight in flight 80 kg to 100 kg</i> Symmetric control pressure/travel	not available	0	not available	0
<i>Max. weight in flight greater than 100 kg</i> Symmetric control pressure/travel	Increasing, Greater than 65 cm	A	not available	0
<b>5. Pitch stability exiting accelerated flight</b>				
Dive forward angle on exit	not available	0	not available	0
Collapse occurs	not available	0	not available	0
<b>6. Pitch stability operating controls during accelerated flight</b>				
Collapse occurs	not available	0	not available	0
<b>7. Roll stability and damping</b>				
Oscillations	Reducing	A	not available	0
<b>8. Stability in gentle spirals</b>				
Tendency to return to straight flight	Spontaneous exit	A	not available	0
<b>9. Behaviour in a steeply banked turn</b>				
Sink rate after two turns	More than 14 m/s	B	not available	0
<b>10. Symmetric front collapse</b>				
Entry	Rocking back less than 45°	A	not available	0
Recovery	Spontaneous in less than 3 s	A	not available	0
Dive forward angle on exit	Dive forward 0° to 30°, Keeping course	A	not available	0
Cascade occurs	No	A	not available	0
<i>With accelerator</i>				
Entry	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit	not available	0	not available	0
Cascade occurs	not available	0	not available	0
<b>11. Exiting deep stall (parachutal stall)</b>				
Deep stall achieved	Yes	A	not available	0
Recovery	Spontaneous in less than 3 s	A	not available	0
Dive forward angle on exit	Dive forward 0° to 30°	A	not available	0
Change of course	Changing course less than 45°	A	not available	0
Cascade occurs	No	A	not available	0
<b>12. High angle of attack recovery</b>				
Recovery	not available	0	not available	0
Cascade occurs	not available	0	not available	0
<b>13. Recovery from a developed full stall</b>				
Dive forward angle on exit	Dive forward 30° to 60°	B	not available	0
Collapse	No collapse	A	not available	0
Cascade occurs (other than collapse)	No	A	not available	0
Rocking back	Less than 45°	A	not available	0
Line tension	Most line tight	A	not available	0
<b>14. Asymmetric collapse</b>				
<i>With 50% collapse-Maximum dive forward or roll angle</i>				
Change of course until re-inflation	Less than 90°, Dive or roll angle 15° to 45°	A	not available	0
Re-inflation behaviour	Spontaneous re-inflation	A	not available	0
Total change of course	Less than 360°	A	not available	0
Collapse on the opposite side occurs	No	A	not available	0
Twist occurs	No	A	not available	0
Cascade occurs	No	A	not available	0
<i>With 75% collapse-Maximum dive forward or roll angle</i>				
Change of course until re-inflation	90° to 180°, Dive or roll angle 45° to 60°	C	not available	0
Re-inflation behaviour	Spontaneous re-inflation	A	not available	0
Total change of course	Less than 360°	A	not available	0
Collapse on the opposite side occurs	No	A	not available	0
Twist occurs	No	A	not available	0
Cascade occurs	No	A	not available	0
<i>With 50% collapse and accelerator-Maximum dive forward or roll angle</i>				
Change of course until re-inflation	not available	0	not available	0
Re-inflation behaviour	not available	0	not available	0
Total change of course	not available	0	not available	0
Collapse on the opposite side occurs	not available	0	not available	0

Twist occurs	not available	0	not available	0
Cascade occurs	not available	0	not available	0
<i>With 75% collapse and accelerator-Maximum dive forward or roll angle</i>				
Change of course until re-inflation	not available	0	not available	0
Re-inflation behaviour	not available	0	not available	0
Total change of course	not available	0	not available	0
Collapse on the opposite side occurs	not available	0	not available	0
Twist occurs	not available	0	not available	0
Cascade occurs	not available	0	not available	0
<b>15. Directional control with a maintained asymmetric collapse</b>				
Able to keep course	Yes	A	not available	0
180° turn away from the collapsed side possible in 10 s	Yes	A	not available	0
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	A	not available	0
<b>16. Trim speed spin tendency</b>				
Spin occurs	No	A	not available	0
<b>17. Low speed spin tendency</b>				
Spin occurs	No	A	not available	0
<b>18. Recovery from a developed spin</b>				
Spin rotation angle after release	Stops spinning in less than 90°	A	not available	0
Cascade occurs	No	A	not available	0
<b>19. B-line stall</b>				
Change of course before release	not available	0	not available	0
Behaviour before release	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit	not available	0	not available	0
Cascade occurs	not available	0	not available	0
<b>20. Big ears</b>				
Entry procedure	Dedicated controls	A	not available	0
Behaviour during big ears	Unstable flight	C	not available	0
Recovery	Spontaneous in less than 3 s	A	not available	0
Dive forward angle on exit	Dive forward 0° to 30°	A	not available	0
<b>21. Big ears in accelerated flight</b>				
Entry procedure	not available	0	not available	0
Behaviour during big ears	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit	not available	0	not available	0
Behaviour immediately after releasing the accelerator while maintaining big ears	not available	0	not available	0
<b>22. Behaviour exiting a steep spiral</b>				
Tendency to return to straight flight	Spontaneous exit	A	not available	0
Turn angle to recover normal flight	Less than 720°, spontaneous recovery	A	not available	0
Sink rate when evaluating spiral stability [m/s]	19 m/s		not available	
<b>23. Alternative means of directional control</b>				
180° turn achievable in 20 s	Yes	A	not available	0
Stall or spin occurs	No	A	not available	0
<b>24. Any other flight procedure and/or configuration described in the user's manual</b>				
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0
<b>Comments of test pilot</b>				
Comments	no		not available	



### Air Turquoise

Rue de la Poterlaz 6  
Case postale 10  
CH- 1844 Villeneuve  
Switzerland  
mobile: +41 79 202 52 30  
Tel. no : +41 21 965 65 65  
fax : +41 219 65 65 66  
email: info@airturquoise.ch  
homepage: www.para-test.com



ISO 9001:2000