## AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Compte 8 🔺 CH-1844 Villeneuve 🔺 +41 (0)21 965 65 65

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



## Flight test report: EN 926-2:2013+A1:2021 and NfL 2024-2-785

•				_			
Manufacturer	IFLY GLIDERS HAV	CILIK Certification numbe		ber	er PG_2571.2025		
Address ESENTEPE MAH. TAI 34394 KAPI NO: 1 SIS			Flight test		09.10.2020		
	Turkey						
Glider model	SAFE L		Classification		Α		
Serial number	ARTT-L22920-PRLB	<	Representative		None		
Trimmer	no		Place of test		Villeneuve		
Folding lines used	no						
Test pilot		Claude Thurnheer		Alain Zoller			
Harness		Supair s.a.s. Evo XC 3 M		Advance Thun AG Success 4 L			
Harness to risers di	istance [cm]	43	•		43		
Distance between ri		44			48		
					-0		
Total weight in fligh	ıt [kg]	90		119			
1. Inflation/Take-off		Α					
Rising behaviour		Smooth, easy and cor	Smooth, easy and constant rising A		Smooth, easy and constant rising	A	
Special take off technique	required	No A		A	No	A	
2. Landing		A					
Special landing technique	required			А	No	А	
	•						
3. Speed in straight fligh		Α					
Trim speed more than 30	km/h	Yes A		Yes	A		
Speed range using the controls larger than 10 km/h		Yes A		Yes	Α		
Minimum speed		Less than 25 km/h		A	Less than 25 km/h	A	
4. Control movement		Α					
Max. weight in flight up to 80 kg							
Symmetric control pressure / travel		not available		0	not available	0	
Max. weight in flight 80 kg to 100 kg							
Symmetric control pressure / travel		Increasing / greater than 60 cm A		not available	0		
Max. weight in flight greater than 100 kg							
Symmetric control pressure / travel		not available		0	Increasing / greater than 65 cm	A	
5. Pitch stability exiting	accelerated flight	Α					
Dive forward angle on exit		Dive forward less than	1 30°	А	Dive forward less than 30°	А	
Collapse occurs		No		A	Νο	А	
6. Pitch stability operating controls during accelerated flight		A					
accelerated flight Collapse occurs		No A		No	Α		
7. Roll stability and damping		Α					
Oscillations		Reducing		A	Reducing	A	
8. Stability in gentle spirals		A					
Tendency to return to straight flight		Spontaneous exit A		Spontaneous exit	А		

The validation of this test report is given by the signature of the test manager on inspection certificate 91.20 // Rev 08 | 02.02.2025 // ISO | 91.22 // Page 1 of 4

9. Behaviour exiting a fully developed spiral dive	A			
Initial response of glider (first 180°)	Immediate reduction of rate of turn	A	Immediate reduction of rate of turn	A
Tendency to return to straight flight	Spontaneous exit (g force decreasing, rate of turn decreasing)	A	Spontaneous exit (g force decreasing, rate of turn decreasing)	A
Turn angle to recover normal flight	Less than 720°, spontaneous recovery	A	Less than 720°, spontaneous recovery	A
10. Symmetric front collapse Approximately 30 % chord	A			
Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Spontaneous in less than 3 s		Spontaneous in less than 3 s	A
Dive forward angle on exit Change of course	Dive forward 0° to 30° / Keeping course		Dive forward 0° to 30° / Keeping course	A
Cascade occurs	No A		No	A
Folding lines used	No	A	No	A
At least 50% chord Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	A	Dive forward 0° to 30° / Keeping course	A
Cascade occurs	No	A	No	A
Folding lines used	No	A	No	A
With accelerator				
Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	A	Dive forward 0° to 30° / Keeping course	А
Cascade occurs	No	A	No	A
Folding lines used	No	A	No	A
11. Exiting deep stall (parachutal stall)	A		N	
Deep stall achieved	Yes		Yes	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Change of course	Changing course less than 45°	A	Changing course less than 45°	A
Cascade occurs	No	A	No	A
<b>12. High angle of attack recovery</b> Recovery	A Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Cascade occurs	No	A	No	A
<b>13. Recovery from a developed full stall</b> Dive forward angle on exit	<b>A</b> Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Collapse	No collapse	A	No collapse	A
Cascade occurs (other than collapses)	No	A	No	A

Rocking back	Less than 45°		Less than 45°	А
Line tension	Most lines tight		Most lines tight	A
14. Asymmetric collapse	A			
Small asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45° $$	A	Less than 90° / Dive or roll angle 0° to $15^\circ$	A
Re-inflation behaviour	Spontaneous re-inflation		Spontaneous re-inflation	A
Total change of course	Less than 360°		Less than 360°	A
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)		No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No		No	А
Cascade occurs	No	А	No	A
Folding lines used	No		No	А
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45° $$	A	Less than 90° / Dive or roll angle 15° to 45° $$	A
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	А
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	A	No	A
Cascade occurs	No	A	No	A
Folding lines used	No	A	No	А
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45° $$	A	Less than 90° / Dive or roll angle 0° to $15^\circ$	A
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	A
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	A	No	А
Cascade occurs	No	A	No	A
Folding lines used	No	A	No	A
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45° $$	A	Less than 90° / Dive or roll angle 15° to 45°	A
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	А
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	A	No	A
Cascade occurs	No	A	No	A

Folding lines used	Νο	A	No	A
15. Directional control with a maintained	Α			
asymmetric collapse Able to keep course	Yes	А	Yes	А
' 180° turn away from the collapsed side possible in 10 s	Yes	А	Yes	A
	More than 50 % of the symmetric control travel		More than 50 % of the symmetric control travel	A
Amount of control range between turn and stall or spin	·	A		A
<b>16. Trim speed spin tendency</b> Spin occurs	A No	A	No	A
17. Low speed spin tendency Spin occurs	A No	A	No	А
18. Recovery from a developed spin	A			
Spin rotation angle after release	Stops spinning in less than 90°		Stops spinning in less than 90°	А
Cascade occurs	No	A	No	A
19. B-line stall	Α			
Change of course before release	Changing course less than 45°	A	Changing course less than 45°	A
Behaviour before release	Remains stable with straight span	А	Remains stable with straight span	А
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Cascade occurs	No	A	No	A
20. Big ears	Α			
Entry procedure	Dedicated controls	A	Dedicated controls	A
Behaviour during big ears	Stable flight	A	Stable flight	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
21. Big ears in accelerated flight	Α			
Entry procedure	Dedicated controls	A	Dedicated controls	A
Behaviour during big ears	Stable flight	A	Stable flight	А
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	A	Stable flight	A
22. Alternative means of directional control	Α		Mar	
180° turn achievable in 20 s	Yes	A	Yes	A
Stall or spin occurs	No	A	No	A
23. Any other flight procedure and/or configuration described in the user's manual	0			
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0