



Test Report

This test report describes the test results of the below mentioned paragliding harness.

All the tests were carried out by:

Air Turquoise SA, official test laboratory of Switzerland.

para-test.com



paragliding by air turquoise

Standards

Tests were carried out in conformity with the following standards:

- 2. DV LuftGerPV §1, Nr. 7 c (*note: in what follows this will be abbreviated by "LTF")
- European Standard EN1651 September 1999 (*note in what follows this will be abbreviated by "EN")
- European Standard EN12491 September 2001 (*note in what follows this will be abbreviated by "EN12491")

Harness details

| | |
|--------------------------------|----------------------|
| Manufacturer: | KARPO FLY s.r.o. |
| Harness model: | Fantom race series |
| Size: | All |
| Harness Weight: | 4.1 kg |
| Maximum certified pilot | 120 kg |
| Impact protection type: | Inflatable protector |
| Harness type: | ABS |

| | |
|---------------------------------------|-----------------|
| Test responsible: | Alain Zoller |
| Test place: | Villeneuve |
| Test date: | March 20, 2013 |
| Test room temp & humidity: | 24.6°C; 29 %rel |
| Certification number EN: | PH 044.2013 |
| Certification number LTF: | GZ 044.2013 |

page 1 of 4

Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3



Test summary

A. STRUCTURAL STRENGTH TESTS

A test plan was set up in order to execute the different tests in an efficient order. The table below summarizes this test plan together with the applicable standards and results.

| Test ID | TESTED ? | Standard Ref. | | TEST setup | Anchoring | | Forces | | Min. Test duration [sec] | Result |
|---------|----------|---------------|----------------|---------------------------|--------------------------|----------------------------|----------------|----------------|--------------------------|--------|
| | | EN | LTF | | Attach - ment points | Dummy | Req. Load in g | Min. force [N] | | |
| 1 | ✓ | 5.3.2.1 | | Default flying position | 2 main attachment points | Hip fixated | 6g | 6000 | 10 | OK |
| 2 | ✓ | 5.3.2.2 | 4.2.1.a | | | | 9g | 9000 | | |
| 3 | ✓ | | 4.2.1.b | Default, landing position | 2 main att. points | Hip fixated, landing conf. | 6g | 6000 | 10 | OK |
| 4 | ✓ | 5.3.2.7 | | | | | 15g | 15000 | | |
| 5 | ✓ | | 4.2.1.a rescue | Rescue | 2 rescue att. Pnts. | Hip fixated | 9g | 9000 | 10 | OK |
| 6 | ✓ | 5.3.2.4 | | | | | 15g | 15000 | | |
| 7 | ✓ | | 4.2.1.b rescue | Rescue, landing | | Hip fixated, landing conf. | 6g | 6000 | 10 | OK |
| 8 | ✓ | 5.3.2.3 | | One riser | ONE main att. | 1 central hip fixation | 6g | 6000 | 10 | OK |
| 9 | | 5.3.2.5 | 4.2.1.d | Towing | 2 main att. + 2 tow att. | None | 3g | 3000 | 10 | n/a |
| 10 | ✓ | 5.3.2.6 | | Default, Negatif | One main att. | Head fix. | 4.5g | 4500 | 10 | OK |
| 11 | ✓ | | 4.2.1.c | Upside down | 2 main att. downw. | Head fix. | 6g | 6000 | 10 | OK |
| 12 | ✓ | | 4.2.1.c rescue | Upside down rescue | 2 rescue att. downw. | | 6g | 6000 | 10 | OK |

B. HARNESS PROTECTION SHOCK TEST

Most paraglider harnesses are equipped with a protection device that damps the shock on the pilot's spine during a hard landing.

Shock impact tests have to be executed on these harnesses in order to prove the damping characteristics of it.



| Test ID | TESTED ? | Standar d Ref.: | TEST setup | Anchoring | | Impact | | | Result | | |
|---------------------------|----------|--------------------|--|---|-------|------------------------------------|-----------------------------|--|--------|--|-----------|
| | | LTF | | Attach- ment points | Dummy | Max. tolerated peak impact in g | Max Peak impact measured | Impact duration of + 38 g (if any) recorded: | | Impact duration of + 20 g (if any) recorded: | |
| PRO TECT 1 | ✓ | 5.1.1 | Default flying position | Test dummy is attached to the harness like a pilot in flight. | | | +50g | 26.0 g | 0 | 18 ms | OK |

C. RESCUE DEPLOYMENT RESISTANCE TEST

The deployment of the rescue system has to be ensured in all circumstances of flight. This test is to verify whether the force needed to deploy is in between reasonable limits.

| Test ID | TESTED ? | Standar d Ref. | TEST setup | Anchoring | | Force for single hand deployment | | | Result | |
|----------------------|----------|-------------------|--|---|-------|----------------------------------|----------------------|---------------------------------|--------|-----------|
| | | LTF | | Attach- ment points | Dummy | Min. force [N] | max. force [N] | Resistance measured [daN] | | |
| Resc depl | ✓ | 6.1.5 | Default flying position | Test responsible is attached to the harness like a pilot in flight. (no dummy required) | | | 20 N | 70 N | n/t | OK |

D. RESCUE DEPLOYMENT STRAP STRENGTH TEST

The connection between handgrip and inner container has to have sufficient load capacity/structural strength in any situation that may arise during normal use. During this test is verified, whether this connection fulfill the requirements.

| Test ID | TESTED ? | Standard Ref. | | TEST setup | Minimum force [N] | Min. Test durati on [s] | Breaking resistance measured | Result |
|-----------------------|----------|---------------|-------------|---|----------------------|-------------------------------------|------------------------------------|-----------|
| | | LTF | EN 12491 | | | | | |
| Resc strap | ✓ | 6.1.8 | 5.3.2 | Connection strap in tensile testing machine | 700N | 10 | n/t | OK |

After careful examination as explained in above mentioned test reports (from page 2 to page 18), the undersigned persons declare that the harness:

KARPO FLY s.r.o.
Fantom race series
All

Complied with:

- **European Standard EN 1651 September 1999**

And / or (if tested)

- **European Standard EN 12491 March 2001**

And / or (if tested)

- **2. DV LuftGerPV §1, Nr. 7 c**

Villeneuve, March 20, 2013

Place, Date

Alain Zoller

Test responsible



page 4 of 4



Annex: detailed test reports


Harness Test

Test ID 1

Item: Fantom race series
Manufacturer: KARPO FLY s.r.o.
Test place & date: Villeneuve March 20, 2013
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 24.6°C; 29 %rel
Maximum certified pilot weight [kg]: 120 kg

Standard: EN 1651 & 2. DV LuftGerPV §1, Nr. 7 c
Test standard §: 5.3.2.1 (EN) & 4.2.1 a (LTF DV)

Test setup: Default flying position
Anchoring: Attachment points: Both main riser attachments (3, 4)
Dummy: Default, hip fixed (7, 8)



Required load in g : 9g (EN: 6g)
Minimum load [N]: 9000 N (EN: 6000 N)
Required test load in kg: **1080 kg**
Min. duration [s]: 10 s


Results

Duration of maintained min. load [s]: **10.9 s**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 1
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3



| Harness Test | | Test ID 2 |
|--------------------------------------|------------------------------------|----------------|
| Item: | Fantom race series | |
| Manufacturer | KARPO FLY s.r.o. | |
| Test place & date: | Villeneuve | March 20, 2013 |
| Test responsible: | Alain Zoller | |
| Temp. [°C] & Humidity: | 24.6°C; 29 %rel | |
| Maximum certified pilot weight [kg]: | 120 | kg |
| Standard | EN 1651 | |
| Test standard §: | 5.3.2.2 | |
| Test setup: | Default flying position | |
| Anchoring: Attachment points: | Both main riser attachments (3, 4) | |
| Dummy: | Default, hip fixed (7, 8) | |
| Required load in g: | 15 | g |
| Min load [N]: | 15 000 N | |
| Required test load in kg: | 1800 | kg |
| Min. duration [s]: | 5s | |

| Results | |
|--|--------------------|
| Duration of maintained min. load [s]: | 5.7 s |
| Any signs of structural failure after this test: | No visible failure |
| Test result: | Passed |

Graph:

— TEST ID 2: EN 5.3.2.2
 — Norm 1500 daN

| Time (s) | Force (daN) - TEST ID 2 | Force (daN) - Norm |
|----------|-------------------------|--------------------|
| 5 | 0 | 1500 |
| 15 | 200 | 1500 |
| 25 | 600 | 1500 |
| 35 | 1000 | 1500 |
| 45 | 1500 | 1500 |
| 46 | 100 | 1500 |
| 47 | 600 | 1500 |
| 48 | 1100 | 1500 |
| 50 | 1500 | 1500 |
| 55 | 1900 | 1500 |
| 56 | 2000 | 1500 |
| 57 | 1800 | 1500 |
| 60 | 1800 | 1500 |
| 61 | 300 | 1500 |
| 62 | 100 | 1500 |
| 65 | 0 | 1500 |

Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 2
Prepared by RE
Rev.0, 25.01.2011
No. 71.9.3



Harness Test

Test ID 3

Item: Fantom race series
 Manufacturer: KARPO FLY s.r.o.
 Test place & date: Villeneuve March 20, 2013
 Test responsible: Alain Zoller
 Temp. [°C] & Humidity: 24.6°C; 29 %rel
 Maximum certified pilot weight [kg]: 120 kg

Standard: 2. DV LuftGerPV §1, Nr. 7 c

Test standard §: 4.2.1.b

Test setup: Flying position before landing: seat board (11) in landing position, leg straps (10) closed.

Anchoring: Attachment points: Both of the main riser attachments attached (3 and 4);


Dummy: Default, hip fixed (7, 8)

Required load in g: 6 g

Min load [N]: 6000 N

Required test load in kg: **720** kg

Min. duration [s]: 10 s




Results

Duration of maintained min. load [s]: **10.5 s**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 3
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3



Harness Test

Test ID 4

Item: Fantom race series
 Manufacturer: KARPO FLY s.r.o.
 Test place & date: Villeneuve March 20, 2013
 Test responsible: Alain Zoller
 Temp. [°C] & Humidity: 24.6°C; 29 %rel
 Maximum certified pilot weight [kg]: 120 kg

Standard: EN 1651

Test standard §: EN 5.3.2.7

Test setup: Flying position before landing: seat board (11) in landing position, leg straps (10) closed.

Anchoring: Attachment points: Both of the main riser attachments attached (3 and 4);


Dummy: Default, hip fixed (7, 8)

Required load in g: 15 g

Min load [N]: 15 000 N

Required test load in kg: **1800 kg**

Min. duration [s]: 5 s




Results

Duration of maintained min. load [s]: **6.4 s**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 4
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3



Harness Test

Test ID 5

Item: Fantom race series
 Manufacturer: KARPO FLY s.r.o.
 Test place & date: Villeneuve March 20, 2013
 Test responsible: Alain Zoller
 Temp. [°C] & Humidity: 24.6°C; 29 %rel
 Maximum certified pilot weight [kg]: 120 kg

Standard: 2. DV LuftGerPV §1, Nr. 7 c

Test standard §: 4.2.1.a rescue

Test setup: Rescue attachments

Anchoring: Attachment points: Rescue riser attachments (1,2)


Dummy: Hip fixed (7, 8)

Required load in g: 9 g

Min load [N]: 9 000 N

Required test load in kg: **1080 kg**

Min. duration [s]: 10 s




Results

Duration of maintained min. load [s]: **11.8 s**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 5
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3



Harness Test

Test ID 6


| | | |
|---|--------------------|----------------|
| Item: | Fantom race series | |
| Manufacturer | KARPO FLY s.r.o. | |
| Test place & date: | Villeneuve | March 20, 2013 |
| Test responsible: | Alain Zoller | |
| Temp. [°C] & Humidity: | 24.6°C; 29 %rel | |
| Maximum certified pilot weight [kg]: | 120 | kg |

| | |
|-------------------------|--------------------|
| Standard | EN 1651 |
| Test standard §: | 5.3.2.4 |
| Test setup: | Rescue attachments |

Anchoring: Attachment points: Rescue riser attachments (1,2)

Dummy: Hip fixed (7, 8)

| | | |
|----------------------------------|-------------|-----------|
| Required load in g: | 15 | g |
| Min load [N]: | 15 000 | N |
| Required test load in kg: | 1800 | kg |
| Min. duration [s]: | 5 | s |




Results

Duration of maintained min. load [s]: **6.4 s**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 6
Prepared by RE
Rev.0, 25.01.2011
No. 71.9.3



Harness Test

Test ID 7

Item: Phantom race series
Manufacturer: KARPO FLY s.r.o.
Test place & date: Villeneuve March 20, 2013
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 24.6°C; 29 %rel
Maximum certified pilot weight [kg]: 120 kg

Standard: 2. DV LuftGerPV §1, Nr. 7 c

Test standard §: 4.2.1.b rescue

Test setup: Flying position before landing: seat board (11) in landing position, leg straps (10) closed.

Anchoring: Attachment points: Both of the rescue riser attachments attached (1 and 2);


Dummy: Default, hip fixed (7, 8)

Required load in g: 6 g

Min load [N]: 6 000 N

Required test load in kg: 720 kg

Min. duration [s]: 10 s




Results

Duration of maintained min. load [s]: 11 s

Any signs of structural failure after this test: No visible failure

Test result: Passed

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 7
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3



Harness Test

Test ID 8


Item: Fantom race series
 Manufacturer: KARPO FLY s.r.o.
 Test place & date: Villeneuve March 20, 2013
 Test responsible: Alain Zoller
 Temp. [°C] & Humidity: 24.6°C; 29 %rel
 Maximum certified pilot weight [kg]: 120 kg

Standard: EN 1651
 Test standard §: 5.3.2.3
 Test setup: Only one riser attached

Anchoring: Attachment points: One main riser attachments (3)

Dummy: Hip fixed (7, 8 -> 12)

Required load in g: 6 g
 Min load [N]: 6 000 N
 Required test load in kg: **720 kg**
 Min. duration [s]: 10 s




Results

Duration of maintained min. load [s]: **11.7 s**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c


Annex TEST ID 8
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3



Harness Test **Test ID 10**

Item: Phantom race series
Manufacturer: KARPO FLY s.r.o.
Test place & date: Villeneuve March 20, 2013
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 24.6°C; 29 %rel
Maximum certified pilot weight [kg]: 120 kg


Standard: EN 1651
Test standard §: 5.3.2.6
Test setup: Normal flying position in NEGATIF
Anchoring: Attachment points: ONE of the main riser attachments attached downwards(3 or 4);
Dummy: Dummy anchored at the head position (9)
Required load in g: 4.5 g
Min load [N]: 4500 N
Required test load in kg: **540** kg
Min. duration [s]: 10 s



Results

Duration of maintained min. load [s]: **11.8 s**
Any signs of structural failure after this test: **No visible failure**
Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c


Annex TEST ID 10
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3

Harness Test

Test ID 11

Item: Fantom race series
Manufacturer: KARPO FLY s.r.o.
Test place & date: Villeneuve March 20, 2013
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 24.6°C; 29 %rel
Maximum certified pilot weight [kg]: 120 kg


Standard: 2. DV LuftGerPV §1, Nr. 7 c
Test standard §: 4.2.1.c
Test setup: Pilot upside down flying position
Anchoring: Attachment points: Both of the main riser attachments attached downwards (3 and 4);
Dummy: Dummy anchored at the head position (9)
Required load in g: 6 g
Min load [N]: 6 000 N
Required test load in kg: **720 kg**
Min. duration [s]: 10 s



Results

Duration of maintained min. load [s]: **11.2 s**
Any signs of structural failure after this test: **No visible failure**
Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID 11
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3



Harness Test

Test ID 12

Item: Fantom race series
Manufacturer: KARPO FLY s.r.o.
Test place & date: Villeneuve March 20, 2013
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 24.6°C; 29 %rel
Maximum certified pilot weight [kg]: 120 kg

Standard 2. DV LuftGerPV §1, Nr. 7 c

Test standard §: 4.2.1.c rescue

Test setup: Pilot upside down flying position

Anchoring: Attachment points: Both of the rescue riser attachments attached downwards (1 and 2);


Dummy: Dummy anchored at the head position (9)

Required load in g: 6 g

Min load [N]: 6 000 N

Required test load in kg: **720 kg**

Min. duration [s]: 10 s




Results

Duration of maintained min. load [s]: **11.8 s**

Any signs of structural failure after this test: **No visible failure**

Test result: **Passed**

Graph:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c


Annex TEST ID 12
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3




| Protector shock test | | Test ID Protect |
|---|--|--|
| Item: | Fantom race series | |
| Manufacturer | KARPO FLY s.r.o. | |
| Test place & date: | Villeneuve March 20, 2013 | |
| Test responsible: | Alain Zoller | |
| Temp. [°C] & Humidity: | 24.6°C; 29 %rel | |
| Maximum certified pilot weight [kg]: | 120 kg | |
| Standard | 2. DV LuftGerPV §1, Nr. 7 c | |
| Test standard §: | 5.1.1 | |
| Test setup: | <p>Harness attached to protector test dummy, in a similar way like a real pilot in flight.</p> <p>Impact will be simulated by dropping the dummy from a certain height (with and without reserve).</p> <p>To simulate the "in-flight" conditions, the airbag is inflated with pressurized air equalling an airspeed of 7m/s. Inflation has to be stopped at least 5 sec before impact.</p> <p>Impact will be measured by an accelerometer mounted on the dummy. (Impact measured in g's)</p> | |
| Requirements: | Minimum height: | 1.65 m (between lowest point test dummy and impact surface) |
| | Impact requirements: | +50g as absolute maximum; +38g during less than 7 msec; +20g during less than 25 msec. |
| | Repetitions: | The test will be performed 2 times, minimum 1 hour and maximum 2 hours after the first impact (with airbag protectors this pause is not necessary). The 2 Max-values should not differ more than 20% |
| Results | | |
| Shock test 1: | | |
| Impact at a height of 1.65m: | 26.0 g | |
| Impact duration of + 38 g (if any): | 0 | |
| Impact duration of +20 g (if any): | 18 ms | |
| Shock test 2: | | |
| Impact at a height of 1.65m: | 25.84 g | |
| Impact duration of + 38 g (if any): | 0 | |
| Impact duration of +20 g (if any): | 21 ms | |
| Test Result: | Passed | |



Graph 1:



Graph 2:



Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
 Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID Protect 1
 Prepared by RE
 Rev.0, 25.01.2011
 No. 71.9.3



| Rescue deployment resistance test | | Test ID resc |
|---|---|---|
| Item: | Fantom race series | |
| Manufacturer | KARPO FLY s.r.o. | |
| Test place & date: | Villeneuve | March 20, 2013 |
| Test responsible: | Alain Zoller | |
| Temp. [°C] & Humidity: | 24.6°C; 29 %rel | |
| Maximum certified pilot weight [kg]: | 120 | kg |
| Standard | 2. DV LuftGerPV §1, Nr. 7 c | |
| Test standard §: | 6.1.5 | |
| Test setup: | <p>The deployment of the rescue system has to be ensured in all circumstances, especially with a damaged glider.</p> <p>The pilot has to be able to deploy the rescue chute with a single pull out of the outer container, single handed and in an anatomical favorable direction.</p> <p>In order to simulate this, the test responsible deploys the rescue seated in the harness. In a similar way as in real flight. The deployment resistance is approximately measured by the load cell, which is placed between the hand of the test responsible and the rescue hand grip.</p> <p>On the other hand inadvertent deployment has to be fairly remote. Therefore a shear link has to withstand a minimum load.</p> | |
| Requirements: | <p>Max force for single hand deployment:</p> <p>Min force to prevent unwanted opening:</p> | <p>approx. 70 N</p> <p>approx. 20 N</p> |
| Results | | |
| Measured peak to peak required force for deployment [daN]: | | 6.6 |
| Comment: | Passed | |
| Graph: | | |

Air Turquoise SA certified by



Air Turquoise S.A. - Certification of paraglider equipment
Tested in accordance with EN 1651:1999 and 2.DV LuftGerPV§1, Nr.7c

Annex TEST ID resc depl
Prepared by RE
Rev.0, 25.01.2011
No. 71.9.3



Rescue deployment strap strength test

Test ID resc strap

Item: Phantom race series
Manufacturer: KARPO FLY s.r.o.
Test place & date: Villeneuve March 20, 2013
Test responsible: Alain Zoller
Temp. [°C] & Humidity: 24.6°C; 29 %rel
Maximum certified pilot weight [kg]: 120 kg

Standard EN 12491 & 2. DV LuftGerPV §1, Nr. 7 c

Test standard §: 5.3.2 (EN 12491) & 6.1.8 (LTF)

Test setup: The handgrip of the outer container has to be connected to the inner container with a removable loop in a way that it is possible to use the inner container with different types of outer containers.
 The connection between handgrip and inner container has to have sufficient load capacity/structural strength in any situation that may arise during normal operation.
 In order to verify this, the connection is tested on its tensile strength by a default tensile testing setup.
 In addition to this the breaking resistance will also be measured.

Requirements: Min. tensile strenght for 10 s: 700 N (= 70daN)

Results

Duration of maintained load [s]: 11.5 s

Breaking resistance [daN]: 700

Comment: Passed

Graph:

