

Flight test report: EN 926-2:2013+A1:2021 and NfL 2024-2-785

Manufacturer	Mac Para Technology	Certification number	PG_2743.2026
Address	Televizní 2615 756 61 Roznov pod Radhostem Czech Republic	Flight test	14.07.2026
Glider model	Elixir 29	Classification	C
Serial number	4429-1507	Representative	None
Trimmer	no	Place of test	Villeneuve
Folding lines used	yes		
Test pilot	Claude Thurnheer	Alexandre Jofresa	
Harness	Advance Thun AG Success 4 M	Advance Thun AG Success 4 M	
Harness to risers distance [cm]	43	43	
Distance between risers [cm]	46	48	
Total weight in flight [kg]	108	119	
1. Inflation/Take-off	C		
Rising behaviour	Overshoots, shall be slowed down to avoid a front collapse	C	Overshoots, shall be slowed down to avoid a front collapse C
Special take off technique required	No	A	No A
2. Landing	A		
Special landing technique required	No	A	No A
3. Speed in straight flight	A		
Trim speed more than 30 km/h	Yes	A	Yes A
Speed range using the controls larger than 10 km/h	Yes	A	Yes A
Minimum speed	Less than 25 km/h	A	Less than 25 km/h A
4. Control movement	B		
Max. weight in flight up to 80 kg			
Symmetric control pressure / travel	not available	0	not available 0
Max. weight in flight 80 kg to 100 kg			
Symmetric control pressure / travel	not available	0	not available 0
Max. weight in flight greater than 100 kg			
Symmetric control pressure / travel	Increasing / greater than 65 cm	A	Approximately constant / greater than 65 cm B
5. Pitch stability exiting accelerated flight	A		
Dive forward angle on exit	Dive forward less than 30°	A	Dive forward less than 30° A
Collapse occurs	No	A	No A
6. Pitch stability operating controls during accelerated flight	A		
Collapse occurs	No	A	No A
7. Roll stability and damping	A		
Oscillations	Reducing	A	Reducing A
8. Stability in gentle spirals	A		
Tendency to return to straight flight	Spontaneous exit	A	Spontaneous exit A

9. Behaviour exiting a fully developed spiral dive		B	
Initial response of glider (first 180°)	No immediate reaction	B No immediate reaction	B
Tendency to return to straight flight	Spontaneous exit (g force decreasing, rate of turn decreasing)	A Spontaneous exit (g force decreasing, rate of turn decreasing)	A
Turn angle to recover normal flight	Less than 720°, spontaneous recovery	A Less than 720°, spontaneous recovery	A
10. Symmetric front collapse		C	
Approximately 30 % chord			
Entry	Rocking back less than 45°	A Rocking back less than 45°	A
Recovery	Spontaneous in less than 3 s	A Spontaneous in 3 s to 5 s	B
Dive forward angle on exit Change of course	Dive forward 0° to 30° / Keeping course	A Dive forward 0° to 30° / Keeping course	A
Cascade occurs	No	A No	A
Folding lines used	Yes	C Yes	C
At least 50% chord			
Entry	Rocking back less than 45°	A Rocking back less than 45°	A
Recovery	Spontaneous in 3 s to 5 s	B Spontaneous in 3 s to 5 s	B
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	A Dive forward 30° to 60° / Keeping course	B
Cascade occurs	No	A No	A
Folding lines used	Yes	C Yes	C
With accelerator			
Entry	Rocking back less than 45°	A Rocking back less than 45°	A
Recovery	Spontaneous in 3 s to 5 s	B Spontaneous in less than 3 s	A
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	A Dive forward 30° to 60° / Keeping course	B
Cascade occurs	No	A No	A
Folding lines used	Yes	C Yes	C
11. Exiting deep stall (parachutal stall)		B	
Deep stall achieved	Yes	A Yes	A
Recovery	Spontaneous in less than 3 s	A Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A Dive forward 30° to 60°	B
Change of course	Changing course less than 45°	A Changing course less than 45°	A
Cascade occurs	No	A No	A
12. High angle of attack recovery		A	
Recovery	Spontaneous in less than 3 s	A Spontaneous in less than 3 s	A
Cascade occurs	No	A No	A
13. Recovery from a developed full stall		B	
Dive forward angle on exit	Dive forward 30° to 60°	B Dive forward 0° to 30°	A
Collapse	No collapse	A No collapse	A
Cascade occurs (other than collapses)	No	A No	A

Rocking back	Less than 45°	A	Less than 45°	A
Line tension	Most lines tight	A	Most lines tight	A
14. Asymmetric collapse		C		
Small asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	A	Less than 90° / Dive or roll angle 15° to 45°	A
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	A
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous re-inflation)	A	No (or only a small number of collapsed cells with a spontaneous re-inflation)	A
Twist occurs	No	A	No	A
Cascade occurs	No	A	No	A
Folding lines used	Yes	C	Yes	C
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	B	Less than 90° / Dive or roll angle 15° to 45°	A
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	A
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous re-inflation)	A	No (or only a small number of collapsed cells with a spontaneous re-inflation)	A
Twist occurs	No	A	No	A
Cascade occurs	No	A	No	A
Folding lines used	Yes	C	Yes	C
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	A	Less than 90° / Dive or roll angle 15° to 45°	A
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	A
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous re-inflation)	A	No (or only a small number of collapsed cells with a spontaneous re-inflation)	A
Twist occurs	No	A	No	A
Cascade occurs	No	A	No	A
Folding lines used	Yes	C	Yes	C
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	B	Less than 90° / Dive or roll angle 15° to 45°	A
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	A
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous re-inflation)	A	No (or only a small number of collapsed cells with a spontaneous re-inflation)	A
Twist occurs	No	A	No	A
Cascade occurs	No	A	No	A

Folding lines used	Yes	C	Yes	C
15. Directional control with a maintained asymmetric collapse	A			
Able to keep course	Yes	A	Yes	A
180° turn away from the collapsed side possible in 10 s	Yes	A	Yes	A
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	A	More than 50 % of the symmetric control travel	A
16. Trim speed spin tendency	A			
Spin occurs	No	A	No	A
17. Low speed spin tendency	A			
Spin occurs	No	A	No	A
18. Recovery from a developed spin	B			
Spin rotation angle after release	Stops spinning in 90° to 180°	B	Stops spinning in 90° to 180°	B
Cascade occurs	No	A	No	A
19. B-line stall	0			
Change of course before release	not available	0	not available	0
Behaviour before release	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit	not available	0	not available	0
Cascade occurs	not available	0	not available	0
20. Big ears	A			
Entry procedure	Dedicated controls	A	Dedicated controls	A
Behaviour during big ears	Stable flight	A	Stable flight	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
21. Big ears in accelerated flight	A			
Entry procedure	Dedicated controls	A	Dedicated controls	A
Behaviour during big ears	Stable flight	A	Stable flight	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	A	Stable flight	A
22. Alternative means of directional control	A			
180° turn achievable in 20 s	Yes	A	Yes	A
Stall or spin occurs	No	A	No	A
23. Any other flight procedure and/or configuration described in the user's manual	A			
Procedure works as described	Yes	A	Yes	A
Procedure suitable for novice pilots	Yes	A	Yes	A
Cascade occurs	No	A	No	A

