

# Harness Impact Pad Report

Inspection certificate number: **PH\_440.2024**

## Manufacturer data:

Manufacturer name: **Neo SAS**  
 Representative: **Eric Roussel**  
 Street: **ZA des Vernays**  
 Post code place: **74210 Doussard**  
 Country: **France**

Harness model: **MOON PRO MODEL**

## Sample data:

Name impact pad: **n/a**  
 Impact pad integrated: **No**  
 Impact pad type: **Koroyd**  
 Weight of sample [kg]: **0.21**  
 Serial number: **110 002**  
 Date of test: **01.03.2021**

## Atmosphere AGL:

Temp. [C°]	<b>20</b>
R.H. [%]	<b>33</b>
Press. [hPa]	<b>1018</b>

## Summary of Impact pad test <sup>(1)</sup>

Test id	–	Test configuration <sup>(2)</sup>	Max Peak of Impact [g] <sup>(3)</sup>	Duration at 38 [g] in [ms] <sup>(4)</sup>	Duration at 20 [g] in [ms] <sup>(5)</sup>	Diff. of test 1 and 2 [%]	Result
P	V	Test sample attached to dummy in flying position, without emergency parachute	<b>44.54</b>	<b>6.67</b>	<b>17.50</b>	<b>n/a</b>	<b>POSITIVE</b>
PR		Test sample attached to dummy in flying position, Including emergency parachute	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>	<b>n/a</b>	<b>n/a</b>

Manufacturer	Instrument	Type no	S/N	Validity Calibration
Burster/MTS	Accelerometer 100 g	89010-100	1263567	23.01.2024
JDC elec	Geos n°11 Skywatch	Geos n°11	Unit11	18.06.2025

The validation of this test report is given by the signature of the test manager on the Inspection Certificate no 94.20a or 94.20b

**Air Turquoise SA**, has thoroughly tested the sample mentioned above and certifies its conformity with the following standards:

**EN1651:2018+A1:2020<sup>(7)</sup>**

<sup>(1)</sup> Calculated values in tests reports include the value minus the uncertainty (on safe side) / The uncertainty stated is the expanded uncertainty obtained by multiplying the standard uncertainty by the coverage factor  $k = 2$ . The value of the measurand lies within the assigned range of values with a probability of 95%

<sup>(2)</sup> The dummy is lifted minimum up to 1.65 m, and impact pad is mounted on. Where the impact occurs, measure distance from bottom of impact pad to ground

<sup>(3)</sup> Maximum peak of impact should be less or equal to 50 [g], <sup>(4)</sup> If any, the maximum duration in at 38 [g] should be less or equal to 7 [ms], <sup>(5)</sup> If any, the maximum duration in at 20 [g] should be less or equal to 25 [ms].

<sup>(7)</sup> This standard is NOT covered by accreditation D-IS-19457-01

This declaration must not be reproduced in part without the written permission of AIR TURQUOISE SA

Inspection certificate number: **PH\_440.2024**

Name impact pad: **n/a**

**Test results of Impact pad test**

	without emergency parachute		including emergency parachute	
	P1	P2	PR1	PR2
Maximum peak of impact [g]	<b>44.54</b>	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>
Impact duration at +38 [g] in [ms]	<b>6.67</b>	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>
Impact duration at +20 [g] in [ms]	<b>17.50</b>	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>
Uncertainty k=2 [g]	<b>2.56</b>	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>
Diff. between test 1 and 2 [%]	<b>100.00</b>	<b>0.00</b>	<b>100.00</b>	<b>0.00</b>

