## AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Compte 8 • CH-1844 Villeneuve • +41 (0)21 965 65 65

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes

Manufacturer



Certification number PG\_2554.2025

## Flight test report: EN 926-2:2013+A1:2021 and NfL 2024-2-785

Niviuk Gliders / Air Games S.L.

	Manufacturei	NIVIUK Gliders / Air G	iames S.L.	Certification numb	Jei	PG_2554.2025	
	Address C. Del Ter, 6 Nave D 17165 La Cellera de 3		Flight test			07.04.2025	
			er Girona	3			
		Spain					
	Glider model	Artik R2 21		Classification		С	
	Serial number	ARTIKR24221		Representative		None	
	Trimmer	no		Place of test		Villeneuve	
	Folding lines used	yes					
	i diding lines dised	yco					
	Test pilot		Nicole Fedele			Claude Thurnheer	
	Harness		Advance Thun AG Success 4 M			Niviuk Makan M	
	Harness to risers distance [cm]		43		41		
	Distance between ris		40		44		
	Distance between in	sers [ciii]	40			44	
	Total weight in flight	t [ka]	70		05		
	Total weight in high	ı [kg]	70			85	
	1. Inflation/Take-off		С				
	Rising behaviour		Overshoots, shall be slowed down to avoid a front		С	Overshoots, shall be slowed down to avoid a front	С
			collapse			collapse	
	Special take off technique	required	No		Α	No	Α
	2. Landing		Α				
	Special landing technique	required	No		Α	No	Α
	3. Speed in straight flight		В				
	Trim speed more than 30 km/h		Yes		Α	Yes	Α
	Speed range using the con	ntrols larger than 10 km/h	Yes		Α	Yes	Α
	Minimum speed		Less than 25 km/h		Α	25 km/h to 30 km/h	В
	4. Control movement		С				
	Max. weight in flight up to	o 80 ka					
Symmetric control pressure / travel		Increasing / 40 cm to 5	5 cm	С	not available	0	
			· ·				
	Max. weight in flight 80 k	g to 100 kg					
	Symmetric control pressure	e / travel	not available		0	Increasing / 45 cm to 60 cm	С
	Max. weight in flight grea	otor than 100 kg					
	Symmetric control pressure	<del>-</del>	not available		0	not available	0
	Symmetric control pressure	e / liavei	not available		U	not available	Ü
	5. Pitch stability exiting a	ccelerated flight	Α				
	Dive forward angle on exit		Dive forward less than	30°	Α	Dive forward less than 30°	Α
	Collapse occurs		No		Α	No	Α
	6. Pitch stability operatin	g controls during	Α				
	accelerated flight						
	Collapse occurs		No		Α	No	Α
	7. Roll stability and damping		Α				
	Oscillations		Reducing		Α	Reducing	Α
	8. Stability in gentle spira		Α				
	Tendency to return to straig	ght flight	Spontaneous exit		Α	Spontaneous exit	Α

Behaviour exiting a fully developed spiral dive	B No immediate reaction	D	No immediate resetion	
nitial response of glider (first 180°)	No immediate reaction	В	No immediate reaction	
endency to return to straight flight	Spontaneous exit (g force decreasing, rate of turn decreasing)	Α	Spontaneous exit (g force decreasing, rate of turn decreasing)	
urn angle to recover normal flight	720° to 1 080°, spontaneous recovery	В	Less than 720°, spontaneous recovery	
0. Symmetric front collapse pproximately 30 % chord	С			
Entry	Rocking back less than 45°	Α	Rocking back less than 45°	
lecovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	
ive forward angle on exit Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	
ascade occurs	No	Α	No	
olding lines used	Yes	С	Yes	
t least 50% chord ntry	Rocking back less than 45°	Α	Rocking back less than 45°	
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	
ive forward angle on exit / Change of course	Dive forward 30° to 60° / Keeping course	В	Dive forward 0° to 30° / Keeping course	
ascade occurs	No	Α	No	
olding lines used	Yes	С	Yes	
/ith accelerator				
intry	Rocking back greater than 45°	С	Rocking back less than 45°	
ecovery	Spontaneous in 3 s to 5 s	В	Spontaneous in less than 3 s	
vive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	
ascade occurs	No	Α	No	
olding lines used	Yes	С	Yes	
1. Exiting deep stall (parachutal stall)	A	•	Wes	
eep stall achieved	Yes		Yes	
decovery	Spontaneous in less than 3 s		Spontaneous in less than 3 s	
live forward angle on exit	Dive forward 0° to 30°		Dive forward 0° to 30°	
hange of course	Changing course less than 45°	Α	Changing course less than 45°	
ascade occurs	No	A	No	
2. High angle of attack recovery lecovery	A Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	
Cascade occurs	No	Α	No	
3. Recovery from a developed full stall	A			
live forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	
ollapse	No collapse	Α	No collapse	
ascade occurs (other than collapses)	No	Α	No	

Rocking back	Less than 45°	Α	Less than 45°	Α
Line tension	Most lines tight	Α	Most lines tight	Α
14. Asymmetric collapse Small asymmetric collapse	С			
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 0° to 15°	Α	Less than 90° / Dive or roll angle 15° to 45°	Α
Re-inflation behaviour	Inflates in less than 3 s from start of pilot action	С	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes	С	Yes	С
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Inflates in less than 3 s from start of pilot action	С	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes	С	Yes	С
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	Less than 90° / Dive or roll angle 15° to 45°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Inflates in less than 3 s from start of pilot action	С
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes	С	Yes	С
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 45° to 60°	С	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	Α	Inflates in less than 3 s from start of pilot action	С
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α

Folding lines used	Yes	С	Yes	С
15. Directional control with a maintained asymmetric collapse	A			
Able to keep course	Yes	Α	Yes	Α
180° turn away from the collapsed side possible in 10 s	Yes	Α	Yes	Α
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	Α	More than 50 % of the symmetric control travel	Α
16. Trim speed spin tendency	A			
Spin occurs	No	Α	No	Α
17. Low speed spin tendency	A No	٨	No	٨
Spin occurs	INU	^	NU	Α
18. Recovery from a developed spin	В			
Spin rotation angle after release	Stops spinning in less than 90°	Α	Stops spinning in 90° to 180°	В
Cascade occurs	No	Α	No	Α
19. B-line stall	0			
Change of course before release	not available	0	not available	0
Behaviour before release	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit	not available	0	not available	0
Cascade occurs	not available	0	not available	0
20. Big ears	В			
Entry procedure	Dedicated controls	Α	Dedicated controls	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Recovery through pilot action in less than a further 3 s	В	Recovery through pilot action in less than a further 3 s	В
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
21. Big ears in accelerated flight	В			
Entry procedure	Dedicated controls	Α	Dedicated controls	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Recovery through pilot action in less than a further 3 s	В	Recovery through pilot action in less than a further 3 s	В
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	Α	Stable flight	Α
22. Alternative means of directional control	A			
180° turn achievable in 20 s	Yes	Α	Yes	Α
Stall or spin occurs	No	Α	No	Α
23. Any other flight procedure and/or configuration described in the user's manual	0			
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0