AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Compte 8 • CH-1844 Villeneuve • +41 (0)21 965 65 65

Ozone Gliders LTD

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes

Manufacturer



Certification number PG_2572.2025

Flight test report: EN 926-2:2013+A1:2021 and NfL 2024-2-785

Address	16 Barnes Green EH54 8PP Livingston United Kingdom		Flight test		19.05.2025		
Glider model	Delta 5 S		Classification		С		
Serial number	PR2-A-11B-081		Representative		None		
Trimmer	no		Place of test		Villeneuve		
Folding lines used	yes						
r olding imes doed	,						
Test pilot		Nicole Fedele			Victor Chinen Cirilli		
Harness		Woody Valley	srl Wani Light 2 S		Advance Thun AG Success 4 M		
Harness to risers d	istance [cm]	41	· ·		43		
Distance between r		40			44		
Total weight in fligh	nt [kg]	65			85		
1. Inflation/Take-off		C					
Rising behaviour		Overshoots, shall be s collapse	slowed down to avoid a front	С	Overshoots, shall be slowed down to avoid a front collapse	C	
Special take off technique	required	No		Α	No	Α	
2. Landing		Α					
Special landing technique required		No		Α	No	Α	
3 Speed in straight fligh	nt	В					
3. Speed in straight flight Trim speed more than 30 km/h		Yes		Α	Yes	Α	
Speed range using the co	ntrols larger than 10 km/h	Yes		Α	Yes	Α	
Minimum speed		Less than 25 km/h		Α	25 km/h to 30 km/h	В	
4. Control movement	4 - 00 los	С					
Max. weight in flight up to 80 kg Symmetric control pressure / travel		Increasing / 40 cm to s	55 cm	С	not available	0	
Symmetric control pressu	ie / liavei	moreasing / 40 cm to t	50 GIII	Ü	not available	Ü	
Max. weight in flight 80	kg to 100 kg						
Max. weight in flight 80 kg to 100 kg Symmetric control pressure / travel		not available		0	Increasing / 45 cm to 60 cm	С	
May waight in flight are	atou than 100 km						
Max. weight in flight gre Symmetric control pressure	_	not available		0	not available	0	
Symmetric control pressu	ie / liavei	not available		Ü	not available	Ü	
5. Pitch stability exiting	accelerated flight	Α					
Dive forward angle on exi	t	Dive forward less than	130°	Α	Dive forward less than 30°	Α	
Collapse occurs		No		Α	No	Α	
Collapse occurs		NO		^	INO	^	
6. Pitch stability operation accelerated flight	ng controls during	A					
Collapse occurs		No		Α	No	Α	
7. Roll stability and dam	ping	Α					
Oscillations		Reducing		Α	Reducing	Α	
8. Stability in gentle spirals		A					
Tendency to return to stra	ight flight	Spontaneous exit		Α	Spontaneous exit	Α	

9. Behaviour exiting a fully developed spiral dive	В			
Initial response of glider (first 180°)	No immediate reaction	В	Immediate reduction of rate of turn	A
Tendency to return to straight flight	Spontaneous exit (g force decreasing, rate of turn decreasing)	Α	Spontaneous exit (g force decreasing, rate of turn decreasing)	Α
Turn angle to recover normal flight	Less than 720°, spontaneous recovery	Α	Less than 720°, spontaneous recovery	Α
10. Symmetric front collapse Approximately 30 % chord	С			
Entry	Rocking back less than 45°	Α	Rocking back less than 45°	Α
Recovery	Spontaneous in less than 3 s		Spontaneous in less than 3 s	,
Dive forward angle on exit Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	,
Cascade occurs	No	Α	No	
Folding lines used	Yes	С	Yes	
At least 50% chord Entry	Rocking back less than 45°	Α	Rocking back less than 45°	,
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Entering a turn of less than 90°	Α	Dive forward 0° to 30° / Keeping course	
Cascade occurs	No	Α	No	
Folding lines used	Yes	С	Yes	
Nith accelerator				
Entry	Rocking back less than 45°	Α	Rocking back less than 45°	
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	
Dive forward angle on exit / Change of course	Dive forward 30° to 60° / Keeping course	В	Dive forward 0° to 30° / Entering a turn of 90° to 180°	
Cascade occurs	No	Α	No	
Folding lines used	Yes	С	Yes	
11. Exiting deep stall (parachutal stall)	A			
Deep stall achieved	Yes		No	
Recovery	Spontaneous in less than 3 s		Spontaneous in less than 3 s	
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	
Change of course	Changing course less than 45°	Α	Changing course less than 45°	
Cascade occurs	No	Α	No	
I2. High angle of attack recovery Recovery	C Spontaneous in less than 3 s	Α	Spontaneous in 3 s to 5 s	
Cascade occurs	No	Α	No	
13. Recovery from a developed full stall Dive forward angle on exit	C Dive forward 0° to 30°	Α	Dive forward 0° to 30°	
Collapse	No collapse	Α	No collapse	
Cascade occurs (other than collapses)	No	Α	No	

Rocking back	Greater than 45°	С	Greater than 45°	С
Line tension	Nost lines tight A		Most lines tight	Α
14. Asymmetric collapse	С			
Small asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	Less than 90° / Dive or roll angle 0° to 15°	Α
Re-inflation behaviour	Inflates in less than 3 s from start of pilot action		Spontaneous re-inflation	Α
Total change of course	Less than 360° A		Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes	С	Yes	С
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Inflates in less than 3 s from start of pilot action	С	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes	С	Yes	С
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	Less than 90° / Dive or roll angle 15° to 45°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°		Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Yes	С	Yes	С
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α

Folding lines used	Yes	С	Yes	С
15. Directional control with a maintained asymmetric collapse	A			
Able to keep course	Yes	Α	Yes	Α
180° turn away from the collapsed side possible in 10 s	Yes	Α	Yes	Α
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	Α	More than 50 % of the symmetric control travel	Α
16. Trim speed spin tendency	A			
Spin occurs	No	Α	No	Α
17. Low speed spin tendency Spin occurs	A No	Α	No	Α
18. Recovery from a developed spin	В			
Spin rotation angle after release	Stops spinning in 90° to 180°	В	Stops spinning in 90° to 180°	В
Cascade occurs	No	Α	No	Α
19. B-line stall	0			
Change of course before release	not available	0	not available	0
Behaviour before release	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit	not available	0	not available	0
Cascade occurs	not available	0	not available	0
20. Big ears	В			
Entry procedure	Dedicated controls	Α	Standard technique	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Spontaneous in less than 3 s	Α	Recovery through pilot action in less than a further 3 s	r B
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
21. Big ears in accelerated flight	В			
Entry procedure	Dedicated controls	Α	Standard technique	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Spontaneous in less than 3 s	Α	Recovery through pilot action in less than a further 3 s	r B
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	Α	Stable flight	Α
22. Alternative means of directional control	A			
180° turn achievable in 20 s	Yes	Α	Yes	Α
Stall or spin occurs	No	Α	No	Α
23. Any other flight procedure and/or configuration described in the user's manual	0			
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0