AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Compte 8 • CH-1844 Villeneuve • +41 (0)21 965 65 65

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Flight test report: EN 926-2:2013+A1:2021* and NfL 2-565-20

| | | | | . ` | | |
|--|---------------------------------------|-----------------------------|----------------|----------------------------|----------------------------------|---|
| Manufacturer Ozone Gliders LTD | | Certification number | | | | |
| Address | 16 Barnes Green | | Flight test | | 30.04.2024 | |
| | EH54 8PP Livingston United Kingdom | | | | | |
| Glider model | MagMax 3 38 | | Classification | | В | |
| Serial number | PRTAN-Y-50D-011 | | Representative | | Honorin | |
| Trimmer | Closed | | Place of test | | Villeneuve | |
| Folding lines used | no | | | | | |
| r olanig moo dood | | | | | | |
| Test pilot | | Alexandre Jofresa | | Claude Thurnheer | | |
| Harness | | Advance Thun AG Success 4 M | | Advance Thun AG Bi-pro 3 M | | |
| Harness to risers d | istance [cm] | 43 | | 42 | | |
| Distance between r | | 55 | | | 55 | |
| Length of rigid spre | | 0 | | | 31 | |
| Total weight in fligh | | | | | | |
| rotai weigint in nigi | it [kg] | 110 | | | 190 | |
| 1. Inflation/Take-off | | Α | | | _ | |
| Rising behaviour | | Smooth, easy and cor | istant rising | A | Smooth, easy and constant rising | A |
| Special take off technique required | | No | | A | No | A |
| 2. Landing | | Α | | | | |
| Special landing technique | required | No | | A | No | А |
| 3. Speed in straight fligh | nt | В | | | | |
| Trim speed more than 30 km/h | | Yes | | А | Yes | А |
| Speed range using the controls larger than 10 km/h | | Yes A | | Yes | A | |
| Minimum speed | | Less than 25 km/h | | A | 25 km/h to 30 km/h | в |
| 4. Control movement | | A | | | | |
| 4. Control movement | | | | | | |
| Max. weight in flight up to 80 kg Symmetric control pressure / travel | | not available | | 0 | not available | 0 |
| | | | | | | |
| Max. weight in flight 80 kg to 100 kg | | not available | | 0 | not available | 0 |
| Symmetric control pressure / travel | | The available | | 0 | | 0 |
| Max. weight in flight gre | ater than 100 kg | | | | | |
| Symmetric control pressure / travel | | Increasing / greater th | an 65 cm | A | Increasing / greater than 65 cm | A |
| 5. Pitch stability exiting | accelerated flight | 0 | | | | |
| Dive forward angle on exit | | not available | | 0 | not available | 0 |
| Collapse occurs | | not available | | 0 | not available | 0 |
| 6. Pitch stability operating controls during accelerated flight | | 0 | | | | |
| Collapse occurs | | not available 0 | | not available | 0 | |
| 7. Roll stability and damping | | Α | | | | |
| Oscillations | | Reducing | | A | Reducing | А |
| 8. Stability in gentle spirals | | A | | | | |
| Tendency to return to straight flight | | Spontaneous exit | | А | Spontaneous exit | А |
| | | | | | | |

*This standard is NOT covered by accreditation D-IS-19457-01

The validation of this test report is given by the signature of the test manager on inspection certificate 91.20 Rev 07 | 04.03.2022 // ISO | 91.22 // Page 1 of 5

| 9. Behaviour exiting a fully developed spiral dive | Α | | | |
|---|--|---|--|---|
| Initial response of glider (first 180°) | Immediate reduction of rate of turn | A | Immediate reduction of rate of turn | A |
| Tendency to return to straight flight | Spontaneous exit (g force decreasing, rate of turn decreasing) | A | Spontaneous exit (g force decreasing, rate of turn decreasing) | A |
| Turn angle to recover normal flight | Less than 720°, spontaneous recovery | A | Less than 720°, spontaneous recovery | A |
| 10. Symmetric front collapse Approximately 30 % chord | В | | | |
| Entry | Rocking back less than 45° | | Rocking back less than 45° | A |
| Recovery | Spontaneous in 3 s to 5 s | | Spontaneous in less than 3 s | A |
| Dive forward angle on exit Change of course | Dive forward 0° to 30° / Keeping course | | Dive forward 0° to 30° / Keeping course | A |
| Cascade occurs | No A | | No | А |
| Folding lines used | No | A | No | А |
| At least 50% chord Entry | Rocking back less than 45° | A | Rocking back less than 45° | A |
| Recovery | Spontaneous in 3 s to 5 s | В | Spontaneous in 3 s to 5 s | в |
| Dive forward angle on exit / Change of course | Dive forward 0° to 30° / Keeping course | A | Dive forward 0° to 30° / Keeping course | A |
| Cascade occurs | No | A | Νο | A |
| Folding lines used | No | A | Νο | A |
| With accelerator | | | | |
| Entry | not available | 0 | not available | 0 |
| Recovery | not available | 0 | not available | 0 |
| Dive forward angle on exit / Change of course | not available | 0 | not available | 0 |
| Cascade occurs | not available | 0 | not available | 0 |
| Folding lines used | Not available | 0 | Not available | 0 |
| 11. Exiting deep stall (parachutal stall) | A | | Y., | |
| Deep stall achieved | Yes | | Yes | A |
| Recovery | Spontaneous in less than 3 s | A | Spontaneous in less than 3 s | A |
| Dive forward angle on exit | Dive forward 0° to 30° | A | Dive forward 0° to 30° | A |
| Change of course | Changing course less than 45° | A | Changing course less than 45° | A |
| Cascade occurs | No | A | No | A |
| 12. High angle of attack recovery Recovery | A Spontaneous in less than 3 s | A | Spontaneous in less than 3 s | A |
| Cascade occurs | No | A | No | A |
| 13. Recovery from a developed full stall Dive forward angle on exit | A Dive forward 0° to 30° | A | Dive forward 0° to 30° | A |
| Collapse | No collapse | A | No collapse | A |
| Cascade occurs (other than collapses) | No | A | No | A |

| Rocking back | Less than 45° | A | Less than 45° | А |
|---|---|--------|---|---|
| Line tension | Most lines tight | | Most lines tight | A |
| 14. Asymmetric collapse Small asymmetric collapse | В | | | |
| Sman asymmetric compse | | | | |
| Change of course until re-inflation / Maximum dive forward or roll angle | Less than 90° / Dive or roll angle 15° to 45° | A A | Less than 90° / Dive or roll angle 15° to 45° | A |
| Re-inflation behaviour | Spontaneous re-inflation | | • | A |
| Total change of course | Less than 360° | | Less than 360° | A |
| Collapse on the opposite side occurs | No (or only a small number of collapsed cells with a spontaneous reinflation) | A | No (or only a small number of collapsed cells with a spontaneous reinflation) | A |
| Twist occurs | No | | No | А |
| Cascade occurs | No | A | No | A |
| Folding lines used | No | | No | А |
| Large asymmetric collapse | | | | |
| Change of course until re-inflation / Maximum dive forward or roll angle | 90° to 180° / Dive or roll angle 15° to 45° | В | 90° to 180° / Dive or roll angle 15° to 45° | В |
| Re-inflation behaviour | Spontaneous re-inflation | A | Spontaneous re-inflation | А |
| Total change of course | Less than 360° | A | Less than 360° | A |
| Collapse on the opposite side occurs | No (or only a small number of collapsed cells with a spontaneous reinflation) | A | No (or only a small number of collapsed cells with a spontaneous reinflation) | A |
| Twist occurs | No | A | No | A |
| Cascade occurs | No | A | No | A |
| Folding lines used | No | A | No | A |
| Small asymmetric collapse with fully activated accelerator | | | | |
| Change of course until re-inflation / Maximum dive forward or roll angle | not available | 0 | not available | 0 |
| Re-inflation behaviour | not available | 0 | not available | 0 |
| Total change of course | not available | 0 | not available | 0 |
| Collapse on the opposite side occurs | not available | 0 | not available | 0 |
| Twist occurs | not available | 0 | not available | 0 |
| Cascade occurs | not available | 0 | not available | 0 |
| Folding lines used | Not available | 0 | Not available | 0 |
| Large asymmetric collapse with fully activated accelerator | | | | |
| Change of course until re-inflation / Maximum dive forward or roll angle | not available | 0 | not available | 0 |
| Re-inflation behaviour | not available | 0 | not available | 0 |
| Total change of course | not available | 0 | not available | 0 |
| Collapse on the opposite side occurs | not available | 0 | not available | 0 |
| Twist occurs | not available | 0 | not available | 0 |
| Cascade occurs | not available | 0 | not available | 0 |

| Folding lines used | Not available | 0 | Not available | 0 |
|---|--|---|--|---|
| 15. Directional control with a maintained asymmetric collapse | A | | | |
| Able to keep course | Yes | A | Yes | А |
| 180° turn away from the collapsed side possible in 10 s | Yes | A | Yes | A |
| Amount of control range between turn and stall or spin | More than 50 % of the symmetric control travel | A | More than 50 % of the symmetric control travel | А |
| 16. Trim speed spin tendency | A | | | |
| Spin occurs | No | A | No | A |
| 17. Low speed spin tendency | Α | | | |
| Spin occurs | No | A | No | A |
| 18. Recovery from a developed spin | Α | | | |
| Spin rotation angle after release | Stops spinning in less than 90° | A | Stops spinning in less than 90° | A |
| Cascade occurs | No | A | No | A |
| 19. B-line stall | A | | | |
| Change of course before release | Changing course less than 45° | A | not available | 0 |
| Behaviour before release | Remains stable with straight span | A | not available | 0 |
| Recovery | Spontaneous in less than 3 s | А | not available | 0 |
| Dive forward angle on exit | Dive forward 0° to 30° | A | not available | 0 |
| Cascade occurs | No | A | not available | 0 |
| 20. Big ears | В | | | |
| Entry procedure | Dedicated controls | A | Dedicated controls | А |
| Behaviour during big ears | Stable flight | A | Stable flight | A |
| Recovery | Spontaneous in 3 s to 5 s | В | Spontaneous in less than 3 s | А |
| Dive forward angle on exit | Dive forward 0° to 30° | A | Dive forward 0° to 30° | A |
| 21. Big ears in accelerated flight | 0 | | | |
| Entry procedure | not available | 0 | not available | 0 |
| Behaviour during big ears | not available | 0 | not available | 0 |
| Recovery | not available | 0 | not available | 0 |
| Dive forward angle on exit | not available | 0 | not available | 0 |
| Behaviour immediately after releasing the accelerator while maintaining big ears | not available | 0 | not available | 0 |
| 22. Alternative means of directional control | Α | | | |
| 180° turn achievable in 20 s | Yes | A | Yes | Α |
| Stall or spin occurs | No | A | No | A |
| 23. Any other flight procedure and/or configuration described in the user's manual | A | | | |
| Procedure works as described | Yes | A | Yes | А |
| Procedure suitable for novice pilots | Yes | A | Yes | А |
| Cascade occurs | No | A | No | A |
| | | | | |

24. Comments of test pilot

23 : tips stearing

The validation of this test report is given by the signature of the test manager on inspection certificate 91.20 Rev 07 | 04.03.2022 // ISO | 91.22 // Page 5 of 5