AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Compte 8 • CH-1844 Villeneuve • +41 (0)21 965 65 65

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Flight test report: EN 926-2:2013+A1:2021* and NfL 2-565-20

ManufacturerOzone Gliders LTDAddress16 Barnes Green		Certification number Flight test		PG_2418.2024 21.02.2024		
/10000	EH54 8PP Livingston United Kingdom		i light tost		21.02.2024	
Glider model	MagMax 3 41		Classification		В	
Serial number	PRTAN-Y-38D-076		Representative		Russel Ogden	
Trimmer	Closed		Place of test		Villeneuve	
Folding lines used	no					
Test pilot		Anselm Rauh			Alexandre Jofresa	
Harness		Niviuk Makan L		Advance Thun AG Bi-pro 3 M		
Harness to risers di	istance [cm]	41			42	
Distance between r		55			55	
Length of rigid spre		0		15		
Total weight in fligh	it [kg]	130			220	
1. Inflation/Take-off		В				
Rising behaviour		Smooth, easy and constant rising A		A	Easy rising, some pilot correction is required	В
Special take off technique required		No A		No	A	
2. Landing		Α				
Special landing technique	required	No		А	No	А
3. Speed in straight fligh	nt	В				
Trim speed more than 30		Yes		А	Yes	А
Speed range using the controls larger than 10 km/h		Yes A		Yes	А	
		Less than 25 km/h		A	25 km/h to 30 km/h	В
Minimum speed				A	23 KH/H 10 30 KH/H	Б
4. Control movement		Α				
Max. weight in flight up to 80 kg						
Symmetric control pressure / travel		not available		0	not available	0
Max. weight in flight 80 kg to 100 kg						
Symmetric control pressure / travel		not available		0	not available	0
Max. weight in flight gre	ater than 100 kg					
Symmetric control pressure / travel		Increasing / greater than 65 cm A		Increasing / greater than 65 cm	А	
5. Pitch stability exiting	accelerated flight	0				
Dive forward angle on exit		not available		0	not available	0
Collapse occurs		not available 0		not available	0	
6. Pitch stability operating controls during accelerated flight		0				
Collapse occurs		not available 0		not available	0	
7. Roll stability and damping		Α				
Oscillations		Reducing		A	Reducing	А
8. Stability in gentle spirals		Α				
Tendency to return to straight flight		Spontaneous exit		A	Spontaneous exit	А

*This standard is NOT covered by accreditation D-IS-19457-01

The validation of this test report is given by the signature of the test manager on inspection certificate 91.20 Rev 07 | 04.03.2022 // ISO | 91.22 // Page 1 of 5

9. Behaviour exiting a fully developed spiral dive	Α			
Initial response of glider (first 180°)	Immediate reduction of rate of turn	A	Immediate reduction of rate of turn	A
Tendency to return to straight flight	Spontaneous exit (g force decreasing, rate of turn decreasing)	A	Spontaneous exit (g force decreasing, rate of turn decreasing)	A
Turn angle to recover normal flight	Less than 720°, spontaneous recovery	A	Less than 720°, spontaneous recovery	A
10. Symmetric front collapse Approximately 30 % chord	В			
Entry	Rocking back less than 45°		Rocking back less than 45°	A
Recovery	Spontaneous in less than 3 s		Spontaneous in less than 3 s	A
Dive forward angle on exit Change of course	Dive forward 0° to 30° / Keeping course		Dive forward 0° to 30° / Keeping course	A
Cascade occurs	No	A	No	A
Folding lines used	No	A	No	A
At least 50% chord Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Spontaneous in 3 s to 5 s	В	Spontaneous in less than 3 s	A
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	A	Dive forward 0° to 30° / Keeping course	A
Cascade occurs	No	A	Νο	A
Folding lines used	No	A	Νο	A
With accelerator				
Entry	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit / Change of course	not available	0	not available	0
Cascade occurs	not available	0	not available	0
Folding lines used	Not available	0	Not available	0
11. Exiting deep stall (parachutal stall)	A	•	Ver	•
Deep stall achieved	Yes		Yes	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Change of course	Changing course less than 45°	A	Changing course less than 45°	A
Cascade occurs	No	A	No	A
12. High angle of attack recovery Recovery	A Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Cascade occurs	No	A	No	A
13. Recovery from a developed full stall Dive forward angle on exit	A Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Collapse	No collapse	A	No collapse	A
Cascade occurs (other than collapses)	No	А	No	A

Rocking back	Less than 45°	A	Less than 45°	А
Line tension	Most lines tight		Most lines tight	A
14. Asymmetric collapse Small asymmetric collapse	В			
Sman asymmetric compse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	A A	Less than 90° / Dive or roll angle 15° to 45°	A
Re-inflation behaviour	Spontaneous re-inflation		•	A
Total change of course	Less than 360°		Less than 360°	A
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No		No	А
Cascade occurs	No	A	No	A
Folding lines used	No	A	No	А
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	в	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	А
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	A	No	A
Cascade occurs	No	A	No	A
Folding lines used	No	A	No	A
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	not available	0	not available	0
Re-inflation behaviour	not available	0	not available	0
Total change of course	not available	0	not available	0
Collapse on the opposite side occurs	not available	0	not available	0
Twist occurs	not available	0	not available	0
Cascade occurs	not available	0	not available	0
Folding lines used	Not available	0	Not available	0
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	not available	0	not available	0
Re-inflation behaviour	not available	0	not available	0
Total change of course	not available	0	not available	0
Collapse on the opposite side occurs	not available	0	not available	0
Twist occurs	not available	0	not available	0
Cascade occurs	not available	0	not available	0

Folding lines used	Not available	0	Not available	0
15. Directional control with a maintained asymmetric collapse	A			
Able to keep course	Yes	A	Yes	А
180° turn away from the collapsed side possible in 10 s	Yes	A	Yes	A
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	A	More than 50 % of the symmetric control travel	A
16. Trim speed spin tendency	A			
Spin occurs	No	A	No	A
17. Low speed spin tendency	Α			
Spin occurs	No	A	No	A
18. Recovery from a developed spin	В			
Spin rotation angle after release	Stops spinning in 90° to 180°		Stops spinning in less than 90°	A
Cascade occurs	No	A	No	A
19. B-line stall	Α			
Change of course before release	Changing course less than 45°	A	Changing course less than 45°	A
Behaviour before release	Remains stable with straight span	A	Remains stable with straight span	А
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	А
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Cascade occurs	No	A	No	A
20. Big ears	A			
Entry procedure	Dedicated controls	A	Dedicated controls	A
Behaviour during big ears	Stable flight	A	Stable flight	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	А
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
21. Big ears in accelerated flight	0			
Entry procedure	not available	0	not available	0
Behaviour during big ears	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit	not available	0	not available	0
Behaviour immediately after releasing the accelerator while maintaining big ears	not available	0	not available	0
22. Alternative means of directional control	A			
180° turn achievable in 20 s	Yes	A	Yes	Α
Stall or spin occurs	No	A	No	А
23. Any other flight procedure and/or configuration described in the user's manual	A			
Procedure works as described	Yes	A	Yes	А
Procedure suitable for novice pilots	Yes	A	Yes	А
Cascade occurs	No	A	No	А

24. Comments of test pilot

23 : tips stearing

The validation of this test report is given by the signature of the test manager on inspection certificate 91.20 Rev 07 | 04.03.2022 // ISO | 91.22 // Page 5 of 5