

Flight test report

Manufacturer Ozone Gliders
Address 2, Queens Drive
 LA46LN
 UK
Representative Russell Ogden
Type of glider Mojo 2 M
Trimmer not available

Certification number PG 067.2007
Date of flight test 26/04/2007
Place of test Villeneuve



Classification A

Test Pilot	Claude Thurnheer	Chris Geist
Harness	Sky Axel II	SOL Slider
Total weight in flight	80 kg	100 kg

	Min weight		Max weight	
1. Inflation/Take-off				
Rising behaviour	Smooth, easy and constant rising	A	Smooth, easy and constant rising	A
Special take off technique required	No	A	No	A
2. Landing				
Special landing technique required	No	A	No	A
3. Speed in straight flight				
Trim speed more than 30 km/h	Yes	A	Yes	A
Speed range using the controls larger than 10 km/h	Yes	A	Yes	A
Minimum speed	Less than 25 km/h	A	Less than 25 km/h	A
4. Control movement				
<i>Max. weight in flight up to 80 kg</i> Symmetric control pressure/travel	not available	0	not available	0
<i>Max. weight in flight 80 kg to 100 kg</i> Symmetric control pressure/travel	Increasing, Greater than 60 cm	A	Increasing, Greater than 60 cm	A
<i>Max. weight in flight greater than 100 kg</i> Symmetric control pressure/travel	not available	0	not available	0
5. Pitch stability exiting accelerated flight				
Dive forward angle on exit	Dive forward less than 30°	A	Dive forward less than 30°	A
Collapse occurs	No	A	No	A
6. Pitch stability operating controls during accelerated flight				
Collapse occurs	No	A	No	A
7. Roll stability and damping				
Oscillations	Reducing	A	Reducing	A
8. Stability in gentle spirals				
Tendency to return to straight flight	Spontaneous exit	A	Spontaneous exit	A
9. Behaviour in a steeply banked turn				
Sink rate after two turns	12 m/s to 14 m/s	A	Up to 12m/s	A
10. Symmetric front collapse				
Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°, Keeping course	A	Dive forward 0° to 30°, Keeping course	A
Cascade occurs	No	A	No	A
<i>With accelerator</i>				
Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°, Keeping course	A	Dive forward 0° to 30°, Keeping course	A
Cascade occurs	No	A	No	A
11. Exiting deep stall (parachutal stall)				
Deep stall achieved	Yes	A	Yes	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Change of course	Changing course less than 45°	A	Changing course less than 45°	A
Cascade occurs	No	A	No	A
12. High angle of attack recovery				
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Cascade occurs	No	A	No	A
13. Recovery from a developed full stall				
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Collapse	No collapse	A	No collapse	A
Cascade occurs (other than collapse)	No	A	No	A
Rocking back	Less than 45°	A	Less than 45°	A
Line tension	Most line tight	A	Most line tight	A
14. Asymmetric collapse				
<i>With 50% collapse-Maximum dive forward or roll angle</i>				
Change of course until re-inflation	Less than 90°, Dive or roll angle 0° to 15°	A	Less than 90°, Dive or roll angle 0° to 15°	A
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	A
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No	A	No	A
Twist occurs	No	A	No	A
Cascade occurs	No	A	No	A
<i>With 75% collapse-Maximum dive forward or roll angle</i>				
Change of course until re-inflation	Less than 90°, Dive or roll angle 15° to 45°	A	Less than 90°, Dive or roll angle 0° to 15°	A
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	A
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No	A	No	A
Twist occurs	No	A	No	A
Cascade occurs	No	A	No	A
<i>With 50% collapse and accelerator-Maximum dive forward or roll angle</i>				
Change of course until re-inflation	Less than 90°, Dive or roll angle 0° to 15°	A	90° to 180°, Dive or roll angle 0° to 15°	A
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	A
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No	A	No	A

Twist occurs	No	A	No	A
Cascade occurs	No	A	No	A
<i>With 75% collapse and accelerator-Maximum dive forward or roll angle</i>				
Change of course until re-inflation	Less than 90°, Dive or roll angle 15° to 45°	A	90° to 180°, Dive or roll angle 0° to 15°	A
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	A
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No	A	No	A
Twist occurs	No	A	No	A
Cascade occurs	No	A	No	A
15. Directional control with a maintained asymmetric collapse				
Able to keep course	Yes	A	Yes	A
180° turn away from the collapsed side possible in 10 s	Yes	A	Yes	A
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	A	More than 50 % of the symmetric control travel	A
16. Trim speed spin tendency				
Spin occurs	No	A	No	A
17. Low speed spin tendency				
Spin occurs	No	A	No	A
18. Recovery from a developed spin				
Spin rotation angle after release	Stops spinning in less than 90°	A	Stops spinning in less than 90°	A
Cascade occurs	No	A	No	A
19. B-line stall				
Change of course before release	Change of course less than 45°	A	Change of course less than 45°	A
Behaviour before release	Remains stable with straight span	A	Remains stable with straight span	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Cascade occurs	No	A	No	A
20. Big ears				
Entry procedure	Dedicated controls	A	Dedicated controls	A
Behaviour during big ears	Stable flight	A	Stable flight	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
21. Big ears in accelerated flight				
Entry procedure	Dedicated controls	A	Dedicated controls	A
Behaviour during big ears	Stable flight	A	Stable flight	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Behaviour immediately after releasing the accelerator while	Stable flight	A	Stable flight	A
22. Behaviour exiting a steep spiral				
Tendency to return to straight flight	Spontaneous exit	A	Spontaneous exit	A
Turn angle to recover normal flight	Less than 720°,spontaneous recovery	A	Less than 720°,spontaneous recovery	A
Sink rate when evaluating spiral stability [m/s]	16 m/s		16 m/s	
23. Alternative means of directional control				
180° turn achievable in 20 s	Yes	A	Yes	A
Stall or spin occurs	No	A	No	A
24. Any other flight procedure and/or configuration described in the user's manual				
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0
Comments of test pilot				
Comments	Ok in spiral after modification		no	



Air Turquoise

Rue de la Poterlaz 6
Case postale 10
CH- 1844 Villeneuve
Switzerland
mobile: +41 79 202 52 30
Tel. no : +41 21 965 65 65
fax : +41 219 65 65 66
email: info@airturquoise.ch
homepage: www.cen.li