AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Compte 8 • CH-1844 Villeneuve • +41 (0)21 965 65 65

Ozone Gliders LTD

16 Barnes Green

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes

Manufacturer

Address



Certification number PG_2473.2024

01.11.2024

Flight test

Flight test report: EN 926-2:2013+A1:2021* and NfL 2-565-20

		EH54 8PP Livingston United Kingdom		riigiit test		01.11.2024	
	Glider model Serial number Trimmer Folding lines used	Swiftmax 2 41 PRTAN-Z-29C-012 Opened no		Classification Representative Place of test		B Honorin Villeneuve	
Test pilot		Anselm Rauh			Claude Thurnheer		
	Harness Harness to risers distance [cm] Distance between risers [cm] Length of rigid spreaders [cm] Total weight in flight [kg]		Niviuk Makan I 41 55 none 120	L		Advance Thun AG Bi-pro 2 44 55 15 230	
Inflation/Take-off Rising behaviour		B Easy rising, some pilot	correction is required	В	Easy rising, some pilot correction is required	В	
Special take off technique required		No		А	No	Α	
2. Landing Special landing technique required		A No		Α	No	Α	
3. Speed in straight flight Trim speed more than 30 km/h		B Yes		Α	Yes	Α	
Speed range using the controls larger than 10 km/h		ntrols larger than 10 km/h	Yes		Α	Yes	Α
Minimum speed			Less than 25 km/h		Α	25 km/h to 30 km/h	В
	4. Control movement Max. weight in flight up to 80 kg Symmetric control pressure / travel		A not available				
	Max. weight in flight up t		not available		0	not available	0
	Max. weight in flight up t	e / travel g to 100 kg	not available		0	not available	0
	Max. weight in flight up t Symmetric control pressure Max. weight in flight 80 k	e / travel g to 100 kg e / travel ater than 100 kg		an 65 cm			
	Max. weight in flight up to Symmetric control pressure. Max. weight in flight 80 k Symmetric control pressure. Max. weight in flight great Symmetric control pressure. 5. Pitch stability exiting a	e / travel ig to 100 kg e / travel ater than 100 kg e / travel accelerated flight	not available	an 65 cm	0	not available	0
	Max. weight in flight up to Symmetric control pressure. Max. weight in flight 80 kt Symmetric control pressure. Max. weight in flight great Symmetric control pressure.	e / travel ig to 100 kg e / travel ater than 100 kg e / travel accelerated flight	not available Increasing / greater that	an 65 cm	0 A	not available Increasing / greater than 65 cm	0 A
	Max. weight in flight up to Symmetric control pressure. Max. weight in flight 80 k Symmetric control pressure. Max. weight in flight great Symmetric control pressure. 5. Pitch stability exiting a Dive forward angle on exit. Collapse occurs. 6. Pitch stability operation.	e / travel g to 100 kg e / travel ater than 100 kg e / travel accelerated flight	not available Increasing / greater that O not available	an 65 cm	0 A	not available Increasing / greater than 65 cm not available	0 A
	Max. weight in flight up to Symmetric control pressure. Max. weight in flight 80 k Symmetric control pressure. Max. weight in flight great Symmetric control pressure. 5. Pitch stability exiting a Dive forward angle on exit. Collapse occurs	e / travel g to 100 kg e / travel ater than 100 kg e / travel accelerated flight	not available Increasing / greater that O not available not available	an 65 cm	0 A	not available Increasing / greater than 65 cm not available	0 A
	Max. weight in flight up to Symmetric control pressure. Max. weight in flight 80 ks Symmetric control pressure. Max. weight in flight great Symmetric control pressure. 5. Pitch stability exiting a Dive forward angle on exit. Collapse occurs. 6. Pitch stability operating accelerated flight.	e / travel g to 100 kg e / travel ater than 100 kg e / travel accelerated flight	not available Increasing / greater that Onot available not available O	an 65 cm	0 A 0 0	not available Increasing / greater than 65 cm not available not available	0 A 0 0
	Max. weight in flight up to Symmetric control pressure. Max. weight in flight 80 ks. Symmetric control pressure. Max. weight in flight great symmetric control pressure. 5. Pitch stability exiting a Dive forward angle on exit. Collapse occurs. 6. Pitch stability operating accelerated flight. Collapse occurs. 7. Roll stability and damper.	e / travel g to 100 kg e / travel ater than 100 kg e / travel accelerated flight ag controls during ping	not available Increasing / greater that Onot available not available Onot available A	an 65 cm	0 A O O	not available Increasing / greater than 65 cm not available not available not available	0 A O O

B. Behaviour exiting a fully developed spiral dive	В			
nitial response of glider (first 180°)	Immediate reduction of rate of turn	Α	No immediate reaction	E
Fendency to return to straight flight	Spontaneous exit (g force decreasing, rate of turn decreasing)	Α	Spontaneous exit (g force decreasing, rate of turn decreasing)	,
Furn angle to recover normal flight	Less than 720°, spontaneous recovery		Less than 720°, spontaneous recovery	A
0. Symmetric front collapse Approximately 30 % chord	В			
Entry	Rocking back less than 45°	Α	Rocking back less than 45°	
Recovery	Spontaneous in 3 s to 5 s	В	Spontaneous in 3 s to 5 s	
Dive forward angle on exit Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	
Cascade occurs	No	Α	No	
Folding lines used	No	Α	No	
At least 50% chord Entry	Rocking back less than 45°	Α	Rocking back less than 45°	
Recovery	Spontaneous in 3 s to 5 s	В	Spontaneous in 3 s to 5 s	
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	
Cascade occurs	No	Α	No	
Folding lines used	No	Α	No	
Vith accelerator				
Entry	not available	0	not available	
Recovery	not available	0	not available	
Dive forward angle on exit / Change of course	not available	0	not available	
Cascade occurs	not available	0	not available	
Folding lines used	Not available	0	Not available	
1. Exiting deep stall (parachutal stall)	A Yes	٨	Yes	
Deep stall achieved	Spontaneous in less than 3 s		Spontaneous in less than 3 s	
Recovery	Dive forward 0° to 30°		Dive forward 0° to 30°	
Dive forward angle on exit	Changing course less than 45°		Changing course less than 45°	
Change of course	No		No	
Cascade occurs		А	No	
I2. High angle of attack recovery Recovery	A Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	
Cascade occurs	No	Α	No	
3. Recovery from a developed full stall Dive forward angle on exit	B Dive forward 0° to 30°	Α	Dive forward 30° to 60°	
Collapse	No collapse	Α	No collapse	
Cascade occurs (other than collapses)	No	Α	No	

Rocking back	Less than 45°	Α	Less than 45°	Α
Line tension	Most lines tight	Α	Most lines tight	Α
14. Asymmetric collapse Small asymmetric collapse	В			
Small asymmetric conapse				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	Less than 90° / Dive or roll angle 15° to 45°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	Α	No	Α
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	Α	No	Α
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	not available	0	not available	0
Re-inflation behaviour	not available	0	not available	0
Total change of course	not available	0	not available	0
Collapse on the opposite side occurs	not available	0	not available	0
Twist occurs	not available	0	not available	0
Cascade occurs	not available	0	not available	0
Folding lines used	Not available	0	Not available	0
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	not available	0	not available	0
Re-inflation behaviour	not available	0	not available	0
Total change of course	not available	0	not available	0
Collapse on the opposite side occurs	not available	0	not available	0
Twist occurs	not available	0	not available	0
Cascade occurs	not available	0	not available	0

Folding lines used	Not available	0	Not available	0
15. Directional control with a maintained asymmetric collapse	A			
Able to keep course	Yes	Α	Yes	Α
180° turn away from the collapsed side possible in 10 s	Yes	Α	Yes	Α
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	Α	More than 50 % of the symmetric control travel	Α
16. Trim speed spin tendency	Α			
Spin occurs	No	Α	No	Α
17. Low speed spin tendency Spin occurs	A No	Α	No	Α
	В			
18. Recovery from a developed spin Spin rotation angle after release	Stops spinning in less than 90°	Α	Stops spinning in 90° to 180°	В
Cpm retation angle alter release				
Cascade occurs	No	Α	No	Α
19. B-line stall	Α			
Change of course before release	Changing course less than 45°	Α	not available	0
Behaviour before release	Remains stable with straight span	Α	not available	0
Recovery	Spontaneous in less than 3 s	Α	not available	0
Dive forward angle on exit	Dive forward 0° to 30°	Α	not available	0
Cascade occurs	No	Α	not available	0
20. Big ears	В			
Entry procedure	Dedicated controls	Α	Dedicated controls	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Recovery through pilot action in less than a further 3 s	В	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
21. Big ears in accelerated flight	0			
Entry procedure	not available	0	not available	0
Behaviour during big ears	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit	not available	0	not available	0
Behaviour immediately after releasing the accelerator while maintaining big ears	not available	0	not available	0
22. Alternative means of directional control	Α			
180° turn achievable in 20 s	Yes	Α	Yes	Α
Stall or spin occurs	No	Α	No	Α
23. Any other flight procedure and/or configuration described in the user's manual	0			
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0