AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Comte 8 A CH-1844 Villeneuve A +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Harness inspection certificate - EN

Inspection certificate number:

PH 295.2020

Impact pad number:

Name Impact pad: (1)

Impact pad type:

Serial number: (1)

Date of reception:

Impact pad integrated: (1)

MISC_152.2020

Manufacturer data

Manufacturer name:

Representative:

OZONE Gliders Russell Ogden 2, Queens Drive

Post code / place:

LA46LN

Country:

Street:

UK

-								
0	-	~	m١	0	ᆈ	-4	-	
	71		C 31	-		71		Е.

Serial number:

Clip-in weight [kg]:

Harness

Impact pad

Name: Type:

Size:

F*Race ABS M

1.547 001 100

Integrated container for rescue system:

Volume container [cm³]:

Weight of Sample [kg]:

Date of reception:

Yes

6000 max

3000 min

F*Race inflated protector

Inflatable Weight of Sample [kg]: (1) 0.124 protector01

23.01.2020

Test report summary

Structual test

Impact pad test

Result Place Date

POSITIVE Villeneuve 23.01.2020

23.01.2020

POSITIVE Villeneuve 23.01.2020

Issue data

Place of declaration: Date of issue:

Managing Director: Signature:

Villeneuve 06.08.2020 Alain Zoller

This signature approve the validity of the test reports if available; no. 94.21b (test id 01,03,05,06,08,09,10,11,12,14,RRDT,RRST) and no. 94.22 (test id: P,PR) Air Turquoise SA, having thoroughly assessed the sample mentioned above, declare it was found conform with all requirements defined by the following norms:

European Standard EN1651:2018, and EN12491:2015

Present declaration's scope only extends to the conformity of a given sample, on a given date and in a given place – as mentioned here above. This inspection certificate contain the following test and is complet with the test, if available, report: 94.21 and 94.22

⁽¹⁾ If Impact pad is NOT integrated in the harness, it will have independently Inspection number, and serial number. Definition of integrated impact pad is impact pad which can not be dismounted from the harness, e.g. airbag.