

Miscellaneous Impact Pad Report

Inspection certificate number: **MISC_309.2025**

Manufacturer data:

Manufacturer name: **Ozone Gliders LTD**
 Representative: **Russell Ogden**
 Street: **16 Barnes Green**
 Post code place: **EH54 8PP Livingston**
 Country: **Scotland UK**

Harness model: **Atak2 S/M**

Sample data:

Name impact pad: **Ozair**
 Emergency parachute integrated: **No**
 Impact pad type: **Inflatable**
 Weight of sample [kg]: **0.44**
 Serial number: **PRT-OZ-001-V10**
 Date of test: **17.01.2025**


Atmosphere AGL:

Temp. [C°]	20
R.H. [%]	40
Press. [hPa]	998

Summary of Impact pad test ⁽¹⁾

Test id	–	Test configuration ⁽²⁾	Max Peak of Impact [g] ⁽³⁾	Duration at 38 [g] in [ms] ⁽⁴⁾	Duration at 20 [g] in [ms] ⁽⁵⁾	Result
P	✓	Test sample attached to dummy in flying position, without emergency parachute	31.72	0.00	25.00	POSITIVE
PR		Test sample attached to dummy in flying position, including emergency parachute	0.00	0.00	0.00	n/a

Issue data

Place of declaration: **Villeneuve**
 Date of issue: **02.04.2025**
 Managing director: **Andrea Wigger**
 Signature: 

Manufacturer	Instrument	Type no	S/N	Validity Calibration
Burster/MTS	Accelerometer 100 g	89010-100	1263567	23.08.2028
JDC elec	Geos n°11 Skywatch	Geos n°11	Unit11	18.06.2025

This signature approves the validity of the test report

Air Turquoise SA has thoroughly tested the sample of emergency parachute container mentioned above and certifies its conformity with the following standards:
EN 1651:2018+A1:2020, NFL 2024-2-785

⁽¹⁾ Calculated value in tests reports include the value minus the uncertainty (on safe side) / The uncertainty stated is the expanded uncertainty obtained by multiplying the standard uncertainty by the coverage factor k = 2. The value of the measurand lies within the assigned range of values with a probability of 95%.

⁽²⁾ The dummy is lifted minimum up to 1.65 m, and impact pad is mounted on. Where the impact occurs, measure distance from bottom of impact pad to ground.

⁽³⁾ Maximum peak of impact should be less or equal to 50 [g], ⁽⁴⁾ If any, the maximum duration in at 38 [g] should be less or equal to 7 [ms],

⁽⁵⁾ If any, the maximum duration in at 20 [g] should be less or equal to 25 [ms].

The declaration must not be reproduced in part without the written permission of Air Turquoise SA





Inspection certificate number: **MISC_309.2025**

Name impact pad: **Ozair**

Test results of Impact pad test

	without emergency parachute	including emergency parachute
	P1	PR1
Maximum Peak of impact [g]	31.72	0.00
Impact duration at +38 [g] in [ms]	0.00	0.00
Impact duration at +20 [g] in [ms]	25.00	0.00
Uncertainty k=2[g]	1.33	0.00



⁽³⁾ Maximum peak of impact should be less or equal to 50 [g]. ⁽⁴⁾ If any, the maximum duration in at 38 [g] should be less or equal to 7 [ms]. ⁽⁵⁾ If any, the maximum duration in at 20 [g] should be less or equal to 25 [ms].