AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Compte 8 • CH-1844 Villeneuve • +41 (0)21 965 65 65

Sky Country

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes

Manufacturer



Certification number PG_2538.2025

Flight test report: EN 926-2:2013+A1:2021 and NfL 2024-2-785

Address	Astronomicheskaya s 61085 Kharkov Ukraine	treet, 27,29	Flight test		17.03.2025	
Glider model	Discovery-6 S		Classification		В	
Serial number	1124-4009-004		Representative		None	
Trimmer	no		Place of test		Villeneuve	
	no		1 1400 01 1031		Villerieuve	
Folding lines used	110					
Test pilot		Victor Chinen	Cirilli		Claude Thurnheer	
Harness		Woody Valley srl Wani Light 2 M		Advance Thun AG Success 4 M	1	
Harness to risers d		43		43		
Distance between r	risers [cm]	40			44	
Total weight in fligh	nt [kg]	70			90	
1. Inflation/Take-off		В				
Rising behaviour		Easy rising, some pi	lot correction is required	В	Easy rising, some pilot correction is required	В
Special take off technique	e required	No		Α	No	Α
2. Landing		Α				
Special landing technique	e required	No		Α	No	Α
2 Chand in attraight fligh	~	A				
Speed in straight flightTrim speed more than 30		A Yes		Α	Yes	Α
Thin speed more than 50	KIII/II	100		,,	100	^`
Speed range using the co	ontrols larger than 10 km/h	Yes		Α	Yes	Α
Minimum speed		Less than 25 km/h		Α	Less than 25 km/h	Α
4. Control movement		Α				
Max. weight in flight up	to 80 kg					
Max. weight in flight up to 80 kg Symmetric control pressure / travel		Increasing / greater than 55 cm A		Α	not available	0
Max. weight in flight 80	ka to 100 ka					
Symmetric control pressu	-	not available		0	Increasing / greater than 60 cm	Α
Cymmound demain product	10 / 114701					
Max. weight in flight gre	eater than 100 kg					
Symmetric control pressu	re / travel	not available		0	not available	0
5. Pitch stability exiting	accelerated flight	Α				
Dive forward angle on exi		Dive forward less that	an 30°	Α	Dive forward less than 30°	Α
Collapse occurs		No		Α	No	Α
6. Pitch stability operati	ng controls during	Α				
Collapse occurs		No		Α	No	Α
7. Roll stability and dam	npina	A				
Oscillations	-F9	Reducing		Α	Reducing	Α
8. Stability in gentle spi		A				
Tendency to return to stra	aight flight	Spontaneous exit		Α	Spontaneous exit	Α

). Behaviour exiting a fully developed spiral dive	A	٨	Immediate reduction of rate of turn	
nitial response of glider (first 180°)	Immediate reduction of rate of turn	А	Immediate reduction of rate of turn	
Fendency to return to straight flight	Spontaneous exit (g force decreasing, rate of turn decreasing)	Α	Spontaneous exit (g force decreasing, rate of turn decreasing)	
Furn angle to recover normal flight	Less than 720°, spontaneous recovery	Α	Less than 720°, spontaneous recovery	
IO. Symmetric front collapse Approximately 30 % chord	В			
Entry	Rocking back less than 45°	Α	Rocking back less than 45°	
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	
Dive forward angle on exit Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	
Cascade occurs	No	Α	No	
Folding lines used	No	Α	No	
At least 50% chord Entry	Rocking back less than 45°	Α	Rocking back less than 45°	
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	
Dive forward angle on exit / Change of course	Dive forward 30° to 60° / Keeping course	В	Dive forward 0° to 30° / Keeping course	
Cascade occurs	No	Α	No	
Folding lines used	No	Α	No	
Vith accelerator				
Entry	Rocking back less than 45°	Α	Rocking back less than 45°	
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	
Cascade occurs	No	Α	No	
Folding lines used	No	Α	No	
1. Exiting deep stall (parachutal stall)	A			
Deep stall achieved	Yes		Yes	
Recovery	Spontaneous in less than 3 s		Spontaneous in less than 3 s	
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	
Change of course	Changing course less than 45°		Changing course less than 45°	
Cascade occurs	No	Α	No	
2. High angle of attack recovery Recovery	A Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	
Cascade occurs	No	Α	No	
3. Recovery from a developed full stall Dive forward angle on exit	A Dive forward 0° to 30°	Α	Dive forward 0° to 30°	
Collapse	No collapse	Α	No collapse	
Cascade occurs (other than collapses)	No	Α	No	

Rocking back	Less than 45°	Α	Less than 45°	Α
Line tension	Most lines tight	Α	Most lines tight	Α
14. Asymmetric collapse	В			
Small asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 0° to 15°	Α	Less than 90° / Dive or roll angle 15° to 45°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°		Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	Α	No	Α
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	Α	No	Α
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	Less than 90° / Dive or roll angle 0° to 15°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	Α	No	Α
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α

Folding lines used	No	Α	No	Α
15. Directional control with a maintained asymmetric collapse	Α			
Able to keep course	Yes	Α	Yes	Α
180° turn away from the collapsed side possible in 10 s	Yes	Α	Yes	Α
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	Α	More than 50 % of the symmetric control travel	Α
16. Trim speed spin tendency	A			
Spin occurs	No	Α	No	Α
17. Low speed spin tendency Spin occurs	A No	Α	No	Α
18. Recovery from a developed spin	В			
Spin rotation angle after release	Stops spinning in less than 90°	Α	Stops spinning in 90° to 180°	В
Cascade occurs	No	Α	No	Α
19. B-line stall	A			
Change of course before release	Changing course less than 45°	Α	Changing course less than 45°	Α
Behaviour before release	Remains stable with straight span	Α	Remains stable with straight span	Α
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Cascade occurs	No	Α	No	Α
20. Big ears	В			
Entry procedure	Dedicated controls	Α	Dedicated controls	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Spontaneous in less than 3 s	Α	Recovery through pilot action in less than a further 3 s	r B
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
21. Big ears in accelerated flight	В			
Entry procedure	Dedicated controls	Α	Dedicated controls	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Spontaneous in less than 3 s	Α	Recovery through pilot action in less than a further 3 s	r B
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	Α	Stable flight	Α
22. Alternative means of directional control	A			
180° turn achievable in 20 s	Yes	Α	Yes	Α
Stall or spin occurs	No	Α	No	Α
23. Any other flight procedure and/or configuration described in the user's manual	0			
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0