

## Flight and Load test report - EN 12491:2001

**Manufacturer** Sky Paragliders a.s.  
**Address** Okružní 39  
 73911 Frýdlant nad Ostravicí  
 Czech Republic

**Certification number:** EP 026.2010  
**Type/model:** Sky Spare Light XL  
**Total weight in flight:** 130 kg

Description of tests	place:	date:	result:
<b>1. Deployment system strength test</b> A load of 700 N between each components	Villeneuve	17/02/2009	OK
<b>2. Speed of opening test - ref. A (2 times)</b> Time from the instant of free drop until a load of 200 N is sustained Opening time Opening time	Villeneuve Villeneuve	01/04/2008 24/04/2008	< 5 seconds < 5 seconds
<b>3. Descent rate and stability test - ref. A and B (2 times)</b> The paraglider is released as the parachute begins to open, minimum 100 m descent. Stability 1 Sink rate 1 Stability 2 Sink rate 2	Villeneuve Villeneuve Villeneuve Villeneuve	01/04/2008 01/04/2008 24/04/2008 24/04/2008	Stable 5.47 m/s Stable 5.47 m/s
<b>4. Strength test 40 m/s opening shock (2 times)</b> The drop test device is accelerated to a straight line velocity of 40 m/s and the parachute deployment handle activated using a static line attached to a drogue chute. Speed of opening is less than 5 seconds Test 1 Test 2	France France	30/12/2006 30/12/2006	OK, done by Aerotests OK, done by Aerotests
<b>5. Interaction and stability test (piloted) - ref. C</b> a the emergency parachute is deployed from a paraglider in normal straight flight. b the pilot shall take no action while the behaviour of the parachute and paraglider are observed 200 metres. c the pilot take action while the behaviour of the parachute and paraglider are observed 200 metres.			not available  not available  not available

The model described is in conformity with the flight and load tests carried out by Air Turquoise SA.



For Air Turquoise SA

*Randi Eriksen*  
 Randi Eriksen

**Air Turquoise SA**  
 Route du Pré-au-Comte 8  
 Case postale 10  
 CH- 1844 Villeneuve  
 email: info@para-test.com



homepage: www.para-test.com

## Weather data, ref. 3 and B

Date / place	hPa	wind	temp	humidity
01/04/2008 Villeneuve	979	0	8.9	77.5%
	Corrected mass:	<b>128.32 kg</b>		
24/04/2008 Villeneuve	980	0	8.0°	82.2%
	Corrected mass:	<b>128.86 kg</b>		

## Reference

A. At horizontal airspeed 8 m/s and vertical speed 1.5 m/s

B. Formula to be used for correcting the test mass ofr differences from ICAO standard atmosphere

$$m_{\text{corr}} := m_{\text{dec}} \cdot \frac{p \cdot T_0}{p_0 \cdot T}$$

Ground level atmospheric pressure at the test location: (p)

ICAO standard atmospheric pressure at MSL: (p<sub>0</sub>)

Ground level temperature at the test location: (T)

ICAO standard temperature at MSL: (T<sub>0</sub>)

Total weight in flight: (m<sub>dec</sub>)

Corrected mass: (m<sub>corr</sub>)

C. Only parachute with controls for steering and landing flare



## Air Turquoise SA

Route du Pré-au-Comte 8  
 Case postale 10  
 CH - 1844 Villeneuve  
 Switzerland  
 mobile: +41 79 202 52 30  
 Tel. no : +41 21 965 65 65  
 fax : +41 219 65 65 68  
 email: info@para-test.com  
 homepage: www.para-test.com

For Air Turquoise SA

*Randi Eriksen*  
 Randi Eriksen

