## AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Comte 8 . CH-1844 Villeneuve . + +41 (0)2) 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



## Harness inspection certificate - NfL

Inspection certificate number:

PH\_365.2022

Impact pad number:

MISC 208.2022

Manufacturer data

Manufacturer name:

Skywalk GmbH & Co. KG

Representative:

Post code / place:

Mr. Arne Wehrlin

Street:

Windeckstrasse 4 83250 Marquarstein

Country:

Germany

Sample data:

Harness

Impact pad

Name:

**RANGE X-ALPS 3** 

Name Impact pad: (1)

Permair A2

Type:

ABS

Impact pad integrated: (1) Impact pad type:

Yes

Size

M 1.97

Weight of Sample [kg]: (1)

Inflatable 0.258

Weight of Sample [kg]: Serial number:

SHRXA3M00-13072022-02

Serial number: (1)

Date of reception:

SHRXA3MO-07042022 V2R5

Clip-in weight [kg]: Integrated container for 120 Yes

rescue system: (2) Volume container [cm3]:

5800 max

2500 min

Date of reception:

20.04.2022

20.04.2022

Test report summary

Structual test

Impact pad test

Result: Place: Date:

**POSITIVE** Villeneuve 05.03.2024 **POSITIVE** Villeneuve 25.04.2022

Issue data

Place of declaration:

Managing Director:

Date of issue:

Villeneuve 04.04.2023

Andrea Wigger

Signature:

Revision 01: 05.03.2024

This revision cancels and replaces the previous one.

This signature approve the validity of the test reports 94.21a and 94.22 (only if test reports are applicable) Air Turquoise SA, has thoroughly tested the sample mentioned above and certifies its conformity with the following standards:

NfL 2-565-20, EN12491:2015 and EN1651:1999

The certificate of inspection is completed with test reports, if available, number: 94.21a and 94.22 The declaration must not be reproduced in part without the written permission of AIR TURQUOISE SA

<sup>(1)</sup> If Impact pad is NOT integrated in the harness, it will have independently Inspection number, and serial number. Definition of integrated impact pad is impact pad which can not be dismounted from the harness, e.g. airbag. (2) If harness has an integrated inner container for emergency parachute, extra deployment tests are done.