## AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Comte 8 . CH-1844 Villeneuve . +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



## Harness inspection certificate - NfL

Inspection certificate number:

PH 433.2024

Impact pad number:

PH 433.2024

## Manufacturer data

Manufacturer name:

Sol Paragliders - SOL SPORTS Ind. e Com. Ltda

Representative:

**Ary Carols Pradi** 

Street:

Rua Walter Marguardt,1180

Post code / place:

Cep 89259-565 Jaraguá do Sul, SC

Country:

Brazil

Sample data:	Harness		Impact pad	
Name:	<b>CALLIPLOX REVERSE 2</b>	Name Impact pad: (1)	n/a	
Type:	ABS	Impact pad integrated: (1)	Yes	
Size:	L	Impact pad type:	Airbag	
Weight of Sample [kg]:	3.58	Weight of Sample [kg]: (1)	n/a	
Serial number:	29982	Serial number:(1)	29983	
Clip-in weight [kg]:	120			
Integrated container for rescue system:	Yes	Date of reception:	09.10.2023	
Volume container [cm <sup>3</sup> ]:	<b>6000</b> max			
	<b>2500</b> min			
Date of reception:	22.08.2023			

Test repo	ort summary S	Structual test	Impact pad test	51 -IB 1 II I 1 1000 -
Result	F	POSITIVE	POSITIVE	
Place	\	Villeneuve	Villeneuve	
Date	2	24.08.2023	09.10.2023	

## Issue data

Place of declaration: Date of issue:

Managing Director:

Signature:

Villeneuve 13.02.2024 Andrea Wigger

This signature approve the validity of the test reports 94.21a and 94.22 (only if test reports are applicable)

Air Turquoise SA, has thoroughly tested the sample mentioned above and certifies its conformity with the following standards:

NfL 2-565-20, EN12491:2015 and EN1651:1999

The certificate of inspection is completed with test reports, if available, number: 94.21a and 94.22.

The declaration must not be reproduced in part without the written permission of AIR TURQUOISE SA

<sup>(1)</sup> If Impact pad is NOT integrated in the harness, it will have independently Inspection number, and serial number. Definition of integrated impact pad is impact pad which can not be dismounted from the harness, e.g. airbag. (2) If harness has an integrated inner container for emergency parachute, extra deployment tests are done.