

## Harness Impact Pad Report

Inspection certificate number: **PH\_412.2023**

### Manufacturer data:

Manufacturer name: **Supair SAS**  
 Representative: **Laurent Chiabaut**  
 Street: **Parc Altais / 34, rue Adrastée**  
 Post code place: **74650 Chavanod**  
 Country: **France**

Harness model: **PAP LIGHT**

### Sample data:

Name impact pad: **n/a**  
 Impact pad integrated: **Yes**  
 Impact pad type: **Airbag**  
 Weight of sample [kg]: **n/a**  
 Serial number: **2173LL0613RO**  
 Date of test: **11.07.2023**

### Atmosphere AGL:

Temp. [C°]	<b>25</b>
R.H. [%]	<b>51</b>
Press. [hPa]	<b>1007</b>

### Summary of Impact pad test <sup>(1)</sup>

Test id	–	Test configuration <sup>(2)</sup>	Max Peak of Impact [g] <sup>(3)</sup>	Duration at 38 [g] in [ms] <sup>(4)</sup>	Duration at 20 [g] in [ms] <sup>(5)</sup>	Diff. of test 1 and 2 [%] <sup>(6)</sup>	Result
P	V	Test sample attached to dummy in flying position, without emergency parachute	<b>28.85</b>	<b>0.00</b>	<b>18.33</b>	<b>-0.66</b>	<b>POSITIVE</b>
PR		Test sample attached to dummy in flying position, Including emergency parachute	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>	<b>n/a</b>	<b>n/a</b>

Manufacturer	Instrument	Type no	S/N	Validity Calibration
Burster/MTS	Accelerometer 100 g	89010-100	1263567	23.01.2024
JDC elec	Geos n°11 Skywatch	Geos n°11	Unit11	18.06.2025

The validation of this test report is given by the signature of the test manager on the Inspection Certificate no 94.20a or 94.20b

**Air Turquoise SA**, has thoroughly tested the sample mentioned above and certifies its conformity with the following standards:

**NfL 2-565-20 and EN1651:2018+A1:2020<sup>(7)</sup>**

<sup>(1)</sup> Calculated values in tests reports include the value minus the uncertainty (on safe side) / The uncertainty stated is the expanded uncertainty obtained by multiplying the standard uncertainty by the coverage factor  $k = 2$ . The value of the measurand lies within the assigned range of values with a probability of 95%

<sup>(2)</sup> The dummy is lifted minimum up to 1.65 m, and impact pad is mounted on. Where the impact occurs, measure distance from bottom of impact pad to ground

<sup>(3)</sup> Maximum peak of impact should be less or equal to 50 [g], <sup>(4)</sup> If any, the maximum duration in at 38 [g] should be less or equal to 7 [ms], <sup>(5)</sup> If any, the maximum duration in at 20 [g] should be less or equal to 25 [ms], <sup>(6)</sup> The test should be done twice, and the 2nd test the maximum peak should not differ more than 20% from the first test, maximum peak.

<sup>(7)</sup> This standard is NOT covered by accreditation D-IS-19457-01

This declaration must not be reproduced in part without the written permission of AIR TURQUOISE SA

Inspection certificate number: **PH\_412.2023**

Name impact pad: **n/a**

**Test results of Impact pad test**

	without emergency parachute		including emergency parachute	
	P1	P2	PR1	PR2
Maximum peak of impact [g]	<b>28.85</b>	<b>28.66</b>	<b>0.00</b>	<b>0.00</b>
Impact duration at +38 [g] in [ms]	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>
Impact duration at +20 [g] in [ms]	<b>18.33</b>	<b>18.33</b>	<b>0.00</b>	<b>0.00</b>
Uncertainty k=2 [g]	<b>1.66</b>	<b>1.65</b>	<b>0.00</b>	<b>0.00</b>
Diff. between test 1 and 2 [%]	<b>100.00</b>	<b>99.34</b>	<b>100.00</b>	<b>0.00</b>

